

Bryan W. Shaw, Ph.D., P.E., *Chairman*
Toby Baker, *Commissioner*
Jon Niermann, *Commissioner*
Richard A. Hyde, P.E., *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

November 1, 2016

Mr. Laurence P. Dahl
Eden Home, Inc.
631 Lakeview Boulevard
San Antonio, Texas 78216

Re: Edwards Aquifer Protection Program, Comal County

NAME OF PROJECT: **Eden Hill Lakeview Site Private Park**; Located approximately 0.25 northwest of the intersection of River Road and Lakeview Boulevard; New Braunfels, Texas

TYPE OF PLAN: Request for **Extension of Time to Commence Regulated Activities** Authorized by a **Water Pollution Abatement Plan (WPAP)**; 30 Texas Administrative Code (TAC) Chapter 213 Edwards Aquifer

Regulated Entity Number: RN107799876, Additional ID No. 13-14073102

Dear Mr. Dahl:

On October 1, 2016, the Texas Commission on Environmental Quality (TCEQ) received your request for an extension of time to commence regulated activities related to the above referenced Water Pollution Abatement Plan (WPAP) approval. The request has been reviewed for compliance with 30 TAC §213.4(h) and §213.13 which set forth the procedures for requesting an extension of time to commence regulated activities authorized by the approval and was found to be in general agreement with these procedures. The request for an extension to the term of approval for the referenced project is recommended for approval. A summary of the dates of approval and expiration are as follows:

Date of Original Approval:	October 22, 2014
Date of Expiration:	October 22, 2016
Date Extension Request Received	Date of Extension Expiration
October 1, 2016	April 22, 2017

The request and fee were received in compliance with 30 TAC §213.4(h) and §213.13. As indicated in the rules, an extension may not be granted if the proposed regulated activities or approved plan for the regulated activities have changed. As understood, there will be no changes or modifications to the originally approved plan. This request for extension expires on April 22, 2017. Should construction not commence before the end of the six (6) month

Mr. Laurence P. Dahl
November 1, 2016
Page 2

period, another request for extension would be required to keep the Edwards aquifer Protection Plan validated.

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality. If you have any questions or require additional information, please contact Lillian Butler of the Edwards Aquifer Protection Program of the San Antonio Regional Office at (210) 403-4026.

Sincerely,



Lynn Bumguardner, Water Section Manager
San Antonio Region
Texas Commission on Environmental Quality

LB/LB/eg

cc: Mr. Daryl P. Pawelek, P.E., Pawelek and Moy, Inc.
Mr. Robert Camareno, P.E., City of New Braunfels
Ms. Tom Hornseth, P.E., Comal County
Mr. H.L. Saur, Comal Trinity Groundwater Conservation District
Mr. Roland Ruiz, Edwards Aquifer Authority
TCEQ Central Records, Building F, MC 212

RECEIVED
DEC 14 2016
COUNTY ENGINEER



PAWELEK & MOY, INC.

CIVIL ENGINEERING & CONSULTING SERVICES

- RESIDENTIAL DEVELOPMENT
- SITE DEVELOPMENT
- PUBLIC WORKS
- UTILITIES

Edwards Aquifer Protection Plan Extension Request

RECEIVED


OCT 07 2016

COUNTY ENGINEER

Eden Hill – Lakeview Site
Private Park

New Braunfels, Texas

by
PAWELEK & MOY, INC.
Project No. 1401.01



Edwards Aquifer Protection Plan Extension Request

- Edwards Aquifer Application Cover Page (TCEQ-20705)
- Extension Request for an Edwards Aquifer Protection Plan (TCEQ-10260)
 - Attachment A - Approval Letter or Extension Approval
- Agent Authorization Form (TCEQ-0599), if application submitted by agent
- Application Fee Form (TCEQ-0574)
- Check Payable to the "Texas Commission on Environmental Quality"
- Core Data Form (TCEQ-10400)

Extension Request for an Edwards Aquifer Protection Plan

Texas Commission on Environmental Quality

Relating to 30 TAC §213.4(g) Effective June 1, 1999

Regulated Entity Information

If requested by an agent, attach the agent authorization form.

1. Regulated Entity Name: Eden Hill Lakeview Site Private Park
2. Customer (Applicant): Eden Home, Inc. (dba, as Eden Hill Communities)
Contact Person: Laurence P. Dahl
Entity: Eden Home, Inc. (dba, as Eden Hill Communities)
Mailing Address: 631 Lakeview Blvd.
City, State: New Braunfels, Texas Zip: 78130
Telephone: (830) 625-6291 Fax: (830) 620-7786
Email Address: larryd@edenhill.org
3. Agent/Representative (if any): Pawelek & Moy, Inc.
Contact Person: Daryl D. Pawelek
Entity: Pawelek & Moy, Inc.
Mailing Address: 130 W. Jahn St.
City, State: New Braunfels, Texas Zip: 78130
Telephone: (830) 629-2563 Fax: (830) 629-2564
Email Address: daryl.pawelek@sbcglobal.net

Extension Request

4. **Attachment A - Approval Letter or Extension Approval.** A copy of the last approval letter or the last approved extension is attached.
Date of letter: October 22, 2014
Expiration date: October 22, 2016
5. This extension request is submitted not earlier than sixty (60) days prior to the expiration date of an approved Edwards Aquifer protection plan or a previously approved extension.
6. A completed fee form is attached. The fee for a six-month extension of time is \$150.

Signature

Print Name of Customer/Agent: Daryl D. Pawelek

Date: 9/27/16

Signature of Customer/Agent:



ATTACHMENT A

Byron W. Shaw, Ph.D., P.E., *Chairman*
Tony Baker, *Commissioner*
Ch. Cowie, *Commissioner*
Richard A. Hyde, P.E., *Executive Director*

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

October 22, 2014

Mr. Laurence P. Dahl
Eden Home, Inc.
631 Lakeview Boulevard
San Antonio, Texas 78216

Re: Edwards Aquifer, Comal County

NAME OF PROJECT: Eden Hill Lakeview Site Private Park; Located approximately 0.25 northwest of the intersection of River Road and Lakeview Boulevard; New Braunfels, Texas

TYPE OF PLAN: Request for the Approval of a Water Pollution Abatement Plan; 30 Texas Administrative Code (TAC) Chapter 213

Investigation No. 1186365; Regulated Entity No. RN107799876; Additional ID No. 13-14073102

Dear Mr. Dahl:

The Texas Commission on Environmental Quality (TCEQ) has completed its review of the WPAP Application for the above-referenced project submitted to the San Antonio Regional Office by Pawelek and Moy, Inc. on behalf of Eden Home, Inc. on July 31, 2014. Final review of the WPAP was completed after additional material was received on September 25, October 2, and October 14, 2014. As presented to the TCEQ, the Temporary and Permanent Best Management Practices (BMPs) were selected and construction plans were prepared by a Texas Licensed Professional Engineer to be in general compliance with the requirements of 30 TAC Chapter 213. These planning materials were sealed, signed and dated by a Texas Licensed Professional Engineer. Therefore, based on the engineer's concurrence of compliance, the planning materials for construction of the proposed project and pollution abatement measures are hereby approved subject to applicable state rules and the conditions in this letter. The applicant or a person affected may file with the chief clerk a motion for reconsideration of the executive director's final action on this Edwards Aquifer Protection Plan. A motion for reconsideration must be filed no later than 23 days after the date of this approval letter. *This approval expires two (2) years from the date of this letter unless, prior to the expiration date, more than 10 percent of the construction has commenced on the project or an extension of time has been requested.*

PROJECT DESCRIPTION

The proposed commercial project will have an area of approximately 8.47 acres. It will include the construction of two parking areas, associated drives, sidewalks and pervious nature trails. The impervious cover will be 0.902 acres (10.65 percent). No wastewater is generated by this project.

PERMANENT POLLUTION ABATEMENT MEASURES

To prevent the pollution of stormwater runoff originating on-site or upgradient of the site and potentially flowing across and off the site after construction, one 50-foot (50') natural vegetative filter strip (VFS) and one 15' engineered VFS, designed using the TCEQ technical guidance document, Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices (2005), will be constructed to treat stormwater runoff. The required total suspended solids (TSS) treatment for this project is 810 pounds of TSS generated from the 0.902 acres of impervious cover. The approved measures meet the required 80 percent removal of the increased load in TSS caused by the project.

The 50' natural VFS shall remain in its natural state with a uniform slope of less than 10 percent, and the 15' engineered VFS's shall have a uniform slope of less than 20 percent and vegetated cover of at least 80 percent which will extend along the entire length of the contributing area and will be free of gullies or rills that can concentrate overland flow. The contributing area shall be relatively flat to evenly distribute runoff. The impervious cover in the direction of flow to the 15 foot VFS's shall not exceed 72 feet.

GEOLOGY

According to the geologic assessment included with the application, the site is located on the leached and collapsed members of the Person Formation. Four manmade features and two geologic features were identified and rated as non-sensitive. The San Antonio Regional Office site assessment conducted on September 12, 2014 revealed the site was generally as described in the application.

SPECIAL CONDITION

- I. The permanent pollution abatement measures shall be operational prior to use of the parking areas and drives.

STANDARD CONDITIONS

1. Pursuant to Chapter 7 Subchapter C of the Texas Water Code, any violations of the requirements in 30 TAC Chapter 213 may result in administrative penalties.
2. The holder of the approved Edwards Aquifer protection plan must comply with all provisions of 30 TAC Chapter 213 and all best management practices and measures contained in the approved plan. Additional and separate approvals, permits, registrations and/or authorizations from other TCEQ Programs (i.e., Stormwater, Water Rights, UIC) can be required depending on the specifics of the plan.
3. In addition to the rules of the Commission, the applicant may also be required to comply with state and local ordinances and regulations providing for the protection of water quality.

Prior to Commencement of Construction:

4. Within 60 days of receiving written approval of an Edwards Aquifer Protection Plan, the applicant must submit to the San Antonio Regional Office, proof of recordation of notice in the county deed records, with the volume and page number(s) of the county deed records of the county in which the property is located. A description of the property boundaries shall be included in the deed recordation in the county deed records. A suggested form (Deed

Recordation Affidavit, TCEQ-0625) that you may use to deed record the approved WPAP is enclosed.

5. All contractors conducting regulated activities at the referenced project location shall be provided a copy of this notice of approval. At least one complete copy of the approved WPAP and this notice of approval shall be maintained at the project location until all regulated activities are completed.
6. Modification to the activities described in the referenced WPAP application following the date of approval may require the submittal of a plan to modify this approval, including the payment of appropriate fees and all information necessary for its review and approval prior to initiating construction of the modifications.
7. The applicant must provide written notification of intent to commence construction, replacement, or rehabilitation of the referenced project. Notification must be submitted to the San Antonio Regional Office no later than 48 hours prior to commencement of the regulated activity. Written notification must include the date on which the regulated activity will commence, the name of the approved plan and program ID number for the regulated activity, and the name of the prime contractor with the name and telephone number of the contact person. The executive director will use the notification to determine if the approved plan is eligible for an extension.
8. Temporary erosion and sedimentation (E&S) controls, i.e., silt fences, rock berms, stabilized construction entrances, or other controls described in the approved WPAP, must be installed prior to construction and maintained during construction. Temporary E&S controls may be removed when vegetation is established and the construction area is stabilized. If a water quality pond is proposed, it shall be used as a sedimentation basin during construction. The TCEQ may monitor stormwater discharges from the site to evaluate the adequacy of temporary E&S control measures. Additional controls may be necessary if excessive solids are being discharged from the site.
9. All borings with depths greater than or equal to 20 feet must be plugged with non-shrink grout from the bottom of the hole to within three (3) feet of the surface. The remainder of the hole must be backfilled with cuttings from the boring. All borings less than 20 feet must be backfilled with cuttings from the boring. All borings must be backfilled or plugged within four (4) days of completion of the drilling operation. Voids may be filled with gravel.

During Construction:

10. During the course of regulated activities related to this project, the applicant or agent shall comply with all applicable provisions of 30 TAC Chapter 213, Edwards Aquifer. The applicant shall remain responsible for the provisions and conditions of this approval until such responsibility is legally transferred to another person or entity.
11. This approval does not authorize the installation of temporary aboveground storage tanks on this project. If the contractor desires to install a temporary aboveground storage tank for use during construction, an application to modify this approval must be submitted and approved prior to installation. The application must include information related to tank location and spill containment. Refer to Standard Condition No. 6, above.
12. If any sensitive feature (caves, solution cavities, sink holes, etc.) is discovered during construction, all regulated activities near the feature must be suspended immediately. The applicant or his agent must immediately notify the San Antonio Regional Office of the discovery of the feature. Regulated activities near the feature may not proceed until the executive director has reviewed and approved the methods proposed to protect the feature and the aquifer from

potentially adverse impacts to water quality. The plan must be sealed, signed, and dated by a Texas Licensed Professional Engineer.

13. No wells exist on site. All water wells, including injection, dewatering, and monitoring wells must be in compliance with the requirements of the Texas Department of Licensing and Regulation under Title 16 TAC Chapter 76 (relating to Water Well Drillers and Pump Installers) and all other locally applicable rules, as appropriate.
14. If sediment escapes the construction site, the sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50 percent. Litter, construction debris, and construction chemicals shall be prevented from becoming stormwater discharge pollutants.
15. Intentional discharges of sediment laden water are not allowed. If dewatering becomes necessary, the discharge will be filtered through appropriately selected best management practices. These may include vegetated filter strips, sediment traps, rock berms, silt fence rings, etc.
16. The following records shall be maintained and made available to the executive director upon request: the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
17. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, and construction activities will not resume within 21 days. When the initiation of stabilization measures by the 14th day is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable.

After Completion of Construction:

18. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the San Antonio Regional Office within 30 days of site completion.
19. The applicant shall be responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. The regulated entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred. A copy of the transfer of responsibility must be filed with the executive director through San Antonio Regional Office within 30 days of the transfer. A copy of the transfer form (TCEQ-10263) is enclosed.
20. Upon legal transfer of this property, the new owner(s) is required to comply with all terms of the approved Edwards Aquifer protection plan. If the new owner intends to commence any new regulated activity on the site, a new Edwards Aquifer protection plan that specifically addresses the new activity must be submitted to the executive director. Approval of the plan for the new regulated activity by the executive director is required prior to commencement of the new regulated activity.

Mr. Laurence P. Dahl


Page 5

October 22, 2014

21. An Edwards Aquifer protection plan approval or extension will expire and no extension will be granted if more than 50 percent of the total construction has not been completed within ten years from the initial approval of a plan. A new Edwards Aquifer protection plan must be submitted to the San Antonio Regional Office with the appropriate fees for review and approval by the executive director prior to commencing any additional regulated activities.
22. At project locations where construction is initiated and abandoned, or not completed, the site shall be returned to a condition such that the aquifer is protected from potential contamination.

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality. If you have any questions or require additional information, please contact Neal Denton of the Edwards Aquifer Protection Program of the San Antonio Regional Office at 210-403-4026.

Sincerely,



Lynn Bumguardner, Water Section Manager
San Antonio Region Office
Texas Commission on Environmental Quality

LMB/ND/eg

Enclosures: Deed Recordation Affidavit, Form TCEQ-0625
Change in Responsibility for Maintenance of Permanent BMPs, Form TCEQ-10263

cc: Mr. Daryl P. Pawelek, P.E., Pawelek and Moy, Inc.
Mr. Charlie Thomas, P.E., City of New Braunfels
Mr. Tom Hornseth, P.E., Comal County
Mr. Roland Ruiz, Edwards Aquifer Authority
TCEQ Central Records, Building F, MC 212

Agent Authorization Form
For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

I _____
Laurence P. Dahl
Print Name

_____ Executive Director/CEO
Title - Owner/President/Other

of _____
Eden Home, Inc. (dba, EdenHill Communities)
Corporation/Partnership/Entity Name

have authorized _____
Daryl D. Pawelek
Print Name of Agent/Engineer

of _____
Pawelek & Moy, Inc.
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

Laurence P. Dahl
Applicant's Signature


09/27/2016
Date

THE STATE OF Texas §

County of Comal §

BEFORE ME, the undersigned authority, on this day personally appeared Laurence P. Dahl known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 27th day of September, 2016.



Susan Harmer
NOTARY PUBLIC

Susan Harmer
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 3/16/19

Application Fee Form

Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: Eden Hill Lakeview Site Private Park

Regulated Entity Location: Located approximately 0.25 mi. northwest of River Road and Lakeview Blvd; New Braunfels, Texas

Name of Customer: Eden Home, Inc. (dba, as Eden Hill Communities)

Contact Person: Laurence P. Dahl

Phone: (830) 625-6291

Customer Reference Number (if issued): CN 600951248

Regulated Entity Reference Number (if issued): RN 107799876

Austin Regional Office (3373)

Hays

Travis

Williamson

San Antonio Regional Office (3362)

Bexar

Medina

Uvalde

Comal

Kinney

Application fees must be paid by check, certified check, or money order, payable to the Texas Commission on Environmental Quality. Your canceled check will serve as your receipt. This form must be submitted with your fee payment. This payment is being submitted to:

Austin Regional Office

San Antonio Regional Office

Mailed to: TCEQ - Cashier

Overnight Delivery to: TCEQ - Cashier

Revenues Section

12100 Park 35 Circle

Mail Code 214

Building A, 3rd Floor

P.O. Box 13088

Austin, TX 78753

Austin, TX 78711-3088

(512)239-0357

Site Location (Check All That Apply):

Recharge Zone

Contributing Zone

Transition Zone

Type of Plan	Size	Fee Due
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	Acres	\$
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	1 Each	\$ 150.00

Signature: 

Date: 9/27/16

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

<i>Project</i>	<i>Project Area in Acres</i>	<i>Fee</i>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

<i>Project</i>	<i>Cost per Linear Foot</i>	<i>Minimum Fee- Maximum Fee</i>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

<i>Project</i>	<i>Cost per Tank or Piping System</i>	<i>Minimum Fee- Maximum Fee</i>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

<i>Project</i>	<i>Fee</i>
Exception Request	\$500

Extension of Time Requests

<i>Project</i>	<i>Fee</i>
Extension of Time Request	\$150

BROADWAY BANK
800.531.7650
broadwaybank.com

88 2193/1140

19015

EDEN HOME, INC.
DBA EDENHILL COMMUNITIES
OPERATING ACCOUNT
631 LAKEVIEW BLVD.
NEW BRAUNFELS, TX 78130
(830) 625-6291

Account Number	20029251	Date	9/23/2016
Amount	\$150.00		

PAY One Hundred Fifty & No/100 *****
TO THE ORDER OF TEXAS COMMISSION
ON ENVIRONMENTAL QUALITY
P.O. BOX 13087
AUSTIN, TX 78711-3087



THIS DOCUMENT CONTAINS HEAT SENSITIVE INK. TOUCH OR PRESS HERE. RED IMAGE DISAPPEARS WITH HEAT.

⑆019015⑆ ⑆114021933⑆

⑆4100023867⑆



TCEQ Core Data Form

TCEQ Use Only

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input checked="" type="checkbox"/> Other EAPP Extension Request	
2. Customer Reference Number (if issued)	Follow this link to search for CN or RN numbers in Central Registry**	3. Regulated Entity Reference Number (if issued)
CN 600951248		RN 107799876

SECTION II: Customer Information

4. General Customer Information	5. Effective Date for Customer Information Updates (mm/dd/yyyy)		
<input checked="" type="checkbox"/> New Customer <input checked="" type="checkbox"/> Update to Customer Information <input type="checkbox"/> Change in Regulated Entity Ownership <input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)			
The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).			
6. Customer Legal Name (If an individual, print last name first: e.g.: Doe, John)		If new Customer, enter previous Customer below:	
7. TX SOS/CPA Filing Number	8. TX State Tax ID (11 digits)	9. Federal Tax ID (9 digits)	10. DUNS Number (if applicable)
11. Type of Customer:	<input checked="" type="checkbox"/> Corporation	<input type="checkbox"/> Individual	Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> State <input type="checkbox"/> Other	<input type="checkbox"/> Sole Proprietorship	<input type="checkbox"/> Other: _____	
12. Number of Employees		13. Independently Owned and Operated?	
<input type="checkbox"/> 0-20 <input type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher		<input type="checkbox"/> Yes <input type="checkbox"/> No	
14. Customer Role (Proposed or Actual) - as it relates to the Regulated Entity listed on this form. Please check one of the following:			
<input checked="" type="checkbox"/> Owner <input type="checkbox"/> Operator <input type="checkbox"/> Owner & Operator <input type="checkbox"/> Occupational Licensee <input type="checkbox"/> Responsible Party <input type="checkbox"/> Voluntary Cleanup Applicant <input type="checkbox"/> Other: _____			
15. Mailing Address:			

City	State	ZIP	ZIP + 4
16. Country Mailing Information (if outside USA)		17. E-Mail Address (if applicable)	
18. Telephone Number	19. Extension or Code	20. Fax Number (if applicable)	
() -		() -	

SECTION III: Regulated Entity Information

21. General Regulated Entity Information (If 'New Regulated Entity' is selected below this form should be accompanied by a permit application)	
<input type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information	
The Regulated Entity Name submitted may be updated in order to meet TCEQ Agency Data Standards (removal of organizational endings such as Inc, LP, or LLC).	
22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)	

23. Street Address of the Regulated Entity: (No PO Boxes)							
	City		State		ZIP		ZIP + 4
24. County							

Enter Physical Location Description if no street address is provided.

25. Description to Physical Location:							
26. Nearest City					State	Nearest ZIP Code	
27. Latitude (N) In Decimal:				28. Longitude (W) In Decimal:			
Degrees	Minutes	Seconds	Degrees	Minutes	Seconds		
29. Primary SIC Code (4 digits)		30. Secondary SIC Code (4 digits)		31. Primary NAICS Code (5 or 6 digits)		32. Secondary NAICS Code (5 or 6 digits)	
33. What is the Primary Business of this entity? (Do not repeat the SIC or NAICS description.)							
34. Mailing Address:							
	City		State		ZIP		ZIP + 4
35. E-Mail Address:							
36. Telephone Number			37. Extension or Code		38. Fax Number (if applicable)		
() -					() -		

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.

<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Waste Water	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

SECTION IV: Preparer Information

40. Name: Daryl D. Pawelek	41. Title: Project Engineer		
42. Telephone Number: (830) 629-2563	43. Ext./Code:	44. Fax Number: (830) 629-2564	45. E-Mail Address: daryl.pawelek@sbcglobal.net

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company: Pawelek & Moy, Inc.	Job Title: Project Engineer
Name (In Print): Daryl D. Pawelek	Phone: (830) 629-2563
Signature: 	Date: 9/27/16

Bryan W. Shaw, Ph.D., P.E., *Chairman*
Toby Baker, *Commissioner*
Zak Covar, *Commissioner*
Richard A. Hyde, P.E., *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

October 22, 2014

Mr. Laurence P. Dahl
Eden Home, Inc.
631 Lakeview Boulevard
San Antonio, Texas 78216

RECEIVED

NOV 05 2014

COUNTY ENGINEER

Re: Edwards Aquifer, Comal County

NAME OF PROJECT: Eden Hill Lakeview Site Private Park; Located approximately 0.25 northwest of the intersection of River Road and Lakeview Boulevard; New Braunfels, Texas

TYPE OF PLAN: Request for the Approval of a Water Pollution Abatement Plan; 30 Texas Administrative Code (TAC) Chapter 213

Investigation No. 1186365; Regulated Entity No. RN107799876; Additional ID No. 13-14073102

Dear Mr. Dahl:

The Texas Commission on Environmental Quality (TCEQ) has completed its review of the WPAP Application for the above-referenced project submitted to the San Antonio Regional Office by Pawelek and Moy, Inc. on behalf of Eden Home, Inc. on July 31, 2014. Final review of the WPAP was completed after additional material was received on September 25, October 2, and October 14, 2014. As presented to the TCEQ, the Temporary and Permanent Best Management Practices (BMPs) were selected and construction plans were prepared by a Texas Licensed Professional Engineer to be in general compliance with the requirements of 30 TAC Chapter 213. These planning materials were sealed, signed and dated by a Texas Licensed Professional Engineer. Therefore, based on the engineer's concurrence of compliance, the planning materials for construction of the proposed project and pollution abatement measures are hereby approved subject to applicable state rules and the conditions in this letter. The applicant or a person affected may file with the chief clerk a motion for reconsideration of the executive director's final action on this Edwards Aquifer Protection Plan. A motion for reconsideration must be filed no later than 23 days after the date of this approval letter. *This approval expires two (2) years from the date of this letter unless, prior to the expiration date, more than 10 percent of the construction has commenced on the project or an extension of time has been requested.*

PROJECT DESCRIPTION

The proposed commercial project will have an area of approximately 8.47 acres. It will include the construction of two parking areas, associated drives, sidewalks and pervious nature trails. The impervious cover will be 0.902 acres (10.65 percent). No wastewater is generated by this project.

PERMANENT POLLUTION ABATEMENT MEASURES

To prevent the pollution of stormwater runoff originating on-site or upgradient of the site and potentially flowing across and off the site after construction, one 50-foot (50') natural vegetative filter strip (VFS) and one 15' engineered VFS, designed using the TCEQ technical guidance document, Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices (2005), will be constructed to treat stormwater runoff. The required total suspended solids (TSS) treatment for this project is 810 pounds of TSS generated from the 0.902 acres of impervious cover. The approved measures meet the required 80 percent removal of the increased load in TSS caused by the project.

The 50' natural VFS shall remain in its natural state with a uniform slope of less than 10 percent, and the 15' engineered VFS's shall have a uniform slope of less than 20 percent and vegetated cover of at least 80 percent which will extend along the entire length of the contributing area and will be free of gullies or rills that can concentrate overland flow. The contributing area shall be relatively flat to evenly distribute runoff. The impervious cover in the direction of flow to the 15 foot VFS's shall not exceed 72 feet.

GEOLOGY

According to the geologic assessment included with the application, the site is located on the leached and collapsed members of the Person Formation. Four manmade features and two geologic features were identified and rated as non-sensitive. The San Antonio Regional Office site assessment conducted on September 12, 2014 revealed the site was generally as described in the application.

SPECIAL CONDITION

- I. The permanent pollution abatement measures shall be operational prior to use of the parking areas and drives.

STANDARD CONDITIONS

1. Pursuant to Chapter 7 Subchapter C of the Texas Water Code, any violations of the requirements in 30 TAC Chapter 213 may result in administrative penalties.
2. The holder of the approved Edwards Aquifer protection plan must comply with all provisions of 30 TAC Chapter 213 and all best management practices and measures contained in the approved plan. Additional and separate approvals, permits, registrations and/or authorizations from other TCEQ Programs (i.e., Stormwater, Water Rights, UIC) can be required depending on the specifics of the plan.
3. In addition to the rules of the Commission, the applicant may also be required to comply with state and local ordinances and regulations providing for the protection of water quality.

Prior to Commencement of Construction:

4. Within 60 days of receiving written approval of an Edwards Aquifer Protection Plan, the applicant must submit to the San Antonio Regional Office, proof of recordation of notice in the county deed records, with the volume and page number(s) of the county deed records of the county in which the property is located. A description of the property boundaries shall be included in the deed recordation in the county deed records. A suggested form (Deed

Recordation Affidavit, TCEQ-0625) that you may use to deed record the approved WPAP is enclosed.

5. All contractors conducting regulated activities at the referenced project location shall be provided a copy of this notice of approval. At least one complete copy of the approved WPAP and this notice of approval shall be maintained at the project location until all regulated activities are completed.
6. Modification to the activities described in the referenced WPAP application following the date of approval may require the submittal of a plan to modify this approval, including the payment of appropriate fees and all information necessary for its review and approval prior to initiating construction of the modifications.
7. The applicant must provide written notification of intent to commence construction, replacement, or rehabilitation of the referenced project. Notification must be submitted to the San Antonio Regional Office no later than 48 hours prior to commencement of the regulated activity. Written notification must include the date on which the regulated activity will commence, the name of the approved plan and program ID number for the regulated activity, and the name of the prime contractor with the name and telephone number of the contact person. The executive director will use the notification to determine if the approved plan is eligible for an extension.
8. Temporary erosion and sedimentation (E&S) controls, i.e., silt fences, rock berms, stabilized construction entrances, or other controls described in the approved WPAP, must be installed prior to construction and maintained during construction. Temporary E&S controls may be removed when vegetation is established and the construction area is stabilized. If a water quality pond is proposed, it shall be used as a sedimentation basin during construction. The TCEQ may monitor stormwater discharges from the site to evaluate the adequacy of temporary E&S control measures. Additional controls may be necessary if excessive solids are being discharged from the site.
9. All borings with depths greater than or equal to 20 feet must be plugged with non-shrink grout from the bottom of the hole to within three (3) feet of the surface. The remainder of the hole must be backfilled with cuttings from the boring. All borings less than 20 feet must be backfilled with cuttings from the boring. All borings must be backfilled or plugged within four (4) days of completion of the drilling operation. Voids may be filled with gravel.

During Construction:

10. During the course of regulated activities related to this project, the applicant or agent shall comply with all applicable provisions of 30 TAC Chapter 213, Edwards Aquifer. The applicant shall remain responsible for the provisions and conditions of this approval until such responsibility is legally transferred to another person or entity.
11. This approval does not authorize the installation of temporary aboveground storage tanks on this project. If the contractor desires to install a temporary aboveground storage tank for use during construction, an application to modify this approval must be submitted and approved prior to installation. The application must include information related to tank location and spill containment. Refer to Standard Condition No. 6, above.
12. If any sensitive feature (caves, solution cavities, sink holes, etc.) is discovered during construction, all regulated activities near the feature must be suspended immediately. The applicant or his agent must immediately notify the San Antonio Regional Office of the discovery of the feature. Regulated activities near the feature may not proceed until the executive director has reviewed and approved the methods proposed to protect the feature and the aquifer from

potentially adverse impacts to water quality. The plan must be sealed, signed, and dated by a Texas Licensed Professional Engineer.

13. No wells exist on site. All water wells, including injection, dewatering, and monitoring wells must be in compliance with the requirements of the Texas Department of Licensing and Regulation under Title 16 TAC Chapter 76 (relating to Water Well Drillers and Pump Installers) and all other locally applicable rules, as appropriate.
14. If sediment escapes the construction site, the sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50 percent. Litter, construction debris, and construction chemicals shall be prevented from becoming stormwater discharge pollutants.
15. Intentional discharges of sediment laden water are not allowed. If dewatering becomes necessary, the discharge will be filtered through appropriately selected best management practices. These may include vegetated filter strips, sediment traps, rock berms, silt fence rings, etc.
16. The following records shall be maintained and made available to the executive director upon request: the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
17. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, and construction activities will not resume within 21 days. When the initiation of stabilization measures by the 14th day is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable.

After Completion of Construction:

18. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the San Antonio Regional Office within 30 days of site completion.
19. The applicant shall be responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. The regulated entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred. A copy of the transfer of responsibility must be filed with the executive director through San Antonio Regional Office within 30 days of the transfer. A copy of the transfer form (TCEQ-10263) is enclosed.
20. Upon legal transfer of this property, the new owner(s) is required to comply with all terms of the approved Edwards Aquifer protection plan. If the new owner intends to commence any new regulated activity on the site, a new Edwards Aquifer protection plan that specifically addresses the new activity must be submitted to the executive director. Approval of the plan for the new regulated activity by the executive director is required prior to commencement of the new regulated activity.

Mr. Laurence P. Dahl


Page 5

October 22, 2014

21. An Edwards Aquifer protection plan approval or extension will expire and no extension will be granted if more than 50 percent of the total construction has not been completed within ten years from the initial approval of a plan. A new Edwards Aquifer protection plan must be submitted to the San Antonio Regional Office with the appropriate fees for review and approval by the executive director prior to commencing any additional regulated activities.
22. At project locations where construction is initiated and abandoned, or not completed, the site shall be returned to a condition such that the aquifer is protected from potential contamination.

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality. If you have any questions or require additional information, please contact Neal Denton of the Edwards Aquifer Protection Program of the San Antonio Regional Office at 210-403-4026.

Sincerely,



Lynn Bumguardner, Water Section Manager
San Antonio Region Office
Texas Commission on Environmental Quality

LMB/ND/eg

Enclosures: Deed Recordation Affidavit, Form TCEQ-0625
Change in Responsibility for Maintenance of Permanent BMPs, Form TCEQ-10263

cc: Mr. Daryl P. Pawelek, P.E., Pawelek and Moy, Inc.
Mr. Charlie Thomas, P.E., City of New Braunfels
Mr. Tom Hornseth, P.E., Comal County
Mr. Roland Ruiz, Edwards Aquifer Authority
TCEQ Central Records, Building F, MC 212










OWNER:
 EDEN HOME, INC.
 dbo, EDEN HILL COMMUNITIES
 631 LAKEVIEW BLVD
 NEW BRAUNFELS, TX 78130

SITE PLAN FOR
EDENHILL COMMUNITIES - PRIVATE PARK
 NEW BRAUNFELS, TEXAS

EDEN HILL LAKEVIEW SITE- PRIVATE PARK PERMANENT BEST MANAGEMENT PRACTICE SUMMARY 8.47 ACRE SITE

Watershed Area	Permanent BMP	Drainage Area (Acres)	Imp. Cover (Acres)	Target TSS Removal (lb/yr)	TSS Removal Provided (lb/yr)
A(Onsite)	Vegetative Filter Strips	1.050	0.552	495	495
A(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
B1	Uncaptured	0.530	0.000	0	0
B2	Vegetative Filter Strips	0.310	0.136	122	122
C1	Uncaptured	0.610	0.000	0	0
C2	Vegetative Filter Strips	0.490	0.172	154	154
C3(Onsite)	Vegetative Filter Strips	0.030	0.014	13	13
C3(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
F	Uncaptured	5.450	0.000	0	0
Total		8.510	0.902	810	810

Notes:
 1. Uncaptured area without impervious cover, no treatment necessary



- ### LEGEND
- S.F.** SILT FENCE
 - LIMITS OF AREA TO BE DISTURBED
 - [Pattern] ROCK BERM
 - [Pattern] GABION MATTRESS (VELOCITY CONTROL)
 - [Pattern] ROCK RIPRAP (VELOCITY CONTROL)
 - [Pattern] PROPOSED VEGETATIVE FILTER
 - [Pattern] PROPOSED PAD
 - [Pattern] PROPOSED CONCRETE
 - [Pattern] TEMPORARY STABILIZED CONSTRUCTION ENTRANCE/EXIT
 - [Symbol] CONCRETE WASHOUT
 - [Arrow] EXISTING FLOW DIRECTION
 - EXISTING CONTOURS
 - PROPOSED CONTOURS
 - PROPERTY LINE
 - S-#** POTENTIAL RECHARGE FEATURE (PRF)
 - KeP** EDWARDS PERSON LIMESTONE
 - Kkm** NAVARRO AND TAYLOR GROUPS, UNDIVIDED
 - [Symbol] FAULT

IMPERVIOUS COVER SUMMARY

IMPERVIOUS COVER OF PROJECT SITE	Sq. Ft.	Sq. Ft./Acre	Acres
STRUCTURES/ROOFTOPS	0	+ 43,560 =	0.00
PAVING/DRIVES/PADS/SIDEWALKS	39,280	+ 43,560 =	0.90
TOTAL IMPERVIOUS COVER	39,280	+ 43,560 =	0.90

TOTAL IMPERVIOUS COVER ÷ TOTAL ACREAGE x 100 = 10.63 %

TOTAL PROJECT SITE ACREAGE = 8.47 AC.


NOTES:

- SEE DRAINAGE AREA MAP SHEET D-1 FOR OVERALL DRAINAGE AREAS.

SOIL STABILIZATION NOTE:
 IN ALL AREAS TO BE DISTURBED OUTSIDE OF THE LIMITS OF PAVING, SIDEWALKS, LANDSCAPING, ETC., AND FOR THE ENGINEERED VEGETATIVE FILTER STRIPS, VEGETATIVE STABILIZATION IN ACCORDANCE WITH RG-348 COMPLYING WITH THE EDWARDS AQUIFER RULES, ITEM 1.3.8-TEMPORARY VEGETATION, ITEM 1.3.9-BLANKETS AND MATTING, ITEM 1.3.10-HYDRAULIC MULCH AND/OR ITEM 1.3.11 SOD SHALL BE IMPLEMENTED. THE AREAS TO BE VEGETATED SHALL BE WATERED SUFFICIENTLY TO ESTABLISH 70% STABILIZATION.

VELOCITY CONTROL NOTE:
 AT THE POINT WHERE PROPOSED DRAINAGE PIPES OUTFALL AND THE ON THE DOWNSTREAM SIDE OF THE DETENTION POND OUTFALLS, A VELOCITY CONTROL PROCEDURE UTILIZING HEAVY ROCK RIPRAP (TYPE 'R' PER TxDOT ITEM 432) OR GABION MATTRESS (PER TxDOT ITEM 459) SHALL BE USED TO DISSIPATE THESE FLOWS (SEE DETAILS ON SHEET S2). THESE APPLICATIONS SHALL REMAIN IN PLACE AND NOT BE REMOVED UPON COMPLETION OF THE CONSTRUCTION ACTIVITIES.

FLOODPLAIN NOTE:
 ACCORDING TO FEMA FIRM MAP PANEL No. 48091C0435F, EFFECTIVE DATE 9/2/2009, A PORTION OF THE PROJECT SITE LIES WITHIN THE 100 YR FLOODPLAIN.



F:\1401.01 - Eden Hills Parking.dwg 2014/10/13 11:31am Administrator

REVISIONS

DATE	DESCRIPTION
9/24/14	ADDRESSED TCEQ COMMENTS 9/12/2014
10/01/14	ADDRESSED TCEQ COMMENTS 9/25/2014
10/13/14	ADDRESSED TCEQ COMMENTS 10/10/2014

DRAWN BY: D.G. III
 CHECKED BY: J.J.M.
 DATE: JULY 2014
 JOB NO.: 1401.01

Bryan W. Shaw, Ph.D., *Chairman*
Toby Baker, *Commissioner*
Zak Covar, *Commissioner*
Richard A. Hyde, P.E., *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

August 1, 2014

RECEIVED

AUG 06 2014

COUNTY ENGINEER

Mr. Thomas H. Hornseth, P.E.
Comal County Engineer
195 David Jonas Drive
New Braunfels TX 78132-3710

Re: Edwards Aquifer, Comal County
PROJECT NAME: **Eden Hill** – Lakeview Site private park, located on the south side of Lakeview Boulevard 0.25 mi north of River Road, New Braunfels, Texas

PLAN TYPE: Application for Approval of **Water Pollution Abatement Plan (WPAP)** 30 Texas Administration Code (TAC) Chapter 213; Edwards Aquifer Protection Program
EAPP Additional ID: 13-14073101

Dear Mr. Hornseth:

The referenced application is being forwarded to you pursuant to the Edwards Aquifer Rules. The Texas Commission on Environmental Quality (TCEQ) is required by 30 TAC Chapter 213 to provide copies of all applications to affected incorporated cities and underground water conservation districts for their comments prior to TCEQ approval. More information regarding this project may be obtained from the TCEQ Central Registry website at http://www.tceq.state.tx.us/permitting/central_registry/.

Please forward your comments to this office by September 1, 2014.

The Texas Commission on Environmental Quality appreciates your assistance in this matter and your compliance efforts to ensure protection of the State's environment. If you or members of your staff have any questions regarding these matters, please feel free to contact the San Antonio Region Office at (210) 490-3096.

Sincerely

A handwritten signature in blue ink, appearing to read "Todd Jones".

Todd Jones
Water Section Work Leader
San Antonio Regional Office

TJ/eg



PAWELEK & MOY, INC.

CIVIL ENGINEERING & CONSULTING SERVICES

- RESIDENTIAL DEVELOPMENT
- SITE DEVELOPMENT
- PUBLIC WORKS
- UTILITIES

Water Pollution Abatement Plan

Eden Hill – Lakeview Site Private Park

TCEQ-R13

JUL 31 2014

SAN ANTONIO

New Braunfels, Texas 78130

by
Pawelek & Moy, Inc.

Job No. 1401.01



Daryl D. Pawelek, P.E.
7-30-14

July 2014

RECEIVED

AUG 06 2014

COUNTY ENGINEER

Water Pollution Abatement Plan Checklist

- X General Information Form (*TCEQ-0587*)
 - ATTACHMENT A - Road Map
 - ATTACHMENT B - USGS / Edwards Recharge Zone Map
 - ATTACHMENT C - Project Description

- X Geologic Assessment Form (*TCEQ-0585*)
 - ATTACHMENT A - Geologic Assessment Table (*TCEQ-0585-Table*)
 - Comments to the Geologic Assessment Table
 - ATTACHMENT B - Soil Profile and Narrative of Soil Units
 - ATTACHMENT C - Stratigraphic Column
 - ATTACHMENT D - Narrative of Site Specific Geology
 - Site Geologic Map(s)
 - Table or list for the position of features' latitude/longitude (if mapped using GPS)

- X Water Pollution Abatement Plan Application Form (*TCEQ-0584*)
 - ATTACHMENT A - Factors Affecting Water Quality
 - ATTACHMENT B - Volume and Character of Stormwater
 - ATTACHMENT C - Suitability Letter from Authorized Agent (if OSSF is proposed)
 - ATTACHMENT D - Exception to the Required Geologic Assessment (if requesting an exception)
 - Site Plan

- X Temporary Stormwater Section (*TCEQ-0602*)
 - ATTACHMENT A - Spill Response Actions
 - ATTACHMENT B - Potential Sources of Contamination
 - ATTACHMENT C - Sequence of Major Activities
 - ATTACHMENT D - Temporary Best Management Practices and Measures
 - ATTACHMENT E - Request to Temporarily Seal a Feature, if sealing a feature
 - ATTACHMENT F - Structural Practices
 - ATTACHMENT G - Drainage Area Map
 - ATTACHMENT H - Temporary Sediment Pond(s) Plans and Calculations
 - ATTACHMENT I - Inspection and Maintenance for BMPs
 - ATTACHMENT J - Schedule of Interim and Permanent Soil Stabilization Practices

- X Permanent Stormwater Section (*TCEQ-0600*)
 - ATTACHMENT A - 20% or Less Impervious Cover Waiver, if project is multi-family residential, a school, or a small business and 20% or less impervious cover is proposed for the site
 - ATTACHMENT B - BMPs for Upgradient Stormwater
 - ATTACHMENT C - BMPs for On-site Stormwater
 - ATTACHMENT D - BMPs for Surface Streams
 - ATTACHMENT E - Request to Seal Features (if sealing a feature)
 - ATTACHMENT F - Construction Plans
 - ATTACHMENT G - Inspection, Maintenance, Repair and Retrofit Plan
 - ATTACHMENT H - Pilot-Scale Field Testing Plan, if BMPs not based on *Complying with the Edwards Aquifer Rules: Technical Guidance for BMPs*
 - ATTACHMENT I - Measures for Minimizing Surface Stream Contamination

- X Agent Authorization Form (*TCEQ-0599*), if application submitted by agent

- X Application Fee Form (*TCEQ-0574*)

- X Check Payable to the "Texas Commission on Environmental Quality"

- X Core Data Form (*TCEQ-10400*)

General Information Form
For Regulated Activities on the
Edwards Aquifer Recharge and Transition Zones
and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B)
Effective June 1, 1999

REGULATED ENTITY NAME: Eden Hill - Lakeview Site
COUNTY: Comal STREAM BASIN: Tributary of
Blieder's Creek

EDWARDS AQUIFER: RECHARGE ZONE
 TRANSITION ZONE

PLAN TYPE: WPAP AST EXCEPTION
 SCS UST MODIFICATION

CUSTOMER INFORMATION

1. Customer (Applicant):

Contact Person: Laurence P. Dahl
Entity: Eden Home, Inc. (dba, as Eden Hills Communities)
Mailing Address: 631 Lakeview Blvd.
City, State: New Braunfels, Texas Zip: 78130-4098
Telephone: (830) 625-6291 FAX: (830) 620-7786

Agent/Representative (If any):

Contact Person: Daryl D. Pawelek
Entity: Pawelek & Moy, Inc.
Mailing Address: 130 W. Jahn St.
City, State: New Braunfels, Texas Zip: 78130-7640
Telephone: (830) 629-2563 FAX: (830) 629-2564

2. This project is inside the city limits of New Braunfels.
 This project is outside the city limits but inside the ETJ (extra-territorial jurisdiction) of _____.
 This project is not located within any city's limits or ETJ.

3. The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

Approximately 0.25 miles northwest of the intersection of River Road and Lakeview Blvd. on the south side of Lakeview Blvd.

4. **ATTACHMENT A - ROAD MAP.** A road map showing directions to and the location of the project site is attached at the end of this form.
5. **ATTACHMENT B - USGS / EDWARDS RECHARGE ZONE MAP.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached behind this sheet. The map(s) should clearly show:

- Project site.
- USGS Quadrangle Name(s).
- Boundaries of the Recharge Zone (and Transition Zone, if applicable).
- Drainage path from the project to the boundary of the Recharge Zone.

6. Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment. **The TCEQ must be able to inspect the project site or the application will be returned.**
7. **ATTACHMENT C - PROJECT DESCRIPTION.** Attached at the end of this form is a detailed narrative description of the proposed project.
8. Existing project site conditions are noted below:
- Existing commercial site
 - Existing industrial site
 - Existing residential site
 - Existing paved and/or unpaved roads
 - Undeveloped (Cleared)
 - Undeveloped (Undisturbed/Uncleared)
 - Other: _____

PROHIBITED ACTIVITIES

9. I am aware that the following activities are prohibited on the **Recharge Zone** and are not proposed for this project:
- (1) waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
 - (2) new feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
 - (3) land disposal of Class I wastes, as defined in 30 TAC §335.1;
 - (4) the use of sewage holding tanks as parts of organized collection systems; and
 - (5) new municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
10. N/A I am aware that the following activities are prohibited on the **Transition Zone** and are not proposed for this project:
- (1) waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);
 - (2) land disposal of Class I wastes, as defined in 30 TAC §335.1; and
 - (3) new municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

ADMINISTRATIVE INFORMATION

11. The fee for the plan(s) is based on:
- For a Water Pollution Abatement Plan and Modifications, the total acreage of the site where regulated activities will occur.
 - For an Organized Sewage Collection System Plans and Modifications, the total linear

- ___ footage of all collection system lines.
- ___ For a UST Facility Plan or an AST Facility Plan, the total number of tanks or piping systems.
- ___ A request for an exception to any substantive portion of the regulations related to the protection of water quality.
- ___ A request for an extension to a previously approved plan.

12. Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

- ___ TCEQ cashier
- ___ Austin Regional Office (for projects in Hays, Travis, and Williamson Counties)
- X San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

13. X Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

14. X No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **GENERAL INFORMATION FORM** is hereby submitted for TCEQ review. The application was prepared by:

Daryl D. Pawelek

Print Name of Customer/Agent




Signature of Customer/Agent

7-30-14

Date

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282.



LOCATION MAP

SCALE: 1" = 2000'

**ATTACHMENT A
ROAD MAP**




PAWELEK & MOY, INC.



CIVIL ENGINEERING & CONSULTING SERVICES
 130 W. Jahn Street tel: (830) 629-2563
 New Braunfels, Texas 78130 fax: (830) 629-2564

TECHNICIAN:	D.G.III	DATE:	JUNE 2014
JOB NO.	1401.01	SHEET:	R1

ATTACHMENT B
USGS/EDWARDS RECHARGE ZONE MAP





Produced by the United States Geological Survey
 Revised in cooperation with the Texas Water Development Board
 Control by USGS, NOS/NOAA, and USCE
 Compiled by the Army Map Service by photogrammetric methods
 from aerial photographs taken 1956. Field checked 1958
 Revised from aerial photographs taken 1966. Field checked 1967
 Map edited 1968
 Projection and 10,000-foot grid ticks: Texas coordinate
 system, south central zone (Lambert conformal conic)
 1000-meter Universal Transverse Mercator grid, zone 14
 1927 North American Datum
 To place on the predicted North American Datum 1983
 move the projection lines 26 meters south and
 28 meters east as shown by dashed corner ticks
 Fine red dashed lines indicate selected fence and field lines
 generally visible on aerial photographs. This information is unclassified



ROAD CLASSIFICATION
 Primary highway, hard surface Light-duty road, hard or improved surface
 Secondary highway, hard surface Unimproved road
 Interstate Route U. S. Route State Route

QUADRANGLE LOCATION
 TEXAS
 2898-413
TCEQ-R13 NEW BRAUNFELS WEST, TEX.
 29098-F2-TF-024
 JUL 31 2014
SAN ANTONIO 1988
 DMA 6343 II NW-SERIES V82

Produced by the United States Geological Survey in
 cooperation with the Defense Mapping Agency
 Control by USGS and NOS/NOAA and USCE
 Compiled from aerial photographs taken 1966. Revisions in purple
 and woodblock compiled from aerial photographs taken 1988 and
 other sources and has been field checked. Map edited 1984
 Conflicts may exist between some updated features and previously
 mapped contours
 North American Datum of 1927 (NAD 27). Projection and
 10,000-foot ticks: Texas Coordinate System, south central zone
 (Lambert Conformal Conic)
 Blue 1000-meter Universal Transverse Mercator ticks, zone 14
 North American Datum of 1983 (NAD 83) is shown by dashed
 corner ticks. The values of the shift between NAD 27 and NAD 83
 for 7.5-minute intersections are obtainable from National Geodetic
 Survey NADCON software



ROAD CLASSIFICATION
 Primary highway, hard surface Light-duty road, hard or improved surface
 Secondary highway, hard surface Unimproved road
 Interstate Route U. S. Route State Route

QUADRANGLE LOCATION
 TEXAS
 2898-414
 NEW BRAUNFELS EAST, TEX.
 29098-F1-TF-024
 1988
 REVISÉD 1994
 DMA 6343 II NE-SERIES V82

ATTACHMENT "C"
PROJECT DESCRIPTION

This 8.47 acre site is located approximately 0.25 miles northwest of the intersection of River Road and Lakeview Blvd. on the south side of Lakeview Blvd. across the street from the existing Eden Hill Communities in New Braunfels. The existing site is undeveloped and generally drains from Lakeview Blvd. to the rear of the property. The project site is located in the Blieder's Creek drainage basin and a portion of the site is located in the FEMA 100 yr. flood plain according to FEMA FIRM Map 48091C0435F (effective 09/02/2009).

The purpose of this project is develop a private park on this 8.47 acre site and to construct two parking areas with associated drives, sidewalks and pervious nature trails. The proposed total impervious cover associated with this site is 0.90 acres (10.63%). 0.59 acres of impervious cover will be treated by 15 ft. wide Engineered Vegetative Filter Strips and 0.31 acres will treated by a Natural 50 ft. wide Vegetative Filter Strip in accordance with the TCEQ's RG-348.

GEOLOGIC SITE ASSESSMENT

PREPARED BY

FROST GEOSCIENCES

FOR

EDEN HILL - LAKEVIEW SITE

Geologic Site Assessment (WPAP)

Eden Hill - Lakeview Site

+/- 8.5 Acres

New Braunfels, Texas

Frost Geosciences, Inc.

PROJECT No.: FGS-E14102

JANUARY 13, 2014

Prepared exclusively for

Eden Hill

631 Lakeview Boulevard

New Braunfels, Texas 78130

Frost Geosciences

Geotechnical • Construction Materials

Geologic • Environmental

13402 Western Oak New Braunfels, Texas 78259 Phone: (210) 372-1315 Fax: (210) 372-1318





13402 Western Oak
New Braunfels, Texas 78259
Phone (210) 372-1315
Fax (210) 372-1318
www.frostgeosciences.com
SDVOSB VBE DIBE SBE
TBPE Firm Registration # F-9227
TBPE Firm Registration # 50040

January 13, 2014

Eden Hill
631 Lakeview Boulevard
New Braunfels, Texas 78130

Attn: Mr. Laurence Dahl, CEO


Re: Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Eden Hill - Lakeview Site
+/- 8.5 Acres
New Braunfels, Texas

Frost GeoSciences, Inc. Control # FGS-EI4102

Dear Sir:

Attached is a copy of the Geologic Assessment Report completed for the above referenced project site as it relates to 30 TAC §213.5(b)(3), effective June 1, 1999. Our investigation was conducted and this report was prepared in general accordance with the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04). The results of our investigation, along with any recommendations for Best Management Practices (BMP's), are provided in the following report.

If you have any questions regarding this report, or if Frost GeoSciences, Inc. may be of additional assistance to you on this project, please feel free to call our office. It has been a pleasure to work with you and we wish to thank you for the opportunity to be of service to you on this project. We look forward to being of continued service.



Sincerely,
Frost GeoSciences, Inc.

Chris Wickman
Chris Wickman, P.G.
Senior Geologist

Distribution: (6) Eden Hill

Table of Contents

GEOLOGIC ASSESSMENT FORM..... 1

STRATIGRAPHIC COLUMN 3

GEOLOGIC ASSESSMENT TABLE 4

LOCATION 5

METHODOLOGY 5

RESEARCH & OBSERVATIONS 6

 7.5 Minute Quadrangle Map Review 6

 Recharge/Transition Zone 6

 100-Year Floodplain 7

 Soils 7

 Narrative Description of the Site Geology 8

BEST MANAGEMENT PRACTICES 11

DISCLAIMER 11

REFERENCES 12

APPENDIX

A: Site Location Figures

 Figure 1: Site Plan

 Figure 2: Street Map

 Figure 3: USGS Topographic Map

 Figure 4: Official Edwards Aquifer Recharge Zone Map

 Figure 5: FEMA Flood Map

 Figure 6: USDA Soil Survey Aerial Photograph, 1"=500'

 Figure 7A: U.S. Geological Survey, Water Resources Investigation # 4030-95

 Figure 7B: Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle

 Figure 8: 2012 Aerial Photograph with PRFs, 1"=200'

 Figure 9: 2012 Aerial Photograph, 1"=500'

B: Site Photographs

C: Site Geologic Map

Geologic Assessment
 For Regulated Activities
 on The Edwards Aquifer Recharge/transition Zones
 and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

REGULATED ENTITY NAME: Eden Hill - Lakeview Site (+/-8.5 Acres)

TYPE OF PROJECT: WPAP AST SCS UST

LOCATION OF PROJECT: Recharge Zone Transition Zone Contributing Zone within the Transition Zone

PROJECT INFORMATION

1. Geologic or manmade features are described and evaluated using the attached **GEOLOGIC ASSESSMENT TABLE**.
2. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (*Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986*). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Soil Units, Infiltration Characteristics & Thickness		
Soil Name	Group*	Thickness (feet)
Eckrant-Rock Complex	D	0.5-1.5
Comfort-Rock Outcrop Complex	D	0.5-1.5

* Soil Group Definitions (Abbreviated)

A. Soils having a high infiltration rate when thoroughly wetted.

B. Soils having a moderate infiltration rate when thoroughly wetted.

C. Soils having a slow infiltration rate when thoroughly wetted.

D. Soils having a very slow infiltration rate when thoroughly wetted.

3. A **STRATIGRAPHIC COLUMN** is attached at the end of this form that shows formations, members, and thicknesses. The outcropping unit should be at the top of the stratigraphic column.
4. A **NARRATIVE DESCRIPTION OF SITE SPECIFIC GEOLOGY** is attached at the end of this form. The description must include a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure, and karst characteristics of the site.
5. Appropriate **SITE GEOLOGIC MAP(S)** are attached:

The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1" : 400'

Applicant's Site Plan Scale	1" = <u>40</u> '
Site Geologic Map Scale	1" = <u>40</u> '
Site Soils Map Scale (if more than 1 soil type)	1" = <u>500</u> '

6. Method of collecting positional data:

- Global Positioning System (GPS) technology.
- Other method(s): 2012 Aerial Photo
- 7. The project site is shown and labeled on the Site Geologic Map.
- 8. Surface geologic units are shown and labeled on the Site Geologic Map.
- 9. Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
 Geologic or manmade features were not discovered on the project site during the field investigation.
- 10. The Recharge Zone boundary is shown and labeled, if appropriate.
- 11. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.):
 There are ___ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)
 The wells are not in use and have been properly abandoned.
 The wells are not in use and will be properly abandoned.
 The wells are in use and comply with 16 TAC Chapter 76.
 There are no wells or test holes of any kind known to exist on the project site.


ADMINISTRATIVE INFORMATION

- 12. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

Date(s) Geologic Assessment was performed: January 9, 2014
 Date(s)

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Chris Wickman, P.G.
 Print Name of Geologist



(210) 372-1315
 Telephone

(210) 372-1318
 Fax

Chris Wickman
 Signature of Geologist

January 13, 2014
 Date

Representing: Frost GeoSciences, Inc.
 (Name of Company)

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282

Stratigraphic Column

[Hydrogeologic subdivisions modified from Maclay and Small (1976); groups, formations, and members modified from Rose (1972); lithology modified from Dunham (1962); and porosity type modified from Choquette and Pray (1970). CU, confining unit; AQ, aquifer]

Hydrogeologic subdivision	Group, formation, or member	Hydro-logic function	Thickness (feet)	Lithology	Field identification	Cavern development	Porosity/permeability type			
Upper Cretaceous	Eagle Ford Group	CU	30 - 50	Brown, flaggy shale and argillaceous limestone	Thin flagstones; petroliiferous	None	Primary porosity lost/ low permeability			
	Buda Limestone	CU	40 - 50	Buff, light gray, dense mudstone	Porcellaneous limestone with calcite-filled veins	Minor surface karst	Low porosity/low permeability			
	Del Rio Clay	CU	40 - 50	Blue-green to yellow-brown clay	Fossiliferous; <i>Ilymatogyra arietina</i>	None	None/primary upper confining unit			
Lower Cretaceous	Edwards aquifer	Edwards Group	Person Formation	Georgetown Formation	Karst AQ; not karst CU	2 - 20	Reddish-brown, gray to light tan marly limestone	Marker fossil: <i>Waconella wacoensis</i>	None	Low porosity/low permeability
				Cycle and marine members, undivided	AQ	80 - 90	Mudstone to packstone; <i>milolid</i> grainstone; chert	Thin graded cycles; massive beds to relatively thin beds; crossbeds	Many subsurface; might be associated with earlier karst development	Laterally extensive; both fabric and not fabric/water-yielding
				Leached and collapsed members, undivided	AQ	70 - 90	Crystalline limestone; mudstone to grainstone; chert; collapsed breccia	Bioturbated iron-stained beds separated by massive limestone beds; stromatolitic limestone	Extensive lateral development; large rooms	Majority not fabric/one of the most permeable
				Regional dense member	CU	20 - 24	Dense, argillaceous mudstone	Wispy iron-oxide stains	Very few; only vertical fracture enlargement	Not fabric/low permeability; vertical barrier
				Grainstone member	AQ	50 - 60	<i>Milolid</i> grainstone; mudstone to wackestone; chert	White crossbedded grainstone	Few	Not fabric/ recrystallization reduces permeability
				Kirschberg evaporite member	AQ	50 - 60	Highly altered crystalline limestone; chalky mudstone; chert	Boxwork voids, with neospar and travertine frame	Probably extensive cave development	Majority fabric/one of the most permeable
				Dolomitic member	AQ	110 - 130	Mudstone to grainstone; crystalline limestone; chert	Massively bedded light gray, <i>Toucasia</i> abundant	Caves related to structure or bedding planes	Mostly not fabric; some bedding plane-fabric/water-yielding
				Basal nodular member	Karst AQ; not karst CU	50 - 60	Shaly, nodular limestone; mudstone and <i>milolid</i> grainstone	Massive, nodular and mottled, <i>Exogyra texana</i>	Large lateral caves at surface; a few caves near Cibolo Creek	Fabric; stratigraphically controlled/large conduit flow at surface; no permeability in subsurface
				Lower confining unit	Upper member of the Glen Rose Limestone	CU; evaporite beds AQ	350 - 500	Yellowish tan, thinly bedded limestone and marl	Stair-step topography; alternating limestone and marl	Some surface cave development

LOCATION

The Site consists of approximately 8.5 acres of wooded land located along the south side of Lakeview Boulevard, immediately southeast of the intersection of Lakeview Boulevard and Lakeview Circle in New Braunfels, Texas. An overall view of the area is shown on copies of the site plan, a street map, the U.S.G.S. Topographic Map, the Official Edwards Aquifer Recharge Zone Map, the FIRM Map, the 1973 USDA Aerial Photo at a scale of 1"=500', a geologic map, a 2012 Aerial Photo at a scale of 1"=200', and a 2012 Aerial Photo at a scale of 1"=500', presented on Figures 1 through 9 in Appendix A.

METHODOLOGY

The Geologic Assessment was performed by Mr. Chris Wickman, P.G., with Frost GeoSciences, Inc. Mr. Wickman is a Licensed Professional Geoscientist in the State of Texas (License # 10403).

Frost GeoSciences, Inc. researched the geology of the area surrounding the intersection of Lakeview Boulevard and Lakeview Circle in north New Braunfels, Texas. The research included, but was not limited to, the Bureau of Economic Geology-Geologic Atlas of Texas, San Antonio Sheet, the Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle, the U.S.G.S. Water-Resources Investigations Report 94-4117, the U.S.D.A. Soil Survey of Comal and Hays Counties, Texas, FEMA maps, Official Edwards Aquifer Recharge Zone Maps, and the U.S.G.S. 7.5 Minute Quadrangle Maps.

After reviewing the available information, a field investigation was performed to identify any geologic or man made potential recharge features (PRFs). A transect spacing of approximately 50 feet, or less depending on vegetation thickness, was used to inspect the project area. A 2012 aerial photograph, in conjunction with a hand held Garmin GPS 72H Global Positioning System with an Estimated Potential Error ranging from 15 to 18 feet, was used to navigate around the property and identify the locations of PRFs, as recommended in the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04). The locations of any

PRFs observed in the field were marked with blue and white flagging. The flagging is numbered with the same PRF I.D. # that is used on the Site Geologic Map. The Site Geologic Map, indicating the limits of the project site, and the locations of potential recharge features and rock outcrops noted on the project site, is included in Appendix C. A copy of a 2012 Aerial Photograph at an approximate scale of 1"=200' indicating the limits of the project site, and the locations of potential recharge features and rock outcrops noted on the project site, is included on Figure 8 in Appendix A. The Geologic Assessment Form TCEQ-0585, (Rev. 10-1-10), Stratigraphic Column, and the Geologic Assessment Table have been filled with the appropriate information for this project site and are included on pages 1-4 of this report.

RESEARCH & OBSERVATIONS

7.5 Minute Quadrangle Map Review

According to the U.S.G.S. 7.5 Minute Quadrangle Map, New Braunfels West, Texas (1988), the elevation across the project site range from 630 to 730 feet above mean sea level. The Site is located on a slight topographic high and sloping to the southeast toward the Comal River located south of the of the project site. The general direction of area runoff is to the southeast into the above mentioned Comal River. A residential subdivision is located on the adjoining property southwest of the project site. Lakeview Boulevard is located immediately north of the project site followed by Eden Hill Communities Independent and Assisted Living. An apparent warehouse building was located southeast of the project site. The Guadalupe River is located east of the project site. A copy of the U.S.G.S. 7.5 Minute Quadrangle Map indicating the location of the project site is included on Figure 3 in Appendix A.

Recharge / Transition Zone

According to the Official Edwards Aquifer Recharge Zone Map, New Braunfels West, Texas (1988), the project site is located within the Recharge Zone of the Edwards Aquifer. An excerpt of the Official Edwards Aquifer Recharge Zone Map indicating the location of the project site is included on Figure 4 in Appendix A.

100-Year Floodplain

The Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map for the Comal County, Texas, Community Panel Number 48091C04351F (Revised September 2, 2009) was reviewed to determine if the project site is located in areas prone to flooding. A review of the above mentioned Panel No., indicates that the project site is located within "Zone X". According to the Panel Legend, Zone X represents areas determined to be outside the 0.2% annual chance floodplain. A copy of the above referenced FIRM panel indicating the location of the project site is included on Figure 5 in Appendix A.

Soils

According to the United States Department of Agriculture, Soil Conservation Service, Soil Survey of Comal and Hays Counties, Texas, issued in 1984, the project site is located on the Comfort-Rock Outcrop Complex (CrD) and the Eckrant-Rock Complex (ErG). A copy of the 1973 aerial photo (approximate scale: 1"=500') from the U.S.D.A. Soil Survey of Comal and Hays Counties, Texas indicating the location of the project site and the soil types is included on Figure 6 in Appendix A.

The Comfort-Rock outcrop complex, undulating consists of shallow, clayey soils and Rock outcrops on the side slopes, hilltops, and ridgetops in the uplands area of the Edwards Plateau. This soil complex is composed of the Comfort extremely stony clay (49% to 95% of the complex), the Rock outcrop (5-36% of the complex), and small amounts of the Rumble, Purves, Eckert, and Real soils. Typically, the surface layer of the Comfort soil is dark brown extremely stony clay about 6" thick. Stones and cobbles (some as much as 4' across) cover approximately 45% of the surface. The subsoil extends to a depth of 13". It's a dark reddish brown extremely stony clay. The underlying material is indurated fractured limestone. The soil is mildly alkaline and non-calcareous throughout. The soil is well drained, surface runoff is slow to medium, permeability is slow, and the available water capacity is very low. Water erosion is a slight hazard. Typically, the Rock outcrop is dolomitic limestone that is barren of soil except in narrow

fractures in the rock. Some areas may have as much as 3" of soil on top of the outcrop.

This soil has a USDA Texture Classification of extremely stony clay, stony clay, very stony clay and weathered bedrock. The Unified Classification is CH, GC, CL or SC. The AASHTO Classification is A-2-7 and A-7-6. This soil has an average permeability from 0.06 to 0.2 inches/hour.

The Eckrant-Rock Outcrop Complex consists of shallow, clayey soils and rock outcrops on uplands in the Edwards Plateau Land Resource Area. The Eckrant soil makes up 50 to 80 percent of the complex, but on the average it makes up to 70 percent. Rock outcrop makes up 9 to 30 percent of the complex, but the average is 20 percent. Typically, the surface layer of the Eckrant soil is very dark gray extremely stony clay about 10 inches thick. It is about 35 percent by volume, cobbles and stones in the upper part and about 75 percent, by volume in the lower part. The underlying layer is indurated fractured limestone. The soil is moderately alkaline and noncalcareous throughout. Typically, the rock outcrop consists of barren exposures of indurated limestone. In a few areas as much as 4 inches of clayey soil material overlies the bedrock. Dark colored clay is in the cracks and fractures. The Eckrant soil is well drained. Surface runoff is rapid. Permeability is moderately slow and the available water capacity is very low. Water erosion is a severe hazard.

This soil has a USDA Texture Classification of extremely stony clay and weathered bedrock. The Unified Classification is GC, SC or CH. The AASHTO Classification is A-7-6 and A-2-7. This soil has an average permeability from 0.2 to 0.6 inches/hour.

Narrative Description of the Site Geology

Based on a visual inspection of the ground surface, the overall potential for fluid flow from the project site into the Edwards Aquifer appears to be low. The locations of the PRFs are identified on the 2012 aerial photograph on Figure 8 in Appendix A, and on the Site Geologic Map provided in Appendix C. Color photos of the project site and some of the potential recharge features are included in Appendix B.

Potential Recharge Feature # S-1 is a sanitary sewer manhole cover associated with the City of New Braunfels sanitary sewer lines servicing the residential areas in the vicinity of the project site. Frost GeoSciences, Inc., rates the relative infiltration of the feature as low on figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 35 on the sensitivity scale, column 10 in the Geologic Assessment Table on page 4 of this report. Frost GeoSciences, Inc. does not consider the manhole to be a sensitive feature.

Potential Recharge Feature # S-2 consists of a limestone outcrop with little or no surface features. This is an extensive limestone outcrop located on a hillside in the southern portion of the project site. The outcrop follows the topography in the southern and southeastern portion of the project site. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores 10 on the sensitivity scale, column 10 in the Geologic Assessment Table on Page 4 of this report. Frost GeoSciences, Inc. does not consider the outcrop to be a sensitive feature.

Potential Recharge Feature # S-3 consists of a collapsed trench or washout within a backfilled sanitary sewer trench located southwest of the manhole cover (PRF # S-1) observed in the northeastern portion of the Site. The sanitary sewer line in which the trench was observed appeared to have been back filled with small limestone boulders, large gravel, soil, and sand. The hole was approximately 2 feet wide and approximately 12 feet long. The hole was approximately 2.5 feet in depth. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 39 on the sensitivity scale, column 10 in the Geologic Assessment Table on Page 4 of this report. Frost GeoSciences, Inc. does not consider this to be a sensitive feature.

Potential Recharge Feature # S-4 was identified on the geologic map as the Comal Springs Fault located in the southeastern portion of the project site, along the southeastern project site boundary. This fault is the boundary between the Edwards aquifer recharge zone and the transition zone. The fault scarp was approximately 20 to 30 feet tall. The fault scarp was observed over the

entire length of the southeastern project boundary with a dominant trend of approximately 45 to 50 degrees northeast-southwest. The fault scarp would potentially act as a discharge point of PIRFs located on the project site. Based on review of the geologic maps of the area, the upwardly displaced formation to the northwest of the fault is the Edwards Limestone and the downward displaced formations, to the southeast of the fault, are Quaternary fluvial deposits and/or the Navarro and Taylor Groups. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 38 on the sensitivity scale, column 10 in the Geologic Assessment Table on Page 4 of this report. Frost GeoSciences, Inc. does consider this to be a sensitive feature.

The Site is covered by a moderately dense stand of vegetative cover with several open grassy areas characterized by large stands of prickly pear cactus. Site visit photos indicating the condition of the property at the time of the on-site inspection are included in Appendix B. Overall vegetation on the project site consists of ashe juniper (*Juniperus ashei*), live oak (*Quercus virginiana*), and cedar elm (*Ulmus crassifolia*), with agarita (*Berberis trifoliolata*), huisache (*Acacia farnesiana*), catclaw (*Acacia greggii*), Pencil Cactus (*Opuntia leptocaulis*) and prickly pear cactus (*Opuntia lindheimeri*). The variations in the vegetative cover on the property are visible in the 2012 aerial photo on Figures 9 and 10 in Appendix A.

Site visit photographs indicating the condition of the property at the time of the on-site inspection are included in Appendix B. The vegetative cover on the property is visible in the 2012 aerial photograph on Figures 8 and 9 in Appendix A.

According to the site plan provided by Pawelek and Moy, Inc., the surveyed elevations within the project area range from 622 feet in the southern portion of the project site to 730 feet in the northwestern portion of the Site. A copy of the site plan indicating the boundary of the project site and the elevations is included on the Site Geologic Map in Appendix C of this report.

According to the U.S.G.S. Water-Resources Investigations (WRI) Report 94-4117 and the Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle, the project site is located

on the Cretaceous Edwards Person Formation, K_{ep} and K_p respectively. The USGS WRI subdivides the Edwards Person Formation into three separate geologic members and indicates that the project site is located on the Leached and Collapsed member of the Edwards Person formation (K_{ep}).

The Leached and Collapsed Member of the Edwards Person Limestone consists of crystalline limestone, mudstone to grainstone with chert, and collapsed breccia. This member is stromatolitic limestone. The Leached and Collapsed Member is characterized by bioturbated iron stained beds separated by massive limestone beds. This member is typically one of the most permeable and has extensive lateral development with large rooms. Overall thickness ranges from 70 to 90 feet thick. A copies of the USGS WRI Map and the Bureau of Economic Geology New Braunfels Quadrangle are included on Figures 7A and 7B in Appendix A. A copy of the Stratigraphic Column highlighting the outcropping formations is included on Page 3 of this report.

BEST MANAGEMENT PRACTICE (BMP)

Based on a visual inspection of the ground surface, the overall potential for fluid flow from the project site into the Edwards Aquifer appears to be low. The potential always exists to encounter solution cavities within the subsurface during excavating activities. Frost GeoSciences, Inc. is of the opinion that it is very important for construction personnel to be informed of the potential to encounter cavities in the subsurface that lack a surface expression. Construction personnel should also be informed of the proper protocol to follow in the event a karst feature is encountered during the development of the project site.

DISCLAIMER

This report has been prepared in general accordance with the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04) by a Licensed Texas Professional Geoscientist. All areas of the project site were carefully inspected for features that could contribute to the recharge of the Edwards Aquifer, however, this survey cannot preclude the presence of subsurface karst features

*January 13, 2014
Eden Hill
page 11*

that lack surface expression. This report is not intended to be a definitive investigation of all possible geologic or karst features at this site. All conclusions, opinions, and recommendations for Best Management Practices (BMP's) in this report are based on information obtained while researching the project, and on the site conditions at the time of our field investigation.


This report has been prepared for the exclusive use of Eden Hill. This report is based on available known records, a visual inspection of the project site, and the work generally accepted for a Geologic Assessment for Regulated Activities / Developments on the Edwards Aquifer Recharge / Transition Zone, relating to 30 TAC §213.5(b)(3), effective June 1, 1999.

REFERENCES

- 1) U.S.G.S. 7.5 Minute Quadrangle Map, New Braunfels West, Texas Sheet (1988).
- 2) Collins, Edward, W., 2000. Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle. Bureau of Economic Geology, The University of Texas at Austin, Texas.
- 3) Official Edwards Aquifer Recharge Zone Map, New Braunfels West, Texas Sheet (1988).
- 4) Small, Ted A. and Hanson, John A., 1994. Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Outcrop, Comal County, Texas.
U.S. Geological Survey Water Resources Investigations 94-4117.
- 5) Barnes, V.L., 1983. Geologic Atlas of Texas, San Antonio Sheet. Bureau of Economic Geology, The University of Texas at Austin, Texas.
- 6) Federal Emergency Management Agency (FEMA), September 29, 2010. Bexar County, Texas and Incorporated Areas. Flood Insurance Rate Map (FIRM), Panel #48091C0435F. FEMA, Washington D.C.
- 7) U.S.D.A. Soil Conservation Service, Soil Survey of Comal and Hays Counties, Texas (1984).
- 8) TCEQ-0585-Instructions (Rev. 10-1-04). "Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zone".

Appendix A

Site Location Plates



PROJECT NAME:

Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 Eden Home - Lakeview Site
 New Braunfels, Texas


Site Plan

PROJECT NO.:

FGS-EI4102

DATE:

January 13, 2014



PROJECT NAME:

Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 Eden Home - Lakeview Site
 New Braunfels, Texas


Street Map

PROJECT NO.:

FGS-EI4102

DATE:

January 13, 2014



PROJECT NAME:

Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 Eden Home - Lakeview Site
 New Braunfels, Texas

U.S.G.S. 7.5 Minute Quadrangle Map
 New Braunfels West, Texas Sheet (1988)

PROJECT NO.:

FGS-E14102

DATE:

January 13, 2014



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Eden Home - Lakeview Site
New Braunfels, Texas


Official Edwards Aquifer Recharge Zone Map,
New Braunfels West, Texas (1988)

PROJECT NO.:

FGS-E14102

DATE:

January 13, 2014




PROJECT NAME:
 Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 Eden Home - Lakeview Site
 San Antonio, Texas

Flood Insurance Rate Map (FIRM)
 Community Panel # 48029C0145G
 (September 29, 2010)

PROJECT NO.:
 FGSE-I4102

DATE:
 January 13, 2014



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Eden Home - Lakeview Site
San Antonio, Texas


1973 Aerial Photograph
Soil Survey of Comal & Hays Counties, Texas
United States Department of Agriculture

PROJECT NO.:

FGS-E14102

DATE:

January 13, 2014




PROJECT NAME:
 Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 Eden Home - Lakeview Site
 New Braunfels, Texas

United States Geologic Survey
 Water Resources Investigations #94-4117
 Geologic Map of Comal County, Texas

PROJECT NO.:
 FGS-E14102

DATE:
 January 13, 2014



PROJECT NAME:
 Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 Eden Home - Lakeview Site
 New Braunfels, Texas

Bureau of Economic Geology
 Geologic Map of the New Braunfels, Texas
 30 X 60 Minute Quadrangle (2000)

PROJECT NO.:
 FGS-E14102

DATE:
 January 13, 2014



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Eden Home - Lakeview Site
New Braunfels, Texas

2012 Aerial Photograph with PRFs
National Agricultural Imagery Program

PROJECT NO.:

FGS-E14102

DATE:

January 13, 2014



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Eden Home - Lakeview Site
New Braunfels, Texas

2012 Aerial Photograph
National Agricultural Imagery Program

PROJECT NO.:

FGS-E14102

DATE:

January 13, 2014

Appendix B

Site Inspection Photographs



View of Potential Recharge Feature # S-1.



Typical view of the vegetative cover in the vicinity of PRF # S-1.



View of Potential Recharge Feature # S-2.



Typical view of the vegetative cover in the vicinity of PRF # S-2.



View of Potential Recharge Feature # S-3.



Additional view of Potential Recharge Feature # S-3.



View to the southeast of the fault scarp.



Additional view over the fault scarp.



Typical view of the vegetative cover observed in the northern portion of the project site.



Typical view of the vegetative cover observed in the western portion of the project site.



Typical view of the vegetative cover observed in the southern portion of the project site.





Typical view of the vegetative cover observed in the eastern portion of the project site.

Appendix C

Site Geologic Map



Location Map



Site Geologic Map

Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 for the
Eden Hill - Lakeview Site
 +/- 8.5 Acres
 New Braunfels, Texas

Frost GeoSciences, Inc. Control # FGS-E14102


Legend

- Fill - Fill Material
- Qal - Alluvium
- Kau - Austin Chalk
- Kef - Eagle Ford Shale
- Kbu - Buda Limestone
- Kdr - Del Rio Clay
- Kgt - Georgetown Limestone
- Kep - Edwards Person Limestone
- Kek - Edwards Kainer Limestone
- Kgr - Glen Rose Formation
- Kknm - Navarro and Taylor Groups, Undivided
- S# - Potential Recharge Feature (PRF)
- - Formation Contact
- - 100-Year Floodplain - Zone A
- - 100-Year Floodplain - Zone AE
- (shaded) - Other Flood Hazard Area - Zone X (shaded)

Floodplain Information Obtained From
 FIRM: Flood Insurance Rate Map
 Comal County, Texas; Panel # 48091C0435F, Revised 9/2/2009

Fault Information Obtained From:
 Bureau of Economic Geology, Geologic Atlas of Texas, San Antonio Sheet (1983)
 U.S. Geological Survey, Water Resources Investigations Report 94-4117 (1994)
 Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle (2000)

ITCEQ-R1:
 JUL 31 2014
 SAN ANTONIO



Christopher Wickman
 Geology
 10403
 State of Texas Licensed Geoscientist
 Chris Wickman, P.G. License No. 10403

Water Pollution Abatement Plan Application
for Regulated Activities
on the Edwards Aquifer Recharge Zone
and Relating to 30 TAC §213.5(b), Effective June 1, 1999

REGULATED ENTITY NAME: Eden Hill - Lakeview Site

REGULATED ENTITY INFORMATION

1. The type of project is:
 Residential: # of Lots: _____
 Residential: # of Living Unit Equivalents: _____
 Commercial
 Industrial
 Other: Private Park for Eden Hill Communities
2. Total site acreage (size of property): 8.47 Acres
3. Projected population: 0
4. The amount and type of impervious cover expected after construction are shown below:

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	0	÷ 43,560 =	0
(Asphalt/Concrete Parking Drives/Sidewalks/Pads)	39,280	÷ 43,560 =	0.90
Other paved surfaces	0	÷ 43,560 =	0
Total Impervious Cover	39,280	÷ 43,560 =	0.90
Total Impervious Cover ÷ Total Acreage x 100 =			10.63%

5. **ATTACHMENT A - Factors Affecting Water Quality.** A description of any factors that could affect surface water and groundwater quality is provided at the end of this form.
6. Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

FOR ROAD PROJECTS ONLY N/A

Complete questions 7-12 if this application is exclusively for a road project.

7. Type of project:
 TXDOT road project.
 County road or roads built to county specifications.
 City thoroughfare or roads to be dedicated to a municipality.
 Street or road providing access to private driveways.
8. Type of pavement or road surface to be used:
 Concrete
 Asphaltic concrete pavement
 Other: _____

- The SCS was submitted with this application.
- The SCS will be submitted at a later date. The owner is aware that the SCS may not be installed prior to Executive Director approval.

The sewage collection system will convey the wastewater to the _____
 (name) Treatment Plant. The treatment facility is:
 existing.
 proposed.

16. N/A All private service laterals will be inspected as required in 30 TAC §213.5.
 (No Buildings/Sewage Being Proposed)

SITE PLAN REQUIREMENTS

Items 17 through 27 must be included on the Site Plan.

17. The Site Plan must have a minimum scale of 1" = 400'.
 Site Plan Scale: 1" = 40'.
18. 100-year floodplain boundaries
 Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.
 No part of the project site is located within the 100-year floodplain.

The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s):
FEMA Flood Insurance Rate Map - Comal County, Texas and Incorporated Areas, Map Number 48091C0435F (Rev. 9/02/09)

19. The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Show lots, recreation centers, buildings, roads, etc.
 The layout of the development is shown with existing contours. Finished topographic contours will not differ from the existing topographic configuration and are not shown.
20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):
 There are _____ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)
 The wells are not in use and have been properly abandoned.
 The wells are not in use and will be properly abandoned.
 The wells are in use and comply with 16 TAC §76.
 There are no wells or test holes of any kind known to exist on the project site.

21. Geologic or manmade features which are on the site:
 All **sensitive** geologic or manmade features identified in the Geologic Assessment are shown and labeled.
 No **sensitive** geologic or manmade features were identified in the Geologic Assessment.
 ATTACHMENT D - Exception to the Required Geologic Assessment. An exception to the Geologic Assessment requirement is requested and explained at the end of this form.

22. The drainage patterns and approximate slopes anticipated after major grading activities.

23. Areas of soil disturbance and areas which will not be disturbed.

- 24. X Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
- 25. X Locations where soil stabilization practices are expected to occur.
- 26. X Surface waters (including wetlands).
- 27. X Locations where stormwater discharges to surface water or sensitive features.
 There will be no discharges to surface water or sensitive features. (Site generally drains to the southeast side of the property)

ADMINISTRATIVE INFORMATION

- 28. X Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
- 29. X Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **WATER POLLUTION ABATEMENT PLAN APPLICATION FORM** is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Daryl D. Pawelek

 Print Name of Customer/Agent



 Signature of Customer/Agent

7-30-14
 Date

WATER POLLUTION ABATEMENT PLAN APPLICATION

5. Attachment A – Factors Affecting Water Quality

The potential sources of contamination on the proposed project include, but are not limited to, hydrocarbons, such as oil and grease, vehicle/machinery fluid leaks, trash or debris, and fertilizers and soil runoff.

All construction equipment will be fueled off-site, and no hazardous materials shall be utilized for the construction of the proposed improvements. Portable toilets will be placed on site for use by construction workers during construction activities. All waste will be hauled off site daily, as generated.

Prior to any construction activity, stormwater pollution prevention controls shall be installed and these controls include silt fence and rock berms, down-gradient of the soil disturbance, concrete washout areas and the installation of stabilized construction entrance/exits to reduce sediment removal from the site. The construction contractor will be responsible for the installation, repair and upkeep of all control measures.

After construction is complete and the site has been built, the factors affecting water quality will include runoff from the paved areas, sidewalks and greenbelt areas. Chemicals that may be present include pesticides and fertilizers for the greenbelt areas as well as miscellaneous oils or fuels from vehicles utilizing the parking areas. However, the stormwater runoff from these areas will be treated by the proposed Natural and Engineered Vegetative Filter Strips as shown on the Site Plan, Sheet S1.

13. Attachment B – Volume and Character of Stormwater

The stormwater runoff generated from this site will consist of runoff from the paved areas, sidewalks and greenbelt areas. The runoff may contain small amounts of suspended solids, fertilizers/pesticides for the greenbelt areas or oils/fuel that would be associated with vehicles entering and exiting the site. The average runoff coefficient for the existing site is $C_{10pre} = 0.38$ and the average Post-Construction runoff coefficient is $C_{10post} = 0.43$. The proposed impervious cover will be treated via Natural and Engineered Vegetated Filter Strips downstream of the impervious cover areas. Additionally, there will be two detention ponds located on the site that will aid in the sedimentation of solids and improve the overall water quality.

SITE PLAN




OWNER:
EDEN HOME, INC.
c/o EDEN HILL COMMUNITIES
631 LAKEVIEW BLVD
NEW BRAUNFELS, TX 78130

SITE PLAN FOR
EDENHILL COMMUNITIES - PRIVATE PARK
 NEW BRAUNFELS, TEXAS

**EDEN HILL LAKEVIEW SITE- PRIVATE PARK
PERMANENT BEST MANAGEMENT PRACTICE SUMMARY
8.47 ACRE SITE**


Watershed Area	Permanent BMP	Drainage Area (Acres)	Imp. Cover (Acres)	Target TSS Removal (lb/yr)	TSS Removal Provided (lb/yr)
A(Onsite)	Vegetative Filter Strips	1.050	0.552	495	495
A(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
B1	Uncaptured	0.530	0.000	0	0
B2	Vegetative Filter Strips	0.310	0.136	122	122
C1	Uncaptured	0.610	0.000	0	0
C2	Vegetative Filter Strips	0.490	0.172	154	154
C3(Onsite)	Vegetative Filter Strips	0.030	0.014	13	13
C3(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
F	Uncaptured	5.450	0.000	0	0
Total		8.510	0.902	810	810

Notes:
1. Uncaptured area without impervious cover, no treatment necessary



LEGEND

- S.F.** SILT FENCE
- ROCK BERM
- GABION MATTRESS (VELOCITY CONTROL)
- ROCK RIPRAP (VELOCITY CONTROL)
- PROPOSED VEGETATIVE FILTER
- PROPOSED PAD
- PROPOSED CONCRETE
- TEMPORARY STABILIZED CONSTRUCTION ENTRANCE/EXIT
- CONCRETE WASHOUT
- EXISTING FLOW DIRECTION
- EXISTING CONTOURS
- PROPOSED CONTOURS
- PROPERTY LINE
- S#** POTENTIAL RECHARGE FEATURE (PRF)
- KeP** EDWARDS PERSON LIMESTONE
- Kkmm** NAVARRO AND TAYLOR GROUPS, UNDIVIDED
- FAULT



ENGINEERED VEGETATIVE FILTER STRIP DETAIL
N.T.S.

IMPERVIOUS COVER SUMMARY


IMPERVIOUS COVER OF PROJECT SITE	Sq. Ft.	Sq. Ft./Acre	Acres
STRUCTURES/ROOFTOPS	0	+ 43,560 =	0.00
PAVING/DRIVES/PADS/SIDEWALKS	39,280	+ 43,560 =	0.90
TOTAL IMPERVIOUS COVER	39,280	+ 43,560 =	0.90

TOTAL IMPERVIOUS COVER ÷ TOTAL ACREAGE x 100 = 10.63 %

TOTAL PROJECT SITE ACREAGE = 8.47 Ac.

NOTES:

- SEE DRAINAGE AREA MAP SHEET D-1 FOR OVERALL DRAINAGE AREAS.
- SOIL STABILIZATION NOTE:**
IN ALL AREAS TO BE DISTURBED OUTSIDE OF THE LIMITS OF PAVING, SIDEWALKS, LANDSCAPING, ETC., AND FOR THE ENGINEERED VEGETATIVE FILTER STRIPS, VEGETATIVE STABILIZATION IN ACCORDANCE WITH RC-348 COMPLYING WITH THE EDWARDS AQUIFER RULES, ITEM 1.3.8-TEMPORARY VEGETATION, ITEM 1.3.9-BLANKETS AND MATTING, ITEM 1.3.10-HYDRAULIC MULCH AND/OR ITEM 1.3.11 SOD SHALL BE IMPLEMENTED. THE AREAS TO BE VEGETATED SHALL BE WATERED SUFFICIENTLY TO ESTABLISH 70% STABILIZATION.
- VELOCITY CONTROL NOTE:**
AT THE POINT WHERE PROPOSED DRAINAGE PIPES OUTFALL AND ON THE DOWNSTREAM SIDE OF THE DETENTION POND OUTFALLS, A VELOCITY CONTROL PROCEDURE UTILIZING HEAVY ROCK RIPRAP (TYPE 'R' PER TXDOT ITEM 432) OR GABION MATTRESS (PER TXDOT ITEM 459) SHALL BE USED TO DISSIPATE THESE FLOWS (SEE DETAILS ON SHEET S2). THESE APPLICATIONS SHALL REMAIN IN PLACE AND NOT BE REMOVED UPON COMPLETION OF THE CONSTRUCTION ACTIVITIES.
- FLOODPLAIN NOTE:**
ACCORDING TO FEMA FIRM MAP PANEL No. 48091C0435F, EFFECTIVE DATE 9/2/2009, A PORTION OF THE PROJECT SITE LIES WITHIN THE 100 YR FLOODPLAIN.



F:\1401.01 - Eden Hills Parking.dwg, 2014/07/21 7:38am Administrator

REVISIONS	DESCRIPTION	DATE

DRAWN BY: D.G. III
CHECKED BY: J.J.M.
DATE: JULY 2014
JOB NO.: 1401.01

Temporary Stormwater Section
for Regulated Activities
on the Edwards Aquifer Recharge Zone
and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

REGULATED ENTITY NAME: Eden Hill - Lakeview Site

POTENTIAL SOURCES OF CONTAMINATION

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:
 - Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.
 - Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
 - Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An **Aboveground Storage Tank Facility Plan** application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
 - Fuels and hazardous substances will not be stored on-site.

2. **ATTACHMENT A - Spill Response Actions.** A description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is provided at the end of this form.

3. Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.

4. **ATTACHMENT B - Potential Sources of Contamination.** Describe in an attachment at the end of this form any other activities or processes which may be a potential source of contamination.
 - The are no other potential sources of contamination. (None anticipated beyond those listed as Examples under Potential Sources of Contamination shown above.)

SEQUENCE OF CONSTRUCTION

5. **ATTACHMENT C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is provided at the end of this form. For each activity described, an estimate of the total area of the site to be disturbed by each activity is given.

6. Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Tributary of Blieder's Creek

TEMPORARY BEST MANAGEMENT PRACTICES (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. **All structural BMPs must be shown on the site plan.**

7. X **ATTACHMENT D - Temporary Best Management Practices and Measures.** A description of the TBMPs and measures that will be used during and after construction are provided at the end of this form. For each activity listed in the sequence of construction, include appropriate control measures and the general timing (or sequence) during the construction process that the measures will be implemented.

X TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information has been provided in the attachment at the end of this form

- a. A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
- b. A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
- c. A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
- d. A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.

8. The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.

 ATTACHMENT E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is provided at the end of this form. The request includes justification as to why no reasonable and practicable alternative exists for each feature.

X There will be no temporary sealing of naturally-occurring sensitive features on the site.

9. X **ATTACHMENT F - Structural Practices.** Describe the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site. Placement of structural practices in floodplains has been avoided.

10. X **ATTACHMENT G - Drainage Area Map.** A drainage area map is provided at the end of this form to support the following requirements.

— For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.

— For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.

— For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.

X There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. ~~A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.~~ (Silt Fences and Rock Berms will be used to control sediment.)

11. N/A **ATTACHMENT H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure has been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are provided as at the end of this form.

12. X **ATTACHMENT I - Inspection and Maintenance for BMPs.** A plan for the inspection of temporary BMPs and measures and for their timely maintenance, repair, and, if necessary, retrofit is provided at the end of this form. A description of documentation procedures and recordkeeping practices is included in the plan.

13. X All control measures must be properly selected, installed, and maintained in accordance with the manufacturers specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicates a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.

14. X If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).

15. N/A Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.

16. X Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

SOIL STABILIZATION PRACTICES

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

- 17. X **ATTACHMENT J - Schedule of Interim and Permanent Soil Stabilization Practices.**
A schedule of the interim and permanent soil stabilization practices for the site is attached at the end of this form.
- 18. X Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 19. X Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.


ADMINISTRATIVE INFORMATION

- 20. X All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. X If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. X Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **TEMPORARY STORMWATER SECTION** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Daryl D. Pawelek

Print Name of Customer/Agent



Signature of Customer/Agent

7-30-14

Date

TEMPORARY STORMWATER SECTION

2. Attachment A – Spill Response Actions

Regarding spill prevention and control, found directly behind this sheet is copy of Section 1.4.16 of the Texas Commission on Environmental Quality (TCEQ) "Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices, pages 1-118 through 1-121, Spill Prevention and Control which covers necessary procedures for spill prevention and control. In the event of a significant or hazardous spill (per the attached TCEQ criteria and guidelines) the contractor or construction personnel shall notify the TCEQ by telephone as soon as possible and within 24 hours at (512) 339-2929 (Austin) or (210) 490-3096 (San Antonio) between 8 am and 5 pm. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.

(See Spill Prevention and Control information on the following sheets)



RG-348
Revised July 2005

Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices

Field Operations Division

printed on
recycled paper

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

1.4.16 Spill Prevention and Control

The objective of this section is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees.

The following steps will help reduce the stormwater impacts of leaks and spills:

Education

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a “significant spill” is for each material they use, and what is the appropriate response for “significant” and “insignificant” spills. Employees should also be aware of when spill must be reported to the TCEQ. Information available in 30 TAC 327.4 and 40 CFR 302.4.
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor’s superintendent or representative oversee and enforce proper spill prevention and control measures.

General Measures

- (1) To the extent that the work can be accomplished safely, spills of oil, petroleum products, substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.
- (6) Spills should be covered and protected from stormwater runoff during rainfall to the extent that it doesn’t compromise clean up activities.
- (7) Do not bury or wash spills with water.

- (8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.
- (9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.
- (10) Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.
- (11) Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.
- (12) Keep waste storage areas clean, well organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

Cleanup

- (1) Clean up leaks and spills immediately.
- (2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.
- (3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

Minor Spills

- (1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.
- (2) Use absorbent materials on small spills rather than hosing down or burying the spill.
- (3) Absorbent materials should be promptly removed and disposed of properly.
- (4) Follow the practice below for a minor spill:
- (5) Contain the spread of the spill.
- (6) Recover spilled materials.
- (7) Clean the contaminated area and properly dispose of contaminated materials.

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman immediately.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities:

- (1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
- (2) For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110,119, and 302, the contractor should notify the National Response Center at (800) 424-8802.
- (3) Notification should first be made by telephone and followed up with a written report.
- (4) The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.
- (5) Other agencies which may need to be consulted include, but are not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc.

More information on spill rules and appropriate responses is available on the TCEQ website at: http://www.tnrcc.state.tx.us/enforcement/emergency_response.html

Vehicle and Equipment Maintenance

- (1) If maintenance must occur onsite, use a designated area and a secondary containment, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.
- (2) Regularly inspect onsite vehicles and equipment for leaks and repair immediately
- (3) Check incoming vehicles and equipment (including delivery trucks, and employee and subcontractor vehicles) for leaking oil and fluids. Do not allow leaking vehicles or equipment onsite.
- (4) Always use secondary containment, such as a drain pan or drop cloth, to catch spills or leaks when removing or changing fluids.
- (5) Place drip pans or absorbent materials under paving equipment when not in use.
- (6) Use absorbent materials on small spills rather than hosing down or burying the spill. Remove the absorbent materials promptly and dispose of properly.
- (7) Promptly transfer used fluids to the proper waste or recycling drums. Don't leave full drip pans or other open containers lying around.
- (8) Oil filters disposed of in trashcans or dumpsters can leak oil and pollute stormwater. Place the oil filter in a funnel over a waste oil-recycling drum to drain excess oil before disposal. Oil filters can also be recycled. Ask the oil supplier or recycler about recycling oil filters.
- (9) Store cracked batteries in a non-leaking secondary container. Do this with all cracked batteries even if you think all the acid has drained out. If you drop a battery, treat it as if it is cracked. Put it into the containment area until you are sure it is not leaking.

Vehicle and Equipment Fueling

- (1) If fueling must occur on site, use designated areas, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.
- (2) Discourage "topping off" of fuel tanks.
- (3) Always use secondary containment, such as a drain pan, when fueling to catch spills/ leaks.

5. **Attachment C – Sequence of Major Activities**

The following is a sequence of major activities which will involve soil disturbance along with an estimate of the area of the site to be disturbed by each activity:

Sequence No.	Description of Soil Disturbing Activity	Estimated Area to be Disturbed by each Activity (Acres ~ Total)
1	Clearing/Grubbing/Construction Staging (For Proposed Parking, Sidewalks, Engineered Vegetative Filter Strips, Detention Ponds & Trails)	5.00
2	Excavation and Grading (Proposed Parking, Sidewalks, Engineering Vegetative Filter Strips and Detention Ponds)	1.87
3	Final Paving and Sidewalks	0.90

7. **Attachment D – Temporary Best Management Practices and Measures**

The Temporary Best Management Practices (TBMP's) that will be used for this development are rock berms, silt fences, a concrete washout area and a temporary construction entrance/exit in accordance with the Site Plan. The temporary controls (i.e. rock berms, silt fences, temporary construction entrance/exit and the concrete washout area) shall be in place prior to construction activities and will be maintained by the contractor during construction. The controls shall be removed by the contractor when vegetation is established on all exposed or disturbed areas.

- a. There is a drainage area that originates off-site and flows onto the project site, Drainage Area E (see Drainage Area Map, Sheet D1). Drainage Area E will enter the site and then be conveyed around the disturbed areas via interceptor/bypass swales and proposed bypass culverts. These measures will be treated with temporary rock berms to reduce/capture sediment prior to exiting the site. Located at the outfall location of these measures will also be a permanent velocity control measure consisting of rock riprap which will be applied to reduce the velocity of the concentrated flow. Therefore off-site water required to enter the site via Drainage Area E will be treated by temporary rock berms prior to exiting the site.

- b. The stormwater that originates on-site will be controlled and filtered by rock berms and silt fences on the down gradient side of the areas of disturbance. The rock berms and silt fences will reduce the velocity of the water and allow the sediment to settle out and be trapped by the control device. After a significant rainfall event, it will be the contractor's responsibility to remove the sediment and debris that is captured.
- c. The BMP's will prevent pollutants from entering surface streams, sensitive features (no sensitive features present on this site), or the aquifer by capturing the silts and sediments through the utilization of the previously mentioned control devices such as silt fences and rock berms. These devices are located such that they capture the silts and sediment prior to entering the surface streams, etc. where they would otherwise be carried downstream. The settlement of the silts and sediment is due to the reduction of the velocity of the water.
- d. There were no sensitive features located on the site. However, previously described temporary measures will be maintained and incorporated where necessary to prevent contamination of stormwater runoff. In the event a sensitive feature is discovered during construction, the contractor or construction personnel shall notify the TCEQ by telephone as soon as possible and within 24 hours at (512) 339-2929 (Austin) or (210) 490-3096 (San Antonio) between 8 am and 5 pm. At that point an assessment will be made with the TCEQ as to how to best protect what was discovered.

9. **Attachment F – Structural Practices**

The structural practices that will be used for temporary erosion/sediment control for this development are rock berms, silt fences, temporary construction entrance/exits, and a concrete washout area. The rock berms and silt fences will allow the silts and sediment to settle out prior to discharging into surface streams or sensitive features (no sensitive features present on this site). As mentioned previously, there will be two detention ponds being constructed on the project site and these detention ponds will aid in the sedimentation of solids and improve the overall water quality.

10. **Attachment G – Drainage Area Map**

The drainage area map can be found at the end of this section.

12. **Attachment I – Inspection and Maintenance for BMP's**

A. Rock Berm Inspection and Maintenance Guidelines:

- 1) Inspection shall be made weekly and after each rainfall by the contractor.
- 2) All debris and sediment shall be removed when buildup reaches 6 inches and this accumulated debris/sediment shall be disposed in an approved site and in a manner as to not introduce additional siltation.
- 3) Any loose wire sheathing shall be repaired.
- 4) During the inspection, the berm shall be reshaped as needed.
- 5) The berm shall be replaced when the structure does not function as intended due to silt accumulation, construction traffic, etc.
- 6) The rock berm shall be left in place until all upstream disturbed areas are stabilized and the accumulated silt has been removed.

B. Silt Fence Inspection and Maintenance Guidelines:

- 1) Inspection shall be made weekly and after each rainfall by the contractor.
- 2) All sediment shall be removed when buildup reaches 6 inches.
- 3) Any torn fabric shall be replaced or a new line of fencing shall be installed parallel to the torn section.
- 4) Replace or repair areas of silt fence that have been damaged due to construction activity, vehicular access, etc. and if the silt fence is located in an area of high construction traffic, relocate to an area that will provide equal protection but will not obstruct vehicular movements.
- 5) When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.

C. Temporary Construction Entrance/Exit:

- 1) The entrance shall be maintained in a way that will prevent tracking of sediment onto the public right-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment.
- 2) Any sediment dropped, spilled, washed or tracked on to the public right of way shall be immediately removed by the contractor.
- 3) When applicable, wheels shall be washed to removed sediment prior to exiting the construction site.

- 4) When washing is required it shall be performed in an area that is stabilized/protected to prevent sediment from entering any public right of ways, streams or sensitive areas.

D. Concrete Washout Area Inspection and Maintenance Guidelines:

- 1) Inspection shall be made weekly and after each rainfall by the contractor.
- 2) When concrete accumulates 6 inches in depth, the concrete shall be broken up, removed and disposed of properly.
- 3) All controls around the perimeter of the washout area shall be checked, maintained and repaired as needed.
- 4) Upon completion of construction, the concrete washout area shall be cleaned and all concrete shall be removed and disposed of properly. Holes, depressions or other ground disturbance caused by the removal of the temporary concrete washout facility shall be backfilled and repaired.

Documentation and Recordkeeping:

All scheduled inspection and maintenance measures made to the temporary BMPs must be documented clearly on the Inspection Forms included for the respective BMP, showing inspection/maintenance measure performed, date and person responsible for inspection and maintenance. Any changes made to the location of type of controls shown on the accepted plans, due to onsite conditions, shall be documented on the site plan that is part of this Water Pollution Abatement Plan(WPAP). No other changes shall be made unless approved by TCEQ and the Design Engineer. Documentation shall clearly show changes made, date, person responsible for the change, and the reason for the change. All documentation and recordkeeping shall be retained onsite with the WPAP.

***Person or Firm Responsible for Erosion/Sedimentation Control Maintenance:**

Company: _____

Contact: _____

Phone: _____

Address: _____

Signature of Responsible Party: _____

(*This information shall be filled out and signed by the responsible party prior to construction)

TEMPORARY CONSTRUCTION ENTRANCE/EXIT INSPECTION FORM

Inspection Date: _____

Signature: _____

General Notes

- 1) Stone Size – 4 to 8 inches crushed rock
- 2) Length – as effective, but not less than 50 feet.
- 3) Thickness – not less than 8 inches.
- 4) Width – not less than 12 feet.
- 5) Washing – when necessary, wheels shall be cleaned to remove sediment prior to access onto the public roadway. When washing is required, it shall be done so that no sediment leaves the site/development. All unfiltered sediment shall be prevented from entering any storm drain, ditch or watercourse.
- 6) Maintenance – the entrance shall be maintained in a condition which will prevent tracking of sediment onto the public roadways. This may require periodic addition of stones as necessary, repair and/or cleanout of any measures used to trap sediment. All sediment spilled, dropped, washed or tracked onto the public roadway must be removed immediately.
- 7) Drainage – the entrance must be properly graded to prevent runoff from leaving the construction site.

	Yes	No	Comment
Is sediment present on the roadway?			
Is the gravel clean and working properly (relatively free of mud/sediment)?			
Does all traffic use the stabilized entrance to leave the site?			

Maintenance Required for Temporary Construction Entrance/Exit:

To Be Performed by: _____ On or Before: _____

SILT FENCE INSPECTION FORM

Inspection Date: _____

Signature: _____

General Notes:

- 1) The steel posts which support the silt fence shall be installed on a slight angle toward the anticipated runoff source. Posts must be embedded a minimum of one foot deep and spaced not more than 6 feet on center.
- 2) The toe of the silt fence shall be trenched in with a spade or mechanical trencher.
- 3) The trench must be a minimum of 6 inches deep and 6 inches wide to allow for the silt fence fabric to be laid in the ground and backfilled and compacted.
- 4) Silt fence should be securely fastened to each steel support post and to woven wire, which in turn is attached to the steel fence post. There shall be a 3 foot double overlap, securely fastened where ends of fabric meet.
- 5) Silt fence shall be removed when the site is completely stabilized so as not to block or impede storm flow or drainage.
- 6) Accumulated silt shall be removed when it reaches a depth of 6 inches. The silt shall be disposed of in an approved site and in such a manner as to not contribute additional silt.

	Yes	No	Comment
Is the bottom of the fabric still buried/secured?			
Is the fabric torn, missing or sagging?			
Are the post tipped over?			
How deep is the sediment?			

Maintenance Required for Silt Fence:

To Be Performed by: _____ On or Before: _____

ROCK BERMS INSPECTION FORM

Inspection Date: _____

Signature: _____

General Notes:

- 1) The woven wire sheathing shall be perpendicular to the flow line and the sheathing shall be 20 gauge woven wire mesh with 1 inch openings.
- 2) The berm shall have a top width of 24 inches with side slopes being 2:1 (H:V) or flatter.
- 3) Placement of the rock along the sheathing shall not be less than 18 inches.
- 4) The wire sheathing shall be wrapped around the rock and secured with tie wire so that the ends of the sheathing overlap at least 2 inches, and the berm retains its shape when walked upon.
- 5) The berm shall be built along the contour at zero percent grade or as near as possible.
- 6) The ends of the berm shall be tied into the existing upslope grade and the berm shall be buried in a trench approximately 3 to 4 inches deep to prevent failure of the control.

	Yes	No	Comment
Is the berm a minimum of 18 inches high?			
Does the berm have a top width of 24 inches?			
Is the level of sediment/silt greater than 6 inches?			
Does the rock berm need repair?			

Maintenance Required for Rock Berms:

To Be Performed by: _____ On or Before: _____

CONCRETE WASHOUT AREA INSPECTION FORM

Inspection Date: _____

Signature: _____

General Notes:

- 1) The concrete washout shall be located at least 50 feet from sensitive features, storm drains, open ditches or water bodies.
- 2) The containment area shall be maintained such that there is no concrete or sediment escaping the containment area and shall be lined with 10 mil plastic.
- 3) Concrete wash out wastes shall be allowed to set, be broken up, and then disposed of properly.

	Yes	No	Comment
Is the concrete washout located near any sensitive features, storm drains, open ditches or water bodies?			
Is the containment area secured and working properly?			
Is there a plastic lining?			
Does the washout area need to be cleaned from too much old concrete?			

Maintenance Required for Concrete Washout Area:

To Be Performed by: _____ On or Before: _____

17. Attachment J – Schedule of Interim and Permanent Soil Stabilization Practices

A. Temporary Stabilization

No bare ground exposed during construction will be left to stabilize naturally. Any disturbed area where construction activities have ceased, permanently or temporarily, the contractor shall initiate temporary stabilization of the area by the use of seeding and mulching within 14 days, except in areas where construction activities are scheduled to resume within 21 days. The temporary seeding will consist of Buffalograss, Green Sprangletop and Bermuda Grass with straw or cedar mulch applied on final layer in accordance with TxDOT Item 164 – Seeding for Erosion Control. Based on the growing season at the time of construction, mixture and application rates may be modified by the engineer.

B. Permanent Stabilization

All disturbed portions of the site where construction activity permanently ceases shall be stabilized with permanent seed no later than 14 days after the last construction activity. The permanent seed mix shall consist of Bermuda Grass, Green Sprangletop and Buffalo Grass with straw or cedar mulch applied on the final layer in accordance with TxDOT Item 164 – Seeding for Erosion Control. Depending on the growing season at the time of construction, the mixture and application rates may be modified. It shall be the contractor's responsibility to sufficiently water the areas to be vegetated to achieve 70% stabilization.

ATTACHMENT G
DRAINAGE AREA MAP

Permanent Stormwater Section
for Regulated Activities
on the Edwards Aquifer Recharge Zone
and Relating to 30 TAC §213.5(b)(4)(C), (D)(li), (E), and (5), Effective June 1, 1999

REGULATED ENTITY NAME: Eden Hill - Lakeview Site

Permanent best management practices (BMPs) and measures that will be used during and after construction is completed.

1. Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.

2. These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.

 The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
 A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is provided below

3. Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.

4. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

 This site will be used for low density single-family residential development and has 20% or less impervious cover.
 This site will be used for low density single-family residential development but has more than 20% impervious cover.
 This site will not be used for low density single-family residential development.

5. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be

recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

- ATTACHMENT A - 20% or Less Impervious Cover Waiver.** This site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is found at the end of this form.
- This site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.
- This site will not be used for multi-family residential developments, schools, or small business sites.

6. **ATTACHMENT B - BMPs for Upgradient Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is identified as **ATTACHMENT B** at the end of this form.
- If no surface water, groundwater or stormwater originates upgradient from the site and flows across the site, an explanation is provided as **ATTACHMENT B** at the end of this form.
- If permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, an explanation is provided as **ATTACHMENT B** at the end of this form .

7. **ATTACHMENT C - BMPs for On-site Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is identified as **ATTACHMENT C** at the end of this form.
- If permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, an explanation is provided as **ATTACHMENT C** at the end of this form.

8. **ATTACHMENT D - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is provided at the end of this form. Each feature identified in the Geologic Assessment as "sensitive" or "possibly sensitive" has been addressed.

9. The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.

- The permanent sealing of or diversion of flow from a naturally-occurring "sensitive"

or "possibly sensitive" feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed for any naturally-occurring "sensitive" or "possibly sensitive" features on this site.

— **ATTACHMENT E - Request to Seal Features.** A request to seal a naturally-occurring "sensitive" or "possibly sensitive" feature, that includes a justification as to why no reasonable and practicable alternative exists, is found at the end of this form. A request and justification has been provided for each feature.

10. X **ATTACHMENT F - Construction Plans.** Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information have been signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed permanent BMPs and measures are provided at the end of this form. Design Calculations, TCEQ Construction Notes, all man-made or naturally occurring geologic features, all proposed structural measures, and appropriate details must be shown on the construction plans.

11. X **ATTACHMENT G - Inspection, Maintenance, Repair and Retrofit Plan.** A plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is provided at the end of this form. The plan has been prepared and certified by the engineer designing the permanent BMPs and measures. The plan has been signed by the owner or responsible party. The plan includes procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofits as well as a discussion of record keeping procedures.

12. X The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.

— Pilot-scale field testing (including water quality monitoring) may be required for BMPs that are not contained in technical guidance recognized by or prepared by the executive director.

— **ATTACHMENT H - Pilot-Scale Field Testing Plan.** A plan for pilot-scale field testing is provided at the end of this form.

13. X **ATTACHMENT I -Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is provided at the end of this form. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity which increase erosion that results in water quality degradation.

Responsibility for maintenance of permanent BMPs and measures after construction is complete.

14. X The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership


of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.

15. X A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **PERMANENT STORMWATER SECTION** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Daryl D. Pawelek

Print Name of Customer/Agent



Signature of Customer/Agent

7-30-14

Date

PERMANENT STORMWATER SECTION

5. **Attachment A- 20% or Less Impervious Cover Waiver**

Not Applicable.

6. **Attachment B- BMP's for Upgradient Stormwater**

Permanent BMP's or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient of the site because the upgradient stormwater runoff that enters this site will be conveyed via interceptor/bypass channels and culverts around on-site permanent BMP's and the off-site water is of different land ownership predominantly in an existing residential state.

7. **Attachment C- BMP's for On-Site Stormwater**

The proposed BMP's for the parking areas and sidewalks are natural and engineered vegetative filter strips downstream of the proposed impervious cover areas. With these BMP's, the storm water will drain in a sheet flow manner, from the paved areas across either 15 ft. of engineered vegetative filter strips or 50 ft. of natural vegetative filter strip. The 80% removal requirement shall be achieved (per TCEQ RG-348) when the natural and engineered vegetative filter strips have a contributing drainage area less than 72 feet and the slope of the engineered vegetated filter strip has a 20% maximum slope and the natural vegetated filter strip has a 10% maximum slope. Additionally, two proposed stormwater detention ponds will aid in the sedimentation of solids and improve the overall water quality prior to stormwater exiting the site.

8. **Attachment D- BMP's for Surface Streams**

The proposed BMP's for this site include natural and engineered vegetative filter strips. The vegetative filter strips will filter the storm water runoff coming off of the parking areas. With these BMP's, the storm water will drain, in a sheet flow manner, from the parking areas across the grass filter strips. With the contributing drainage areas being less than 72 feet and the slope of the engineered vegetated filter strip being 20% or less and the slope of the natural vegetated filter strip being 10% or less, the 80% removal requirement will be achieved (per TCEQ RG-348) and will prevent pollutants from entering surface streams, sensitive features, or the aquifer.


10. **Attachment F- Construction Plans and Calculations**

The design criteria/requirements for the Natural and Engineered Vegetative Filter Strips was taken from the TCEQ "Calculation Template 4-20-09" spreadsheet for Vegetative Filter Strips and is shown below.

"There are no calculations required for determining the load or size of vegetative filter strips. The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with a maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%."

See the Site Plan (Sheet S1) for the locations and detail of the vegetative filter strips.

TSS REMOVAL CALCULATIONS
PREPARED BY
PAWELEK & MOY, INC.
FOR
EDEN HILL – LAKEVIEW SITE PRIVATE PARK



Daryl D. Pawelek P.E.
7-30-14

**EDEN HILL LAKEVIEW SITE- PRIVATE PARK
PERMANENT BEST MANAGEMENT PRACTICE SUMMARY
8.47 ACRE SITE**

Watershed Area	Permanent BMP	Drainage Area (Acres)	Imp. Cover (Acres)	Target TSS Removal (lb/yr)	TSS Removal Provided (lb/yr)
A(Onsite)	Vegetative Filter Strips	1.050	0.552	495	495
A(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
¹ B1	Uncaptured	0.530	0.000	0	0
B2	Vegetative Filter Strips	0.310	0.136	122	122
¹ C1	Uncaptured	0.610	0.000	0	0
C2	Vegetative Filter Strips	0.490	0.172	154	154
C3(Onsite)	Vegetative Filter Strips	0.030	0.014	13	13
C3(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
¹ F	Uncaptured	5.450	0.000	0	0
Total	-----	8.510	0.902	810	810

Notes:

1. Uncaptured area without impervious cover, no treatment necessary

Texas Commission on Environmental Quality

TSS Removal Calculations 04-20-2009

Project Name: **Eden Hill - Private Park**

Date Prepared: **7/28/2014**

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M\ TOTAL\ PROJECT}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan *	8.510	acres
Predevelopment impervious area within the limits of the plan *	0.000	acres
Total post-development impervious area within the limits of the plan *	0.902	acres
Total post-development impervious cover fraction *	0.106	
P =	33	inches

$L_{M\ TOTAL\ PROJECT} =$ **810** lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = **9**

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan =	8.510	acres
Predevelopment impervious area within the limits of the plan =	0.000	acres
Total post-development impervious area within the limits of the plan =	0.902	acres
Total post-development impervious cover fraction =	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}}$ = 810 lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 9

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	1	A(onsite) - Engineered VFS
Total drainage basin/outfall area =	1.050	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.552	acres
Post-development impervious fraction within drainage basin/outfall area =	0.526	
$L_{M \text{ THIS BASIN}}$ =	495	lbs.

16. Vegetated Filter Strips

Designed as Required in RG-348

Pages 3-55 to 3-57

There are no calculations required for determining the load or size of vegetative filter strips. The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%.

If vegetative filter strips are proposed for an interim permanent BMP, they may be sized as described on Page 3-56 of RG-348.

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan =	8.510	acres
Predevelopment impervious area within the limits of the plan =	0.000	acres
Total post-development impervious area within the limits of the plan =	0.902	acres
Total post-development impervious cover fraction =	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}}$ = 810 lbs.

The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 9

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	2	A(offsite) - Engineered VFS
Total drainage basin/outfall area =	0.020	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.014	acres
Post-development impervious fraction within drainage basin/outfall area =	0.700	
$L_{M \text{ THIS BASIN}}$ =	13	lbs.

16. Vegetated Filter Strips

Designed as Required in RG-348

Pages 3-55 to 3-57

There are no calculations required for determining the load or size of vegetative filter strips. The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%.

If vegetative filter strips are proposed for an interim permanent BMP, they may be sized as described on Page 3-56 of RG-348.

Texas Commission on Environmental Quality

TSS Removal Calculations 04-20-2009

Project Name: Eden Hill - Private Park

Date Prepared: 7/28/2014

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan =	8,510	acres
Predevelopment impervious area within the limits of the plan =	0.000	acres
Total post-development impervious area within the limits of the plan =	0.902	acres
Total post-development impervious cover fraction =	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}}$ = 810 lbs.

The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 9

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	3	Uncaptured B1
Total drainage basin/outfall area =	0.530	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious fraction within drainage basin/outfall area =	0.00	
$L_{M \text{ THIS BASIN}}$ =	0	lbs.

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M\ TOTAL\ PROJECT}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan =	8.510	acres
Predevelopment impervious area within the limits of the plan =	0.000	acres
Total post-development impervious area within the limits of the plan =	0.902	acres
Total post-development impervious cover fraction =	0.106	
P =	33	inches

$L_{M\ TOTAL\ PROJECT} = 810$ lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = **9**

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	4	B2 - Natural VFS
Total drainage basin/outfall area =	0.310	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.136	acres
Post-development impervious fraction within drainage basin/outfall area =	0.439	
$L_{M\ THIS\ BASIN} =$	122	lbs.

16. Vegetated Filter Strips

Designed as Required in RG-348

Pages 3-55 to 3-57

There are no calculations required for determining the load or size of vegetative filter strips. The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%.

If vegetative filter strips are proposed for an interim permanent BMP, they may be sized as described on Page 3-56 of RG-348.

Texas Commission on Environmental Quality

TSS Removal Calculations 04-20-2009

Project Name: Eden Hill - Private Park

Date Prepared: 7/28/2014

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan *	8.510	acres
Predevelopment impervious area within the limits of the plan *	0.000	acres
Total post-development impervious area within the limits of the plan *	0.902	acres
Total post-development impervious cover fraction *	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}} = 810$ lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = **9**

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	5	Uncaptured - C1
Total drainage basin/outfall area =	0.620	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious fraction within drainage basin/outfall area =	0.00	
$L_{M \text{ THIS BASIN}} =$	0	lbs.

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348. Characters shown in red are data entry fields. Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where: $L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load
 A_N = Net increase in impervious area for the project
 P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan *	8.510	acres
Predevelopment impervious area within the limits of the plan *	0.000	acres
Total post-development impervious area within the limits of the plan *	0.902	acres
Total post-development impervious cover fraction *	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}} = 810$ lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 9

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	6	C2 - Natural VFS
Total drainage basin/outfall area =	0.490	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.172	acres
Post-development impervious fraction within drainage basin/outfall area =	0.351	
$L_{M \text{ THIS BASIN}} =$	154	lbs.

16. Vegetated Filter Strips

Designed as Required in RG-348

Pages 3-55 to 3-57

There are no calculations required for determining the load or size of vegetative filter strips. The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%.

If vegetative filter strips are proposed for an interim permanent BMP, they may be sized as described on Page 3-56 of RG-348.

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348. Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan *	8.510	acres
Predevelopment impervious area within the limits of the plan *	0.000	acres
Total post-development impervious area within the limits of the plan*	0.902	acres
Total post-development impervious cover fraction *	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}}$ = 810 lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 9

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	7	C3(onsite) - Engineered VFS
Total drainage basin/outfall area =	0.030	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.014	acres
Post-development impervious fraction within drainage basin/outfall area =	0.467	
$L_{M \text{ THIS BASIN}}$ =	13	lbs.

16. Vegetated Filter Strips

Designed as Required in RG-348

Pages 3-55 to 3-57

There are no calculations required for determining the load or size of vegetative filter strips. The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%.

If vegetative filter strips are proposed for an interim permanent BMP, they may be sized as described on Page 3-56 of RG-348.

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan =	8.510	acres
Predevelopment impervious area within the limits of the plan =	0.000	acres
Total post-development impervious area within the limits of the plan =	0.902	acres
Total post-development impervious cover fraction =	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}}$ = 810 lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 9

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	8	C3(offsite) - Engineered VFS
Total drainage basin/outfall area =	0.020	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.014	acres
Post-development impervious fraction within drainage basin/outfall area =	0.700	
$L_{M \text{ THIS BASIN}}$ =	13	lbs.

16. Vegetated Filter Strips

Designed as Required in RG-348

Pages 3-55 to 3-57

There are no calculations required for determining the load or size of vegetative filter strips.

The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%.

If vegetative filter strips are proposed for an interim permanent BMP, they may be sized as described on Page 3-56 of RG-348.

Texas Commission on Environmental Quality

TSS Removal Calculations 04-20-2009

Project Name: Eden Hill - Private Park

Date Prepared: 7/28/2014

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Comal	
Total project area included in plan * =	8.510	acres
Predevelopment impervious area within the limits of the plan * =	0.000	acres
Total post-development impervious area within the limits of the plan * =	0.902	acres
Total post-development impervious cover fraction * =	0.106	
P =	33	inches

$L_{M \text{ TOTAL PROJECT}} = 810$ lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 9

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	9	Uncaptured F
Total drainage basin/outfall area =	5.450	acres
Predevelopment impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious area within drainage basin/outfall area =	0.000	acres
Post-development impervious fraction within drainage basin/outfall area =	0.00	
$L_{M \text{ THIS BASIN}} =$	0	lbs.

11. **Attachment G- Inspection, Maintenance, Repair and Retrofit Plan**

The Maintenance Plan and Scheduled Inspection Plan is located at the end of this section.

12. **Attachment H- Pilot-Scale Field Testing Plan**

Not Applicable.

The proposed BMP's for this site were designed according to the TCEQ Technical Guidance Manual.

13. **Attachment I – Measures for Minimizing Surface Stream Contamination**

As mentioned previously, the proposed parking areas drain to either a natural or engineered vegetative filter strip which then outfall into a proposed detention pond. These proposed detention ponds allow for additional solids/pollutants time to settle. This additional time for settlement will aid in the improvement of the overall water quality and further reduce the impact of the pollutants on surface streams, sensitive features (no sensitive features on this site), or the aquifer. Located at the outfall points of the detention ponds is a proposed velocity control measure which utilizes heavy rock riprap to dissipate the higher flow velocities prior to entering the natural vegetation areas.

Attachment "G"
Maintenance Plan and Schedule for Vegetative Filter Strip

PROJECT NAME: Eden Hill – Lakeview Site
LOCATION: South of Eden Hill Communities, across Lakeview Blvd.
CITY, STATE, ZIP: New Braunfels, Texas 78130

VEGETATIVE FILTER STRIP (per TCEQ: RG-348)

Pest Management: An Integrated Pest Management (IPM) Plan shall be implemented consisting of minimal or no use of herbicides for insect and weed control. Weeds shall be manually removed from the vegetative filter strip where possible and if an abundance of weeds/insects are present, the filter strip shall be sprayed with an environmentally/vegetative safe pesticide/herbicide.

Seasonal Mowing and Lawn Care: If the filter strip is made up of turf grass, it should be mowed as needed to limit vegetation height to 18 inches, using a mulching mower (or removal of clippings). If native grasses are used, the filter may require less frequent mowing, but at a minimum of twice annually. Grass clippings and brush debris should not be deposited on the vegetated filter strip areas. Regular mowing shall include weed control practices, with herbicide use kept to a minimum.

Inspection: The filter strip shall be inspected at a minimum of twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable. The strip shall be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance needs. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish shallow overland flow.

Debris and Litter Removal: All filter strips shall be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but shall be performed no less than 4 times per year.


Sediment Removal: Sediment removal is not normally required, since the vegetation normally grows through it and binds it to the soil. However, sediment may accumulate along the upstream boundary of the strip preventing uniform overland flow. Excess sediment shall be removed by hand or with flat-bottomed shovels.

Grass Reseeding and mulching: A healthy dense grass shall be maintained on the filter strip. If areas are eroded, they shall be filled, compacted and reseeded so that the final grade is level. Grass damaged during the sediment removal process shall be promptly replaced using the same seed mix used during filter strip establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established. Bare spots and areas identified during semi-annual inspections must be replanted and restored to meet specifications. Corrective maintenance, such as weeding or replanting shall be done more frequently in the first two to three years after installation to ensure stabilization. Dense vegetation may require irrigation immediately after planting, during particularly dry periods and when vegetation is initially established.

"Proper" disposal of accumulated silt shall be accomplished following Texas Commission on Environmental Quality guidelines and specifications.

An amended copy of this document will be provided to the Texas Commission on Environmental Quality within thirty (30) days of any changes in the following information.


Responsible Party for Maintenance Eden Home – Laurence Dahl
Address 631 Lakeview Blvd.
City, State Zip New Braunfels, Texas 78130
Telephone Number (830) 625-6291

Signature of Responsible Party  06/13/2014
DATE

Print Name of Responsible Party Laurence Dahl

Attachment "G"
Maintenance Plan and Schedule for Vegetative Filter Strip(cont.)

I have reviewed the attached Maintenance Plan and Schedule for the Vegetative Filter Strips and to the best of my knowledge certify that, if the Plan and Schedule are adhered to, the Vegetative Filter Strips will perform as designed.



Daryl D. Pawelek, P.E.
7-30-14

SIGNATURE PAGE:

[Handwritten Signature]
Applicant's Signature

July 28, 2014
Date

THE STATE OF Texas §


County of Comal §

BEFORE ME, the undersigned authority, on this day personally appeared Lawrence P. Dahl known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 28th day of July, 2014.

[Handwritten Signature]
NOTARY PUBLIC

Norma A. Madero
Typed or Printed Name of Notary



MY COMMISSION EXPIRES: 3/23/15

Texas Commission on Environmental Quality
Edwards Aquifer Protection Program
Application Fee Form

NAME OF PROPOSED REGULATED ENTITY: Eden Hill - Lakeview Site
 REGULATED ENTITY LOCATION: South of Eden Hill Communities, across Lakeview Blvd.
 NAME OF CUSTOMER: Eden Home, Inc. (dba, as Eden Hill Communities)
 CONTACT PERSON: Laurence P. Dahl PHONE: (830)625-6291
 (Please Print)

Customer Reference Number (if issued): CN 600951248 (nine digits)

Regulated Entity Reference Number (if issued): RN 101762425 (nine digits)

Austin Regional Office (3373) Hays Travis Williamson
San Antonio Regional Office (3362) Bexar Comal Medina Kinney Uvalde

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to (Check One):

- | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> Austin Regional Office | <input checked="" type="checkbox"/> San Antonio Regional Office |
| <input type="checkbox"/> Mailed to TCEQ:
TCEQ - Cashier
Revenues Section
Mail Code 214
P.O. Box 13088
Austin, TX 78711-3088 | <input type="checkbox"/> Overnight Delivery to TCEQ:
TCEQ - Cashier
12100 Park 35 Circle
Building A, 3rd Floor
Austin, TX 78753
512/239-1278 |

Site Location (Check All That Apply): Recharge Zone Contributing Zone Transition Zone

Type of Plan	Size	Fee Due
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	8.5 Acres	\$ 5,000.00
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$


Signature

7-30-14
Date

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282.

Texas Commission on Environmental Quality
 Edwards Aquifer Protection Program
Application Fee Schedule
 30 TAC Chapter 213 (effective 05/01/2008)

**Water Pollution Abatement Plans and Modifications
 Contributing Zone Plans and Modifications**

PROJECT	PROJECT AREA IN ACRES	FEE
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

PROJECT	COST PER LINEAR FOOT	MINIMUM FEE MAXIMUM FEE
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

PROJECT	COST PER TANK OR PIPING SYSTEM	MINIMUM FEE MAXIMUM FEE
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

PROJECT	FEE
Exception Request	\$500

Extension of Time Requests

PROJECT	FEE
Extension of Time Request	\$150

12340

Date	6/16/2014	Check Number	12340
------	-----------	--------------	-------

Invoice ID	Invoice Description	Amount Due	Discount	Payment
6/13/14] 061314	PARKING APPLICATION 8.45A	\$5,000.00	\$0.00	\$5,000.00
Vendor ID TEX057	Pay To Name TEXAS COMMISSION	Amount Due Total \$5,000.00	Discount Total \$0.00	Payment Total \$5,000.00

SAFEGUARD L1180 USA 95914 CK7503114L SFMS00053-L4-1CAN TO REORDER, CALL YOUR LOCAL SAFEGUARD DISTRIBUTOR AT 706-327-9550 J53MS40010000 Y12SF008215

ORIGINAL DOCUMENT PRINTED ON CHEMICAL REACTIVE PAPER WITH MICROPRINTED BORDER

BROADWAY BANK
800.531.7650
broadwaybank.com

88-2193/1140

12340

**EDEN HOME, INC.
DBA EDENHILL COMMUNITIES
OPERATING ACCOUNT**

631 LAKEVIEW BLVD.
NEW BRAUNFELS, TX 78130
(830) 625-6291

Account Number	CN600951248	Date	6/16/2014
Amount	\$5,000.00		

PAY

Five Thousand & No/100*****

TO THE
ORDER
OF

TEXAS COMMISSION
ON ENVIRONMENTAL QUALITY
REGIONAL OFFICE
SAN ANTONIO, TX

James B. M.
James B. M.

THIS DOCUMENT CONTAINS HEAT SENSITIVE INK. TOUCH OR PRESS HERE - RED IMAGE DISAPPEARS WITH HEAT.

012340 1140219331 4100023867



TCEQ Use Only

TCEQ Core Data Form

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input type="checkbox"/> Other	
2. Attachments Describe Any Attachments: (ex. Title V Application, Waste Transporter Application, etc.)		
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Water Pollution Abatement Plan (WPAP)		
3. Customer Reference Number (if issued)		4. Regulated Entity Reference Number (if issued)
CN 600951248		RN 101762425

SECTION II: Customer Information

5. Effective Date for Customer Information Updates (mm/dd/yyyy)			
6. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check only one of the following:			
<input type="checkbox"/> Owner	<input type="checkbox"/> Operator	<input type="checkbox"/> Owner & Operator	
<input type="checkbox"/> Occupational Licensee	<input type="checkbox"/> Responsible Party	<input type="checkbox"/> Voluntary Cleanup Applicant	<input type="checkbox"/> Other: _____
7. General Customer Information			
<input type="checkbox"/> New Customer		<input type="checkbox"/> Update to Customer Information	<input type="checkbox"/> Change in Regulated Entity Ownership
<input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State)		<input checked="" type="checkbox"/> No Change**	
**If "No Change" and Section I is complete, skip to Section III – Regulated Entity Information.			
8. Type of Customer:			
<input type="checkbox"/> Corporation	<input type="checkbox"/> Individual	<input type="checkbox"/> Sole Proprietorship- D.B.A	
<input type="checkbox"/> City Government	<input type="checkbox"/> County Government	<input type="checkbox"/> Federal Government	<input type="checkbox"/> State Government
<input type="checkbox"/> Other Government	<input type="checkbox"/> General Partnership	<input type="checkbox"/> Limited Partnership	<input type="checkbox"/> Other: _____
9. Customer Legal Name (If an individual, print last name first: ex: Doe, John)			
		If new Customer, enter previous Customer below	End Date:
10. Mailing Address:			
City	State	ZIP	ZIP + 4
11. Country Mailing Information (if outside USA)		12. E-Mail Address (if applicable)	
13. Telephone Number		14. Extension or Code	15. Fax Number (if applicable)
() -		-	() -
16. Federal Tax ID (9 digits)	17. TX State Franchise Tax ID (11 digits)	18. DUNS Number (if applicable)	19. TX SOS Filing Number (if applicable)
20. Number of Employees		21. Independently Owned and Operated?	
<input type="checkbox"/> 0-20	<input type="checkbox"/> 21-100	<input type="checkbox"/> 101-250	<input type="checkbox"/> 251-500
<input type="checkbox"/> 501 and higher	<input type="checkbox"/> Yes		<input type="checkbox"/> No

SECTION III: Regulated Entity Information

22. General Regulated Entity Information (If 'New Regulated Entity' is selected below this form should be accompanied by a permit application)			
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information <input type="checkbox"/> No Change** (See below)			
**If "NO CHANGE" is checked and Section I is complete, skip to Section IV, Preparer Information.			
23. Regulated Entity Name (name of the site where the regulated action is taking place)			
Eden Hill - Lakeview Site			

24. Street Address of the Regulated Entity: <i>(No P.O. Boxes)</i>	Not available at this time.						
	City		State		ZIP		ZIP + 4
25. Mailing Address:	Eden Home, Inc. (dba Eden Hill Communities)						
	631 Lakeview Blvd.						
	City	New Braunfels	State	Texas	ZIP	78130	ZIP + 4 4098
26. E-Mail Address:	larryd@edenhill.org						
27. Telephone Number	28. Extension or Code		29. Fax Number <i>(if applicable)</i>				
(830)625-6291	-		(830)620-7786				
30. Primary SIC Code (4 digits)	31. Secondary SIC Code (4 digits)		32. Primary NAICS Code (5 or 6 digits)		33. Secondary NAICS Code (5 or 6 digits)		
7999			712190				
34. What is the Primary Business of this entity? <i>(Please do not repeat the SIC or NAICS description.)</i>							
Nature Park for an Assisted Living Facility.							

Questions 34 - 37 address geographic location. Please refer to the instructions for applicability.

35. Description to Physical Location:	Approximately 0.25 miles northwest of the intersection of River Road and Lakeview Blvd. on the south side of Lakeview Blvd.				
36. Nearest City	County		State		Nearest ZIP Code
New Braunfels	Comal		Texas		78130
37. Latitude (N) In Decimal:	29.72312		38. Longitude (W) In Decimal:	98.12732	
Degrees	Minutes	Seconds	Degrees	Minutes	Seconds
29	43	23	98	07	38

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form or the updates may not be made. If your Program is not listed, check other and write it in. See the Core Data Form instructions for additional guidance.

<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input checked="" type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Industrial Hazardous Waste	<input type="checkbox"/> Municipal Solid Waste
<input type="checkbox"/> New Source Review - Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS	<input type="checkbox"/> Sludge
<input type="checkbox"/> Stormwater	<input type="checkbox"/> Title V - Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil	<input type="checkbox"/> Utilities
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Waste Water	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:


SECTION IV: Preparer Information

40. Name:	Daryl D. Pawelek, P.E.		41. Title:	Civil Engineer	
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address		
(830)629-2563	-	(830)629-2564	daryl.pawelek@sbcglobal.net		

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 9 and/or as required for the updates to the ID numbers identified in field 39.

(See the Core Data Form instructions for more information on who should sign this form.)

Company:	Pawelek & Moy, Inc.	Job Title:	Project Engineer		
Name <i>(In Print)</i> :	Daryl D. Pawelek		Phone:	(830)629-2563	
Signature:			Date:	7-30-14	



CIVIL ENGINEERING & CONSULTING SERVICES

- RESIDENTIAL DEVELOPMENT
- SITE DEVELOPMENT
- PUBLIC WORKS
- UTILITIES

October 1, 2014

Mr. Neal Denton
 TCEQ San Antonio Regional Office – Region 13
 14250 Judson Rd.
 San Antonio, Texas 78233-4480

RECEIVED

OCT 09 2014

Re: Response to TCEQ Comments dated September 25, 2014
 Edwards Aquifer, Comal County

COUNTY ENGINEER

NAME OF PROJECT: **Eden Hill – Lakeview Site**; Located approximately 0.25 miles northwest of the intersection of River Road and Lakeview Blvd. on the south side of Lakeview Blvd.; New Braunfels, Texas.

TYPE OF PLAN: Request for Approval of a **Water Pollution Abatement Plan**; 30 Texas Administrative Code (TAC) Chapter 213 Edwards Aquifer; Additional ID No. 13-14073101; Investigation No. 1186365; RN101762425;

Dear Mr. Denton,

Pawelek & Moy, Inc. (P&M) has addressed the comments by the TCEQ dated September 25, 2014 for the above mentioned project. P&M has taken the following actions with regards to the comments:

<u>Comment</u>	<u>Response</u>
1	The calculations are shown per RG-348 with the 2-yr storm. The proposed depths of swales are shown on the typical sections that represent depths that exceed depth of flow plus 6" freeboard. Stone stabilization in Section C-C is shown to a depth of 1' which is greater than 3" above the flow depth. Side slopes are 3:1 which are flatter than 2:1.
2	The silt fence has been moved to just downstream of the limits of disturbance.
3	Based on our conversation with Steve Frost, P&M understands that he discussed this with you after revisiting the site and S-6 should have been identified as an old fence post hole and that no other documentation is required.

Please call if you have questions regarding these responses. Thank you for your assistance.

Sincerely,

Daryl D. Pawelek, P.E.


Attachments:

- Revised S1

cc: Mr. Larry Dahl – Eden Hill

RECEIVED TCEQ
 SAN ANTONIO
 REGION
 2014 OCT -2 AM 8:46

F:\1401.01 - EDEN HILLS PARKING\DWG\WPAP\14-09-26 - TCEQ COMMENTS\TCEQRESPONSELETTER-10-01-14.DOC









OWNER:
EDEN HOME, INC.
dba. EDEN HILL COMMUNITIES
631 LAKEVIEW BLVD
NEW BRAUNFELS, TX 78130

SITE PLAN FOR
EDENHILL COMMUNITIES - PRIVATE PARK
 NEW BRAUNFELS, TEXAS

EDEN HILL LAKEVIEW SITE- PRIVATE PARK
PERMANENT BEST MANAGEMENT PRACTICE SUMMARY
8.47 ACRE SITE

Watershed Area	Permanent BMP	Drainage Area (Acres)	Imp. Cover (Acres)	Target TSS Removal (lb/yr)	TSS Removal Provided (lb/yr)
A(Onsite)	Vegetative Filter Strips	1.050	0.552	495	495
A(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
1B1	Uncaptured	0.530	0.000	0	0
B2	Vegetative Filter Strips	0.310	0.136	122	122
1C1	Uncaptured	0.610	0.000	0	0
C2	Vegetative Filter Strips	0.490	0.172	154	154
C3(Onsite)	Vegetative Filter Strips	0.030	0.014	13	13
C3(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
1F	Uncaptured	5.450	0.000	0	0
Total		8.510	0.902	810	810

Notes:
1. Uncaptured area without impervious cover, no treatment necessary



- LEGEND**
- S.F. SILT FENCE
 - LIMITS OF AREA TO BE DISTURBED
 - ROCK BERM
 - GABION MATTRESS (VELOCITY CONTROL)
 - ROCK RIPRAP (VELOCITY CONTROL)
 - PROPOSED VEGETATIVE FILTER
 - PROPOSED PAD
 - PROPOSED CONCRETE
 - TEMPORARY STABILIZED CONSTRUCTION ENTRANCE/EXIT
 - CONCRETE WASHOUT
 - EXISTING FLOW DIRECTION
 - EXISTING CONTOURS
 - PROPOSED CONTOURS
 - PROPERTY LINE
 - S-# POTENTIAL RECHARGE FEATURE (PRF)
 - Ke# EDWARDS PERSON LIMESTONE
 - Knm NAVARRO AND TAYLOR GROUPS, UNDIVIDED
 - FAULT

IMPERVIOUS COVER SUMMARY

IMPERVIOUS COVER OF PROJECT SITE	Sq. Ft.	Sq. Ft./Acre	Acres
STRUCTURES/ROOFTOPS	0	+ 43,560 =	0.00
PAVING/DRIVES/PADS/SIDEWALKS	39,280	+ 43,560 =	0.90
TOTAL IMPERVIOUS COVER	39,280	+ 43,560 =	0.90

TOTAL IMPERVIOUS COVER + TOTAL ACREAGE x 100 = 10.63 %

TOTAL PROJECT SITE ACREAGE = 8.47 Ac.

NOTES:


- SEE DRAINAGE AREA MAP SHEET D-1 FOR OVERALL DRAINAGE AREAS.
- SOIL STABILIZATION NOTE:**
IN ALL AREAS TO BE DISTURBED OUTSIDE OF THE LIMITS OF PAVING, SIDEWALKS, LANDSCAPING, ETC., AND FOR THE ENGINEERED VEGETATIVE FILTER STRIPS, VEGETATIVE STABILIZATION IN ACCORDANCE WITH RC-348 COMPLYING WITH THE EDWARDS AQUIFER RULES, ITEM 1.3.8-TEMPORARY VEGETATION, ITEM 1.3.9-BLANKETS AND MATTING, ITEM 1.3.9-HYDRAULIC MULCH AND/OR ITEM 1.3.11 SOD SHALL BE IMPLEMENTED. THE AREAS TO BE VEGETATED SHALL BE WATERED SUFFICIENTLY TO ESTABLISH 70% STABILIZATION.
- VELOCITY CONTROL NOTE:**
AT THE POINT WHERE PROPOSED DRAINAGE PIPES OUTFALL AND THE ON THE DOWNSTREAM SIDE OF THE DETENTION POND OUTFALLS, A VELOCITY CONTROL PROCEDURE UTILIZING HEAVY ROCK RIPRAP (TYPE "R" PER TxDOT ITEM 432) OR GABION MATTRESS (PER TxDOT ITEM 459) SHALL BE USED TO DISSIPATE THESE FLOWS (SEE DETAILS ON SHEET S2). THESE APPLICATIONS SHALL REMAIN IN PLACE AND NOT BE REMOVED UPON COMPLETION OF THE CONSTRUCTION ACTIVITIES.
- FLOODPLAIN NOTE:**
ACCORDING TO FEMA FIRM MAP PANEL No. 48091C0435F, EFFECTIVE DATE 9/2/2009, A PORTION OF THE PROJECT SITE LIES WITHIN THE 100 YR FLOODPLAIN.

REVISIONS

DATE	DESCRIPTION
9/24/14	ADDRESSED TCEQ COMMENTS 9/22/2014
10/07/14	ADDRESSED TCEQ COMMENTS 9/25/2014

DRAWN BY: D.G. III
CHECKED BY: J.J.M.
DATE: JULY 2014
JOB NO.: 1401.01

F:\1401.01 - Eden Hills Parking.dwg, 2014/10/01 7:46am Administrator



RECEIVED
OCT 9 9 2014
COUNTY ENGINEER



CIVIL ENGINEERING & CONSULTING SERVICES

- RESIDENTIAL DEVELOPMENT
- SITE DEVELOPMENT
- PUBLIC WORKS
- UTILITIES

September 24, 2014

Mr. Neal Denton
TCEQ San Antonio Regional Office – Region 13
14250 Judson Rd.
San Antonio, Texas 78233-4480

TCEQ-R13
SEP 25 2014
SAN ANTONIO RECEIVED
OCT 09 2014

COUNTY ENGINEER

Re: Response to TCEQ Comments dated September 12, 2014
Edwards Aquifer, Comal County
NAME OF PROJECT: **Eden Hill – Lakeview Site**; Located approximately 0.25 miles northwest of the intersection of River Road and Lakeview Blvd. on the south side of Lakeview Blvd.; New Braunfels, Texas.
TYPE OF PLAN: Request for Approval of a **Water Pollution Abatement Plan**; 30 Texas Administrative Code (TAC) Chapter 213 Edwards Aquifer;
Additional ID No. 13-14073101; Investigation No. 1186365; RN101762425;

Dear Mr. Denton,

Pawelek & Moy, Inc. (P&M) has addressed the comments by the TCEQ dated September 12, 2014 for the above mentioned project. P&M has taken the following actions with regards to the comments:

<u>Comment</u>	<u>Response</u>
1	The silt fence was moved and slopes added to the Site Plan in the area of the silt fence.
2	Sections for proposed swales have been added to the Site Plan with hydraulic data and storm events included.
3	Stone stabilization has been extended to include the entire swale that has a slope that exceeds 2%.
4	The limits of the area to potentially be disturbed has been added to the Site Plan.
5	The proposed curb is a flush curb which will allow runoff from the parking area to sheet flow onto the EVFS. The flush curb has been labeled.
6	Updated information from Frost Geosciences regarding the two features noted in this comment are included in the additional information provided by Frost Geosciences, which includes revised Geologic Assessment Table and Site Geologic Map.

Please call if you have questions regarding these responses. Thank you for your assistance.

Sincerely,

A handwritten signature in black ink, appearing to read "Daryl D. Pawelek". The signature is fluid and cursive, with the first name "Daryl" and last name "Pawelek" clearly distinguishable.

Daryl D. Pawelek, P.E.

Attachments:

- Revised S1
- Revised Geological Assessment Information






cc: Mr. Larry Dahl – Eden Hill

F:\1401.01 - EDEN HILLS PARKING\DWGWPAP\14-09-12 - TCEQ COMMENTS\TCEQRESPONSELETTER-09-24-14.DOC

**EDEN HILL LAKEVIEW SITE- PRIVATE PARK
PERMANENT BEST MANAGEMENT PRACTICE SUMMARY
8.47 ACRE SITE**

Watershed Area	Permanent BMP	Drainage Area (Acres)	Imp. Cover (Acres)	Target TSS Removal (lb/yr)	TSS Removal Provided (lb/yr)
A(Onsite)	Vegetative Filter Strips	1.050	0.552	495	495
A(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
B1	Uncaptured	0.530	0.000	0	0
B2	Vegetative Filter Strips	0.310	0.136	122	122
C1	Uncaptured	0.610	0.000	0	0
C2	Vegetative Filter Strips	0.490	0.172	154	154
C3(Onsite)	Vegetative Filter Strips	0.030	0.014	13	13
C3(Offsite)	Vegetative Filter Strips	0.020	0.014	13	13
F	Uncaptured	5.450	0.000	0	0
Total		8.510	0.902	810	810

Notes:
1. Uncaptured area without impervious cover, no treatment necessary



- LEGEND**
- S.F.** SILT FENCE
 - LIMITS OF AREA TO BE DISTURBED
 - ROCK BERM
 - GABION MATTRESS (VELOCITY CONTROL)
 - ROCK RIPRAP (VELOCITY CONTROL)
 - PROPOSED VEGETATIVE FILTER
 - PROPOSED PAD
 - PROPOSED CONCRETE
 - TEMPORARY STABILIZED CONSTRUCTION ENTRANCE/EXIT
 - CONCRETE WASHOUT
 - EXISTING FLOW DIRECTION
 - EXISTING CONTOURS
 - PROPOSED CONTOURS
 - PROPERTY LINE
 - S-#** POTENTIAL RECHARGE FEATURE (PRF)
 - Kep** EDWARDS PERSON LIMESTONE
 - Kkm** NAVARRO AND TAYLOR GROUPS, UNDIVIDED
 - FAULT

IMPERVIOUS COVER SUMMARY

IMPERVIOUS COVER OF PROJECT SITE	Sq. Ft.	Sq. Ft./Ac	Acres
STRUCTURES/ROOFTOPS	0	+ 43,560 =	0.00
PAVING/DRIVES/PADS/SIDEWALKS	39,280	+ 43,560 =	0.90
TOTAL IMPERVIOUS COVER	39,280	+ 43,560 =	0.90

TOTAL IMPERVIOUS COVER ÷ TOTAL ACREAGE × 100 = 10.63 %

TOTAL PROJECT SITE ACREAGE = 8.47 Ac.


NOTES:

- SEE DRAINAGE AREA MAP SHEET D-1 FOR OVERALL DRAINAGE AREAS.

SOIL STABILIZATION NOTE:
IN ALL AREAS TO BE DISTURBED OUTSIDE OF THE LIMITS OF PAVING, SIDEWALKS, LANDSCAPING, ETC., AND FOR THE ENGINEERED VEGETATIVE FILTER STRIPS, VEGETATIVE STABILIZATION IN ACCORDANCE WITH RG-348 COMPLYING WITH THE EDWARDS AQUIFER RULES, ITEM 1.3.8-TEMPORARY VEGETATION, ITEM 1.3.9-BLANKETS AND MATTING, ITEM 1.3.10-HYDRAULIC MULCH AND/OR ITEM 1.3.11 SOD SHALL BE IMPLEMENTED. THE AREAS TO BE VEGETATED SHALL BE WATERED SUFFICIENTLY TO ESTABLISH 70% STABILIZATION.

VELOCITY CONTROL NOTE:
AT THE POINT WHERE PROPOSED DRAINAGE PIPES OUTFALL AND THE ON THE DOWNSTREAM SIDE OF THE DETENTION POND OUTFALLS, A VELOCITY CONTROL PROCEDURE UTILIZING HEAVY ROCK RIPRAP (TYPE 'R' PER TXDOT ITEM 432) OR GABION MATTRESS (PER TXDOT ITEM 459) SHALL BE USED TO DISSIPATE THESE FLOWS (SEE DETAILS ON SHEET S2). THESE APPLICATIONS SHALL REMAIN IN PLACE AND NOT BE REMOVED UPON COMPLETION OF THE CONSTRUCTION ACTIVITIES.

FLOODPLAIN NOTE:
ACCORDING TO FEMA FIRM MAP PANEL No. 48091C0435F, EFFECTIVE DATE 9/2/2009, A PORTION OF THE PROJECT SITE LIES WITHIN THE 100 YR FLOODPLAIN.




REVISIONS


DATE	DESCRIPTION	ADDRESSED TCE COMMENTS
9/24/14		

DRAWN BY: D.G. III
CHECKED BY: J.J.M.
DATE: JULY 2014
JOB NO.: 1401.01


S1 OF 2



Location Map



Single-Family Residences



Site Geologic Map

Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 for the
 Eden Hill - Lakeview Site
 +/- 8.5 Acres
 New Braunfels, Texas


Frost GeoSciences, Inc. Control # FGS-E14102

Legend


- Fill - Fill Material
- Qal - Alluvium
- Kau - Austin Chalk
- Kef - Eagle Ford Shale
- Kbu - Buda Limestone
- Kdr - Del Rio Clay
- Kgt - Georgetown Limestone
- Kep - Edwards Person Limestone
- Kek - Edwards Kainer Limestone
- Kgr - Glen Rose Formation
- Kknm - Navarro and Taylor Groups, Undivided
- S# - Potential Recharge Feature (PRF)
- - Formation Contact
- - 100-Year Floodplain - Zone A
- - 100-Year Floodplain - Zone AE
- (shaded) - Other Flood Hazard Area - Zone X (shaded)

Floodplain Information Obtained From
 FIRN: Flood Insurance Rate Map
 Comal County, Texas: Panel # 48091C0435F, Revised 9/2/2009

Fault Information Obtained From:
 Bureau of Economic Geology, Geologic Atlas of Texas, San Antonio Sheet (1983)
 U.S. Geological Survey, Water Resources Investigations Report 94-4117 (1994)
 Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle (2000)



Chris Wickman
 Signature of Texas Licensed Geoscientist
 Chris Wickman, P.G. License No. 10403




1 inch = 40 feet
 Representative Fraction 1:480
 Contour Interval - 2 foot

GEOLOGIC ASSESSMENT TABLE			PROJECT NAME: Eden Hill - Lakeview Site (+/- 8.5 Acres)											FGS-E14102						
LOCATION			FEATURE CHARACTERISTICS										EVALUATION		PHYSICAL SETTING					
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10	11		12	
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)	TOPOGRAPHY	
						X	Y	Z		10						< 40	> 40	< 1.6	≥ 1.6	
S-1	N29° 43' 21.84"	W98° 7' 45.06"	MB	30	Kep	0.5	0.5	?	-	-	-	-	X	5	35	35		Yes		Hillside
S-2	N29° 43' 18.78"	W98° 7' 38.94"	O	5	Kep	10	50	-	-	-	-	-	CF	5	10	10		Yes		Hillside
S-3	N29° 43' 21.96"	W98° 7' 34.56"	MB	30	Kep	1	12	2.5	-	-	-	-	C	9	39	39		Yes		Hillside
S-4	N29° 43' 21.66"	W98° 7' 34.92"	F	20	Kep	30	650	25	-	10	-	-	CF	8	38	38		Yes		Cliff
S-5	N29° 43' 21.22"	W98° 7' 34.93"	MB	30	Kep	0.5	0.5	?	-	-	-	-	C	5	35	35		Yes		Hillside
S-6	N29° 43' 20.78"	W98° 7' 37.92"	MB	30	Kep	0.75	0.75	2	-	-	-	-	CF	5	35	35		Yes		Hillside

* DATUM 1983 North American Datum (NAD83)

2A TYPE	TYPE	2B POINTS	8A INFILLING	
C	Cave	30	N	None, exposed bedrock
SC	Solution Cavity	20	C	Coarse - cobbles, breakdown, sand, gravel
SF	Solution-enlarged fracture(s)	20	O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fault	20	F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
O	Other natural bedrock features	5	V	Vegetation. Give details in narrative description
MB	Manmade feature in bedrock	30	FS	Flowstone, cements, cave deposits
SW	Swallow Hole	30	X	Other materials
SH	Sinkhole	20		
CD	Non-karst closed depression	5		
Z	Zone, clustered or aligned features	30		



COUNTY ENGINEER

OCT 09 2014

RECEIVED

I have read, I understood, and I have followed the Texas Natural Resource Conservation Commission's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature *Christopher Wickman* Date January 13, 2014 Sheet 1 of 1

entire length of the southeastern project boundary with a dominant trend of approximately 45 to 50 degrees northeast-southwest. The fault scarp would potentially act as a discharge point of PRFs located on the project site. Based on review of the geologic maps of the area, the upwardly displaced formation to the northwest of the fault is the Edwards Limestone and the downward displaced formations, to the southeast of the fault, are Quaternary fluvial deposits and/or the Navarro and Taylor Groups. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 38 on the sensitivity scale, column 10 in the Geologic Assessment Table on Page 4 of this report. Frost GeoSciences, Inc. does consider this to be a sensitive feature.

Potential Recharge Feature # S-5 appears to be a utility valve buried within the ground. The feature is approximately 6 to 8 inches in diameter. The shutout valve was observed within the hole. Frost GeoSciences, Inc., rates the relative infiltration of the feature as low on figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 35 on the sensitivity scale, column 10 in the Geologic Assessment Table on page 4 of this report. Frost GeoSciences, Inc. does not consider the manhole to be a sensitive feature.

Potential Recharge Feature # S-6 appears to be a drilled core into the limestone boulder. The drilled hole was approximately 8 to 10 inches in diameter. The hole was approximately 1.5 to 2 feet deep and infilled with clay and sand. The feature may have been a former geotechnical boring, exploration boring or a water-well. If the hole is a water-well, it is the opinion of FGS that the feature be properly plugged and abandoned. Frost GeoSciences, Inc., rates the relative infiltration of the feature as low on figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 35 on the sensitivity scale, column 10 in the Geologic Assessment Table on page 4 of this report. Frost GeoSciences, Inc. does not consider the manhole to be a sensitive feature.

The Site is covered by a moderately dense stand of vegetative cover with several open grassy areas characterized by large stands of prickly pear cactus. Site visit photos indicating the condition of the property at the time of the on-site inspection are included in Appendix B. Overall

vegetation on the project site consists of ashe juniper (*Juniperus ashei*), live oak (*Quercus virginiana*), and cedar elm (*Ulmus crassifolia*), with agarita (*Berberis trifoliolata*), huisache (*Acacia farnesiana*), catclaw (*Acacia greggii*), Pencil Cactus (*Opuntia leptocaulis*) and prickly pear cactus (*Opuntia lindheimeri*). The variations in the vegetative cover on the property are visible in the 2012 aerial photo on Figures 9 and 10 in Appendix A.

Site visit photographs indicating the condition of the property at the time of the on-site inspection are included in Appendix B. The vegetative cover on the property is visible in the 2012 aerial photograph on Figures 8 and 9 in Appendix A.

According to the site plan provided by Pawelek and Moy, Inc., the surveyed elevations within the project area range from 622 feet in the southern portion of the project site to 730 feet in the northwestern portion of the Site. A copy of the site plan indicating the boundary of the project site and the elevations is included on the Site Geologic Map in Appendix C of this report.

According to the U.S.G.S. Water-Resources Investigations (WRI) Report 94-4117 and the Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle, the project site is located on the Cretaceous Edwards Person Formation, Kep and Kp respectively. The USGS WRI subdivides the Edwards Person Formation into three separate geologic members and indicates that the project site is located on the Leached and Collapsed member of the Edwards Person formation (Kep).

The Leached and Collapsed Member of the Edwards Person Limestone consists of crystalline limestone, mudstone to grainstone with chert, and collapsed breccia. This member is stromatolitic limestone. The Leached and Collapsed Member is characterized by bioturbated iron stained beds separated by massive limestone beds. This member is typically one of the most permeable and has extensive lateral development with large rooms. Overall thickness ranges from 70 to 90 feet thick. A copies of the USGS WRI Map and the Bureau of Economic Geology New Braunfels Quadrangle are included on Figures 7A and 7B in Appendix A. A copy of the Stratigraphic Column highlighting the outcropping formations is included on Page 3 of this report.

BEST MANAGEMENT PRACTICE (BMP)

Based on a visual inspection of the ground surface, the overall potential for fluid flow from the project site into the Edwards Aquifer appears to be low. The potential always exists to encounter solution cavities within the subsurface during excavating activities. Frost GeoSciences, Inc. is of the opinion that it is very important for construction personnel to be informed of the potential to encounter cavities in the subsurface that lack a surface expression. Construction personnel should also be informed of the proper protocol to follow in the event a karst feature is encountered during the development of the project site.


DISCLAIMER

This report has been prepared in general accordance with the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04) by a Licensed Texas Professional Geoscientist. All areas of the project site were carefully inspected for features that could contribute to the recharge of the Edwards Aquifer, however, this survey cannot preclude the presence of subsurface karst features that lack surface expression. This report is not intended to be a definitive investigation of all possible geologic or karst features at this site. All conclusions, opinions, and recommendations for Best Management Practices (BMP's) in this report are based on information obtained while researching the project, and on the site conditions at the time of our field investigation.

This report has been prepared for the exclusive use of Eden Hill. This report is based on available known records, a visual inspection of the project site, and the work generally accepted for a Geologic Assessment for Regulated Activities / Developments on the Edwards Aquifer Recharge / Transition Zone, relating to 30 TAC §213.5(b)(3), effective June 1, 1999.

REFERENCES


- 1) U.S.G.S. 7.5 Minute Quadrangle Map, New Braunfels West, Texas Sheet (1988).
- 2) Collins, Edward, W., 2000, Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle, Bureau of Economic Geology, The University of Texas at Austin, Texas.
- 3) Official Edwards Aquifer Recharge Zone Map, New Braunfels West, Texas Sheet (1988).
- 4) Small, Ted A. and Hanson, John A., 1994, Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Outcrop, Comal County, Texas.
U.S. Geological Survey Water Resources Investigations 94-4117.
- 5) Barnes, V.L., 1983, Geologic Atlas of Texas, San Antonio Sheet, Bureau of Economic Geology, The University of Texas at Austin, Texas.
- 6) Federal Emergency Management Agency (FEMA), September 29, 2010, Bexar County, Texas and Incorporated Areas, Flood Insurance Rate Map (FIRM), Panel #48091C0435F.
FEMA, Washington D.C.
- 7) U.S.D.A. Soil Conservation Service, Soil Survey of Comal and Hays Counties, Texas (1984).
- 8) TCEQ-0585-Instructions (Rev. 10-1-04). "Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zone".



PROJECT NAME:
 Geologic Site Assessment (WPAP)
 for Regulated Activities / Development on the
 Edwards Aquifer Recharge / Transition Zone
 Eden Home - Lakeview Site
 New Braunfels, Texas

Site Plan	
PROJECT NO.: FGS-E14102	DATE: January 13, 2014

FIGURE 1



PROJECT NAME:
Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Eden Home - Lakeview Site
New Braunfels, Texas


2012 Aerial Photograph with PRFs
National Agricultural Imagery Program

PROJECT NO.:
FGS-E14102


DATE: January 13, 2014



View of Potential Recharge Feature # S-5.



View of the interior of Potential Recharge Feature # S-5.



View of Potential Recharge Feature # S-6.



View of the interior of Potential Recharge Feature # S-6.