

Bryan W. Shaw, Ph.D., *Chairman*
Buddy Garcia, *Commissioner*
Carlos Rubinstein, *Commissioner*
Mark R. Vickery, P.G., *Executive Director*



RECEIVED

APR 19 2010

COUNTY ENGINEER

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

April 8, 2010

Mr. Richard N. Maier
Continental Homes of Texas, L.P.
12554 Riata Vista Circle, 2nd Floor
Austin, Texas 78727

Re: Edwards Aquifer, Comal County
NAME OF PROJECT: Manor Creek Subdivision, located approximately 2 miles west of Loop 337 on the northeast side of State Highway 46, New Braunfels, Texas
TYPE OF PLAN: Request for Modification of an Approved **Water Pollution Abatement Plan** (WPAP); 30 Texas Administrative Code (TAC) Chapter 213 Edwards Aquifer
Edwards Aquifer Protection Program ID No. 2439.03, Investigation No. 792425
Regulated Entity No. RN104801568

Dear Mr. Maier:

The Texas Commission on Environmental Quality (TCEQ) has completed its review of the WPAP modification request for the above-referenced project submitted to the San Antonio Regional Office by The Schultz Group, Inc. on behalf of Continental Homes of Texas, L.P. on February 12, 2010. As presented to the TCEQ, the Temporary and Permanent Best Management Practices (BMPs) and construction plans were prepared by a Texas Licensed Professional Engineer to be in general compliance with the requirements of 30 TAC Chapter 213. These planning materials were sealed, signed and dated by a Texas Licensed Professional Engineer. Therefore, based on the engineer's concurrence of compliance, the planning materials for construction of the proposed project and pollution abatement measures are **hereby approved** subject to applicable state rules and the conditions in this letter. The applicant or a person affected may file with the chief clerk a motion for reconsideration of the executive director's final action on this Edwards Aquifer Protection Plan. A motion for reconsideration must be filed no later than 23 days after the date of this approval letter. *This approval expires two (2) years from the date of this letter unless, prior to the expiration date, more than 10 percent of the construction has commenced on the project or an extension of time has been requested.*

BACKGROUND

The original WPAP for this residential project was approved by letter dated April 4, 2006. The single family residential project had an area of approximately 252.038 acres. It included 343 lots, roads, and utilities. Impervious cover was 50.29 acres (19.95 percent).

PROJECT DESCRIPTION

The proposed residential project will have an area of approximately 266.92 acres. It will include 340 single-family residential lots, roads, and utilities. The impervious cover will be 53.141 acres (19.91 percent). About 0.123 acre of the site was dedicated to TxDOT after the April 4, 2006 WPAP approval and about 15 acres was added to the site west of its north corner. Project wastewater will be disposed of by conveyance to the existing Gruene Road Wastewater Treatment Plant owned by New Braunfels Utilities.

PERMANENT POLLUTION ABATEMENT MEASURES

This single-family residential project will not have more than 20 percent impervious cover.

GEOLOGY

The site is located within the Edwards Aquifer recharge zone. Reddish-brown and dark brown stony clay soils reportedly overlie limestones of the Person Formation of the Edwards Group. According to the geologic assessment included with the initial application and additional information submitted during its review, 104 geologic and man-made features were identified at the site. Thirteen of the features, S15, S21, S25, S35, S38, S61, S63, S70, S71, S81, S85, S89, and S93, were initially assessed as sensitive. Two of the sensitive features, S-38 and S-93, received additional evaluation by the geologist, who determined the features not to be sensitive. The original assessment was shown conducted April 5-14 and 21-28, 2005. The San Antonio Regional Office site inspection of March 22, 2006, revealed that the site was generally as described by the geologic assessment. Additional assessment was shown conducted December 19, 2009 for the 15 acres added to the site. Two additional features were described for the added acreage. Both were shown not sensitive. The San Antonio Regional Office did not conduct a site assessment for the added acreage.

Natural buffers were shown in the April 4, 2006 WPAP approval letter for eleven sensitive features. According to FEMA maps, the features are shown near or within Zone A of the 100-year flood along Blieders Creek. All of the sensitive features except S-89 are shown surrounded with rock berms. Feature S-89 is shown in a "no disturbance" area delineated on the site plan for the WPAP approved April 4, 2006. No regulated activities (such as construction or soil disturbing activities) will take place within the buffers or the "no disturbance" area.

SPECIAL CONDITIONS

- I. This modification is subject to all Special and Standard Conditions listed in the WPAP approval letter dated April 4, 2006.
- II. Since this project will not have more than 20 percent impervious cover, an exemption from additional permanent BMPs is approved. If the percent impervious cover ever increases above 20 percent or the land use changes, the exemption for the whole site as described in the property boundaries required by §213.4(g), may no longer apply and the property owner must notify the appropriate regional office of these changes.

RECEIVED

APR 19 2010

COUNTY ENGINEER

STANDARD CONDITIONS

1. Pursuant to Chapter 7 Subchapter C of the Texas Water Code, any violations of the requirements in 30 TAC Chapter 213 may result in administrative penalties.
2. The holder of the approved Edwards Aquifer protection plan must comply with all provisions of 30 TAC Chapter 213 and all best management practices and measures contained in the approved plan. Additional and separate approvals, permits, registrations and/or authorizations from other TCEQ Programs (i.e., Stormwater, Water Rights, UIC) can be required depending on the specifics of the plan.
3. In addition to the rules of the Commission, the applicant may also be required to comply with state and local ordinances and regulations providing for the protection of water quality.

Prior to Commencement of Construction:

4. Within 60 days of receiving written approval of an Edwards Aquifer Protection Plan, the applicant must submit to the San Antonio Regional Office, proof of recordation of notice in the county deed records, with the volume and page number(s) of the county deed records of the county in which the property is located. A description of the property boundaries shall be included in the deed recordation in the county deed records. A suggested form (Deed Recordation Affidavit, TCEQ-0625) that you may use to deed record the approved WPAP is enclosed.
5. All contractors conducting regulated activities at the referenced project location shall be provided a copy of this notice of approval. At least one complete copy of the approved WPAP and this notice of approval shall be maintained at the project location until all regulated activities are completed.
6. Modification to the activities described in the referenced WPAP application following the date of approval may require the submittal of a plan to modify this approval, including the payment of appropriate fees and all information necessary for its review and approval prior to initiating construction of the modifications.
7. The applicant must provide written notification of intent to commence construction, replacement, or rehabilitation of the referenced project. Notification must be submitted to the San Antonio Regional Office no later than 48 hours prior to commencement of the regulated activity. Written notification must include the date on which the regulated activity will commence, the name of the approved plan and program ID number for the regulated activity, and the name of the prime contractor with the name and telephone number of the contact person. The executive director will use the notification to determine if the approved plan is eligible for an extension.
8. Temporary erosion and sedimentation (E&S) controls, i.e., silt fences, rock berms, stabilized construction entrances, or other controls described in the approved WPAP, must be installed prior to construction and maintained during construction. Temporary E&S controls may be removed when vegetation is established and the construction area is stabilized. If a water quality pond is

proposed, it shall be used as a sedimentation basin during construction. The TCEQ may monitor stormwater discharges from the site to evaluate the adequacy of temporary E&S control measures. Additional controls may be necessary if excessive solids are being discharged from the site.

9. All borings with depths greater than or equal to 20 feet must be plugged with non-shrink grout from the bottom of the hole to within three (3) feet of the surface. The remainder of the hole must be backfilled with cuttings from the boring. All borings less than 20 feet must be backfilled with cuttings from the boring. All borings must be backfilled or plugged within four (4) days of completion of the drilling operation. Voids may be filled with gravel.

During Construction:

10. During the course of regulated activities related to this project, the applicant or agent shall comply with all applicable provisions of 30 TAC Chapter 213, Edwards Aquifer. The applicant shall remain responsible for the provisions and conditions of this approval until such responsibility is legally transferred to another person or entity.
11. This approval does not authorize the installation of temporary aboveground storage tanks on this project. If the contractor desires to install a temporary aboveground storage tank for use during construction, an application to modify this approval must be submitted and approved prior to installation. The application must include information related to tank location and spill containment. Refer to Standard Condition No. 6, above.
12. If any sensitive feature (caves, solution cavities, sink holes, etc.) is discovered during construction, all regulated activities near the feature must be suspended immediately. The applicant or his agent must immediately notify the San Antonio Regional Office of the discovery of the feature. Regulated activities near the feature may not proceed until the executive director has reviewed and approved the methods proposed to protect the feature and the aquifer from potentially adverse impacts to water quality. The plan must be sealed, signed, and dated by a Texas Licensed Professional Engineer.
13. No wells exist on the site. All water wells, including injection, dewatering, and monitoring wells must be in compliance with the requirements of the Texas Department of Licensing and Regulation under Title 16 TAC Chapter 76 (relating to Water Well Drillers and Pump Installers) and all other locally applicable rules, as appropriate.
14. If sediment escapes the construction site, the sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50 percent. Litter, construction debris, and construction chemicals shall be prevented from becoming stormwater discharge pollutants.
15. Intentional discharges of sediment laden storm water are not allowed. If dewatering becomes necessary, the discharge will be filtered through appropriately selected best management

RECEIVED

APR 19 2010

COUNTY ENGINEER

practices. These may include vegetated filter strips, sediment traps, rock berms, silt fence rings, etc.

16. The following records shall be maintained and made available to the executive director upon request: the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
17. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, and construction activities will not resume within 21 days. When the initiation of stabilization measures by the 14th day is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable.


After Completion of Construction:

18. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the San Antonio Regional Office within 30 days of site completion.
19. The applicant shall be responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. The regulated entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred. A copy of the transfer of responsibility must be filed with the executive director through San Antonio Regional Office within 30 days of the transfer. A copy of the transfer form (TCEQ-10263) is enclosed.
20. Upon legal transfer of this property, the new owner(s) is required to comply with all terms of the approved Edwards Aquifer protection plan. If the new owner intends to commence any new regulated activity on the site, a new Edwards Aquifer protection plan that specifically addresses the new activity must be submitted to the executive director. Approval of the plan for the new regulated activity by the executive director is required prior to commencement of the new regulated activity.
21. An Edwards Aquifer protection plan approval or extension will expire and no extension will be granted if more than 50 percent of the total construction has not been completed within ten years from the initial approval of a plan. A new Edwards Aquifer protection plan must be submitted to the San Antonio Regional Office with the appropriate fees for review and approval by the executive director prior to commencing any additional regulated activities.
22. At project locations where construction is initiated and abandoned, or not completed, the site shall be returned to a condition such that the aquifer is protected from potential contamination.

Mr. Richard N. Maier
Continental Homes of Texas, L.P.
April 8, 2010
Page 6

If you have any questions or require additional information, please contact Alan G. Jones of the Edwards Aquifer Protection Program of the San Antonio Regional Office at (210) 403-4074.

Sincerely,



Mark R. Vickery, P.G., Executive Director
Texas Commission on Environmental Quality

MRV/agj/eg

Enclosure:

Deed Recordation Affidavit, Form TCEQ-0625

Change in Responsibility for Maintenance of Permanent BMPs, Form TCEQ-10263

cc: Mr. Michael G. Short, P.E., The Schultz Group, Inc.
Mr. James C. Klein, P.E., City Engineer, City of New Braunfels
Mr. Tom Hornseth, P.E., Comal County
Mr. Karl J. Dreher, Edwards Aquifer Authority
TCEQ Central Records, Building F, MC 212

RECEIVED

APR 19 2010

COUNTY ENGINEER

Deed Recordation Affidavit
Edwards Aquifer Protection Plan

THE STATE OF TEXAS §

County of _____ §

BEFORE ME, the undersigned authority, on this day personally appeared _____ who, being duly sworn by me, deposes and says:

- (1) That my name is _____ and that I own the real property described below.
- (2) That said real property is subject to an EDWARDS AQUIFER PROTECTION PLAN which was required under the 30 Texas Administrative Code (TAC) Chapter 213.
- (3) That the EDWARDS AQUIFER PROTECTION PLAN for said real property was approved by the Texas Commission on Environmental Quality (TCEQ) on _____.

A copy of the letter of approval from the TCEQ is attached to this affidavit as Exhibit A and is incorporated herein by reference.

- (4) The said real property is located in _____ County, Texas, and the legal description of the property is as follows:

LANDOWNER-AFFIANT

SWORN AND SUBSCRIBED TO before me, on this __ day of _____, _____.

NOTARY PUBLIC

THE STATE OF _____ §

County of _____ §

BEFORE ME, the undersigned authority, on this day personally appeared _____ known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this __ day of _____, _____.

NOTARY PUBLIC

Typed or Printed Name of Notary

MY COMMISSION EXPIRES: _____

**Change in Responsibility for Maintenance
on Permanent Best Management Practices and Measures**

The applicant is no longer responsible for maintaining the permanent best management practice (BMP) and other measures. The project information and the new entity responsible for maintenance is listed below.

Customer: _____

Regulated Entity Name: _____

Site Address: _____

City, Texas, Zip: _____

County: _____

Approval Letter Date: _____

BMPs for the project: _____

New Responsible Party: _____

Name of contact: _____

Mailing Address: _____

City, State: _____ Zip: _____

Telephone: _____ FAX: _____

Signature of New Responsible Party Date

I acknowledge and understand that I am assuming full responsibility for maintaining all permanent best management practices and measures approved by the TCEQ for the site, until another entity assumes such obligations in writing or ownership is transferred.

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282.

Bryan W. Shaw, Ph. D, *Chairman*
Buddy Garcia, *Commissioner*
Carlos Rubenstein., *Commissioner*
Mark R. Vickery, P.G., *Executive Director*



RECEIVED

FEB 18 2010

COUNTY ENGINEER

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

February 16, 2010

Mr. Thomas H. Hornseth, P.E.
Comal County Engineer
195 David Jonas Drive
New Braunfels TX 78132-3710

Re: Edwards Aquifer, Comal County
PROJECT NAME: Manor Creek Subdivision, located approximately 2 miles west of Loop 337 on the northeast side of State Highway 46, New Braunfels, Texas
PLAN TYPE: Application for Approval of a Water Pollution Abatement Plan (WPAP) 30 Texas Administration Code (TAC) Chapter 213; Edwards Aquifer Protection Program
EAPP File No.: 2439.03

Dear Mr. Hornseth:

The referenced application administratively complete on February 12, 2010, is being forwarded to you pursuant to the Edwards Aquifer Rules. The Texas Commission on Environmental Quality (TCEQ) is required by 30 TAC Chapter 213 to provide copies of all applications to affected incorporated cities and underground water conservation districts for their comments prior to TCEQ approval.

Please forward your comments to this office by March 11, 2010.

The Texas Commission on Environmental Quality appreciates your assistance in this matter and your compliance efforts to ensure protection of the State's environment. If you or members of your staff have any questions regarding these matters, please feel free to contact the San Antonio Region Office at (210) 490-3096.

Sincerely

A handwritten signature in blue ink, appearing to read "L. M. Bumgardner".

Lynn M. Bumgardner
Water Section Manager
San Antonio Regional Office

LMB/eg

2439.03

RECEIVED

FEB 18 2010

COUNTY ENGINEER

MANOR CREEK SUBDIVISION
WATER POLLUTION ABATEMENT PLAN
MODIFICATION

February 2010

Prepared for:

Continental Homes of Texas, LP
12554 Riata Circle, 2nd Floor
Austin, Texas 78727

Project No. 110309

Prepared By:

The Schultz Group Inc.
2461 Loop 337
New Braunfels, TX 78130
(830) 606-3913

Modification of a Previously Approved Plan Checklist

✓
General Information Form (*TCEQ-0587*)

ATTACHMENT A - Road Map

ATTACHMENT B - USGS / Edwards Recharge Zone Map

ATTACHMENT C - Project Description

✓
Geologic Assessment Form (*TCEQ-0585*)

ATTACHMENT A - Geologic Assessment Table, *TCEQ-0585-Table*

Comments to the Geologic Assessment Table

ATTACHMENT B - Soil Profile and Narrative of Soil Units

ATTACHMENT C - Stratigraphic Column

ATTACHMENT D - Narrative of Site Specific Geology

Site Geologic Map(s)

Table or list for the position of features' latitude/longitude (if mapped using GPS)

✓
Modification of a Previously Approved Plan (*TCEQ-0590*)

ATTACHMENT A - Original Approval Letter and Approved Modification Letters

ATTACHMENT B - Narrative of Proposed Modification

ATTACHMENT C - Current Site Plan of the Approved Project

✓
Application Form (appropriate for the modification)

Aboveground Storage Tank Facility Plan (*TCEQ-0575*)

Organized Sewage Collection System Plan (*TCEQ-0582*)

Underground Storage Tank Facility Plan (*TCEQ-0583*)

Water Pollution Abatement Plan Application Form (*TCEQ-0584*)

Lift Station / Force Main System Application (*TCEQ-0624*)

✓
Temporary Stormwater Section (*TCEQ-0602*), if necessary

ATTACHMENT A - Spill Response Actions

ATTACHMENT B - Potential Sources of Contamination

ATTACHMENT C - Sequence of Major Activities

ATTACHMENT D - Temporary Best Management Practices and Measures

ATTACHMENT E - Request to Temporarily Seal a Feature, if sealing a feature

ATTACHMENT F - Structural Practices

ATTACHMENT G - Drainage Area Map

ATTACHMENT H - Temporary Sediment Pond(s) Plans and Calculations

ATTACHMENT I - Inspection and Maintenance for BMPs

ATTACHMENT J - Schedule of Interim and Permanent Soil Stabilization Practices

✓
Permanent Stormwater Section (*TCEQ-0600*), if necessary

ATTACHMENT A - 20% or Less Impervious Cover Waiver, if project is multi-family residential, a school, or a small business and 20% or less impervious cover is proposed for the site

ATTACHMENT B - BMPs for Upgradient Stormwater

ATTACHMENT C - BMPs for On-site Stormwater

ATTACHMENT D - BMPs for Surface Streams

ATTACHMENT E - Request to Seal Features, if sealing a feature

ATTACHMENT F - Construction Plans

ATTACHMENT G - Inspection, Maintenance, Repair and Retrofit Plan

ATTACHMENT H - Pilot-Scale Field Testing Plan, if BMPs not based on *Complying with the Edwards Aquifer Rules: Technical Guidance for BMPs*

ATTACHMENT I - Measures for Minimizing Surface Stream Contamination

Modification of a Previously Approved Plan Checklist (continued)

- ☒ Agent Authorization Form (*TCEQ-0599*), if application submitted by agent
- ☒ Application Fee Form (*TCEQ-0574*)
- ☒ Check Payable to the "Texas Commission on Environmental Quality"
- ☒ Core Data Form (*TCEQ-10400*)

General Information Form
For Regulated Activities on the
Edwards Aquifer Recharge and Transition Zones
and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B)
Effective June 1, 1999

REGULATED ENTITY NAME: Manor Creek Subdivision
COUNTY: Comal STREAM BASIN: Bleiders Creek

EDWARDS AQUIFER: ☒ RECHARGE ZONE
☐ TRANSITION ZONE

PLAN TYPE: ☐ WPAP ☐ AST ☐ EXCEPTION
☐ SCS ☐ UST ☒ MODIFICATION

CUSTOMER INFORMATION

1. Customer (Applicant):

Contact Person: Richard N. Maier, Assistant Secretary
Entity: Continental Homes of Texas, L.P., a Texas Limited Partnership By: CHTEX of Texas, Inc. a Delaware Corporation, Its General Partner
Mailing Address: 12554 Riata Vista Circle, 2nd Floor
City, State: Austin, TX. Zip: 78727
Telephone: (512) 345-4663 FAX: (512) 533-1429

Agent/Representative (If any):

Contact Person: Michael G. Short, P.E.
Entity: The Schultz Group, Inc.
Mailing Address: 2461 Loop 337
City, State: New Braunfels, TX. Zip: 78130
Telephone: (830) 606-3913 FAX: (830) 625-2204

2. ☒ This project is inside the city limits of New Braunfels, TX.
☐ This project is outside the city limits but inside the ETJ (extra-territorial jurisdiction) of _____
☐ This project is not located within any city's limits or ETJ.

3. The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

The proposed Manor Creek development is located approximately 2 miles West of Loop 337 on the Northeast side of State Highway 46.

4. ☒ **ATTACHMENT A - ROAD MAP.** A road map showing directions to and the location of the project site is attached at the end of this form.
5. ☒ **ATTACHMENT B - USGS / EDWARDS RECHARGE ZONE MAP.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached behind this sheet. The map(s) should clearly show:

- ☒ Project site.
- ☒ USGS Quadrangle Name(s).
- ☒ Boundaries of the Recharge Zone (and Transition Zone, if applicable).
- ☒ Drainage path from the project to the boundary of the Recharge Zone.

6. ☒ Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment. **The TCEQ must be able to inspect the project site or the application will be returned.**
7. ☒ **ATTACHMENT C - PROJECT DESCRIPTION.** Attached at the end of this form is a detailed narrative description of the proposed project.
8. Existing project site conditions are noted below:
- ☐ Existing commercial site
 - ☐ Existing industrial site
 - ☒ Existing residential site
 - ☐ Existing paved and/or unpaved roads
 - ☐ Undeveloped (Cleared)
 - ☒ Undeveloped (Undisturbed/Uncleared)
 - ☐ Other: _____

PROHIBITED ACTIVITIES

9. ☒ I am aware that the following activities are prohibited on the **Recharge Zone** and are not proposed for this project:
- (1) waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
 - (2) new feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
 - (3) land disposal of Class I wastes, as defined in 30 TAC §335.1;
 - (4) the use of sewage holding tanks as parts of organized collection systems; and
 - (5) new municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
10. ☒ I am aware that the following activities are prohibited on the **Transition Zone** and are not proposed for this project:
- (1) waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);
 - (2) land disposal of Class I wastes, as defined in 30 TAC §335.1; and
 - (3) new municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

ADMINISTRATIVE INFORMATION

11. The fee for the plan(s) is based on:
- ☒ For a Water Pollution Abatement Plan and Modifications, the total acreage of the site where regulated activities will occur.

- ☐ For an Organized Sewage Collection System Plans and Modifications, the total linear footage of all collection system lines.
- ☐ For a UST Facility Plan or an AST Facility Plan, the total number of tanks or piping systems.
- ☐ A Contributing Zone Plan.
- ☐ A request for an exception to any substantive portion of the regulations related to the protection of water quality.
- ☐ A request for an extension to a previously approved plan.

12. Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

- ☐ TCEQ cashier
- ☐ Austin Regional Office (for projects in Hays, Travis, and Williamson Counties)
- ☒ San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

13. ☒ Submit one (1) original and three ~~(3)~~ (4) copies of the completed application to the appropriate regional office for distribution by the TCEQ to the local municipality or county, groundwater conservation districts, and the TCEQ's Central Office.

14. ☒ No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the executive director.
☐ No person shall commence any regulated activity until the Contributing Zone Plan for the activity has been filed with the executive director.

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **GENERAL INFORMATION FORM** is hereby submitted for TCEQ review. The application was prepared by:

Michael G. Short, P.E.

 Print Name of Customer/Agent




 Signature of Customer/Agent

2/11/10

 Date

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282.



LOCATION MAP

THE **Schultz Group**, INC.

TEXAS REGISTERED ENGINEERING FIRM F-532
CONSULTING ENGINEERS & LAND SURVEYORS
2461 LOOP 337 NEW BRAUNFELS, TEXAS 78130 P: 830.606.3913
F: 830.625.2204

TEXAS LICENSED SURVEYING FIRM 100059-00

DRAWN BY: M.H.	DATE: NOVEMBER 2009
CHECKED BY: S.S.	JOB NO.: 110109

Edwards Aquifer Recharge Zone Map
30 Texas Administrative Code Chapter 213
Edwards Aquifer Authority Rule Chapter 713

NEW BRAUNFELS WEST QUADRANGLE
TEXAS
7.5 MINUTE SERIES (TOPOGRAPHIC)



Produced by the United States Geological Survey
Revised in cooperation with the Texas Water Development Board
Control by USGS, NOS/NOAA, and USCE
Compiled by the Army Map Service by photogrammetric methods
from aerial photographs taken 1956. Field checked 1958
Revised from aerial photographs taken 1966. Field checked 1987
Map edited 1988
Projection and 10,000-foot grid ticks: Texas coordinate
system, south central zone (Lambert conformal conic)
1000-meter Universal Transverse Mercator grid, zone 14
1927 North American Datum
To place on the predicted North American Datum 1983
move the projection lines 20 meters south and
28 meters east as shown by dashed corner ticks
Fine red dashed lines indicate selected fence and field lines
generally visible on aerial photographs. This information is unchecked

UTM GRID AND 1983 MAGNETIC NORTH
DECLINATION AT CENTER OF MAP
DIAGRAM IS APPROXIMATE

SCALE 1:24 000
1 000 000 2000 3000 4000 5000 6000 7000 8000 9000 10 000
FEET
1 000 000 2000 3000 4000 5000 6000 7000 8000 9000 10 000
METERS
CONTOUR INTERVAL 10 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

TEXAS
QUADRANGLE LOCATION
2998-413

ROAD CLASSIFICATION
Primary highway, hard surface
Secondary highway, hard surface
Light-duty road, hard or improved surface
Unimproved road
Interstate Route U. S. Route State Route
NEW BRAUNFELS WEST, TEX.
2998-F2-TF-024
1988
DMA 6343 II NW-SERIES V822

ATTACHMENT B
USGS/EDWARDS RECHARGE
ZONE MAP

Last revision date of the Recharge Zone Boundary for this Quadrangle Map: March 1974

Attachment C – Project Description

The project was previously titled as Tschirhart Ranch Subdivision, it has since become known as Manor Creek. The original proposed project consisted of 252.038 acres of land that was to be developed into a 343 lot residential subdivision. Each individual residential lot was to contain approximately 3,860 square feet of impervious cover which included a building structure and a concrete driveway. There was to be approximately 6,800 L.F. of street in a 60' R.O.W. The overall developed project was to consist of less than 20% impervious cover, so that structural BMP's would not be required. The permanent BMP's around the sensitive features consist of native vegetation for a minimum of 50 feet around each feature.

Unit one has been constructed and the impervious cover has exceeded the 3,860 square feet of impervious cover allowed for each lot. As a result the owner has purchased an additional 15.001 acres to keep the impervious cover for the site under 20%. The impervious cover for lots within Units 2-6 have been reconfigured to contain approximately 3,662 square feet of impervious cover for interior lots and 3,865 square feet for optional corner lots which includes all proposed typical building structures and a concrete driveway. With the addition of the 15.001 acres and a reduction of area given an existing TxDOT dedication of 0.123 acres, this development will have less than 20% impervious cover; therefore, no structural BMP's are required. The 50 foot vegetative buffer around sensitive features will be maintained.

**Geologic Site Assessment (WPAP)
for Regulated Activities / Development
on the Edwards Aquifer Recharge / Transition Zone**

**The Tschirhart Ranch Subdivision
(Manor Creek)
267.038 Acres
New Braunfels, Texas**

**FROST GEOSCIENCES CONTROL # FGS-E09176
DECEMBER 31, 2009**

Prepared exclusively for

**The Schultz Group
2461 Loop 337
New Braunfels, Texas 78130**

Frost GeoSciences
Geotechnical • Construction Materials
Forensics • Environmental

13402 Western Oak • Helotes, Texas 78023 • Phone: (210) 372-1315 • Fax: (210) 372-1318

Frost GeoSciences

**Geotechnical • Construction Materials
Forensics • Environmental**

13402 Western Oak
Helotes, TX 78023
Phone (210) 372-1315
Fax (210) 372-1318
www.frostgeosciences.com
TBPE Firm Registration # F-9227
TBPG Firm Registration # 50040

December 31, 2009

The Schultz Group
2461 Loop 337
New Braunfels, Texas 78130

Attn: Mr. Shawn Schorn


Re: Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivis9on
267.038 Acres
New Braunfels, Texas

Frost GeoSciences, Inc. Control # FGS-E09176

Gentlemen:

Attached is a copy of the Geologic Assessment Report completed for the above referenced project site as it relates to 30 TAC §213.5(b)(3), effective June 1, 1999. Our investigation was conducted, and this report was prepared in general accordance with the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04). The results of our investigation along with any required recommendations for Best Management Practices (BMP's) are provided in the following report.

If you have any questions regarding this report, or if Frost GeoSciences, Inc. may be of additional assistance to you on this project, please feel free to call our office. It has been a pleasure to work with you and we wish to thank you for the opportunity to be of service to you on this project. We look forward to being of continued service.



Sincerely,
Frost GeoSciences, Inc.

Steve Frost, C.P.G.
President, Senior Geologist

Distribution: (6) The Schultz Group

Table of Contents

GEOLOGIC ASSESSMENT FORM	1
STRATIGRAPHIC COLUMN	3
GEOLOGIC ASSESSMENT TABLE	4
LOCATION	13
METHODOLOGY	13
RESEARCH & OBSERVATIONS	14
7.5 Minute Quadrangle Map Review	14
Recharge/Transition Zone	14
100-Year Floodplain	15
Soils	15
Narrative Description of the Site Geology	17
BEST MANAGEMENT PRACTICES	27
DISCLAIMER	27
REFERENCES	28
APPENDIX	
A: Plate 1a: Site Plan	
Plate 2: Street Map	
Plate 3: U.S.G.S. Topographic Map	
Plate 4: Official Edwards Aquifer Recharge Zone Map	
Plate 5: FEMA Flood Map	
Plate 6: U.S. Geological Survey, Water Resources Investigation # 94-4117	
Plate 8: 2009 Aerial Photograph, 1"=1000'	
Plate 9: 2009 Aerial Photograph with PRF's, 1"=600'	
Plate 10: 1973 Photograph, 1"=1000'	
B: Site Photographs	
C: Site Geologic Map	

**Geologic Assessment
For Regulated Activities
on The Edwards Aquifer Recharge/transition Zones
and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999**

REGULATED ENTITY NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

TYPE OF PROJECT: ☒ WPAP ☐ AST ☐ SCS ☐ UST

LOCATION OF PROJECT: ☒ Recharge Zone ☐ Transition Zone ☐ Contributing Zone within the Transition Zone

PROJECT INFORMATION

1. ☒ Geologic or manmade features are described and evaluated using the attached **GEOLOGIC ASSESSMENT TABLE**.
2. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (*Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986*). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Soil Units, Infiltration Characteristics & Thickness		
Soil Name	Group*	Thickness (feet)
Rumple-Comfort Assoc.	C/D	0.5 to 1
Comfort-Rock Outcrop Complex	D	0.5 to 1

*** Soil Group Definitions (Abbreviated)**

- A. Soils having a high infiltration rate when thoroughly wetted.
- B. Soils having a moderate infiltration rate when thoroughly wetted.
- C. Soils having a slow infiltration rate when thoroughly wetted.
- D. Soils having a very slow infiltration rate when thoroughly wetted.

3. ☒ A **STRATIGRAPHIC COLUMN** is attached at the end of this form that shows formations, members, and thicknesses. The outcropping unit should be at the top of the stratigraphic column.
4. ☒ A **NARRATIVE DESCRIPTION OF SITE SPECIFIC GEOLOGY** is attached at the end of this form. The description must include a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure, and karst characteristics of the site.
5. ☒ Appropriate **SITE GEOLOGIC MAP(S)** are attached:

The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1" = 400'

Applicant's Site Plan Scale	1" = <u>200</u> '
Site Geologic Map Scale	1" = <u>200</u> '
Site Soils Map Scale (if more than 1 soil type)	1" = <u>1000</u> '

6. Method of collecting positional data:

- ☒ Global Positioning System (GPS) technology.
☒ Other method(s). 2003 & 2009 Aerial Photo
7. ☒ The project site is shown and labeled on the Site Geologic Map.
8. ☒ Surface geologic units are shown and labeled on the Site Geologic Map.
9. ☒ Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
☐ Geologic or manmade features were not discovered on the project site during the field investigation.
10. ☒ The Recharge Zone boundary is shown and labeled, if appropriate.
11. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.):
☐ There are ___ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)
☐ The wells are not in use and have been properly abandoned.
☐ The wells are not in use and will be properly abandoned.
☐ The wells are in use and comply with 16 TAC Chapter 76.
☒ There are no wells or test holes of any kind known to exist on the project site.

ADMINISTRATIVE INFORMATION

12. ☒ One (1) original and three (3) copies of the completed assessment has been provided.

Date(s) Geologic Assessment was performed: April 5-14, 21-28, 2005 & December 19, 2009
Date(s)

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Steve Frost, C.P.G.
Print Name of Geologist


(210) 372-1315
Telephone

(210) 372-1318
Fax

Steve Frost
Signature of Geologist

December 31, 2009
Date

Representing: Frost GeoSciences, Inc.
(Name of Company)



If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210-480-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/339-3263.

Stratigraphic Column

[Hydrogeologic subdivisions modified from MacLay and Small (1976); groups, formations, and members modified from Rose (1972); lithology modified from Dunham (1962); and porosity type modified from Choquette and Pray (1970). CU, confining unit; AQ, aquifer]

Hydrogeologic subdivision		Group, formation, or member	Hydro-logic function	Thickness (feet)	Lithology	Field identification	Cave development	Porosity/ permeability type		
Upper Cretaceous	Upper confining units	Eagle Ford Group	CU	30 – 50	Brown, flaggy shale and argillaceous limestone	Thin flagstones; petroliferous	None	Primary porosity lost/ low permeability		
		Buda Limestone	CU	40 – 50	Buff, light gray, dense mudstone	Porcelaneous limestone with calcite-filled veins	Minor surface karst	Low porosity/low permeability		
		Del Rio Clay	CU	40 – 50	Blue-green to yellow-brown clay	Fossiliferous; <i>Hymanogya artemia</i>	None	None/primary upper confining unit		
Lower Cretaceous	I	Edwards Group	Pecos Formation	Georgetown Formation	Karst AQ; not karst CU	2 – 20	Reddish-brown, gray to light tan marly limestone	Marker fossil; <i>Macroneilla macdonaldi</i>	None	Low porosity/low permeability
	II			Cyclic and marine members, undivided	AQ	80 – 90	Mudstone to packstone; nodular grainstone; chert	Thin graded cycles; massive beds to relatively thin beds; crossbeds	Many subsurface; might be associated with earlier karst development	Laterally extensive; both fabric and not fabric/water-yielding
	III			Leached and collapsed members, undivided	AQ	70 – 90	Crystalline limestone; mudstone to grainstone; chert; collapsed breccia	Disturbed iron-stained beds separated by massive limestone beds; stromatolitic limestone	Extensive lateral development; large rooms	Majority not fabric/one of the most permeable
	IV			Regional dense member	CU	20 – 24	Dense, argillaceous mudstone	Waxy iron-oxide stains	Very few; only vertical fracture enlargement	Not fabric/low permeability; vertical barrier
	V			Grainstone member	AQ	50 – 60	Mitoid grainstone; mudstone to wackestone; chert	White crossbedded grainstone	Few	Not fabric/ recrystallization reduces permeability
	VI			Kirschberg evaporite member	AQ	50 – 60	Highly altered crystalline limestone; chalky mudstone; chert	Boxwork voids, with neospar and travertine frame	Probably extensive cave development	Majority fabric/one of the most permeable
	VII			Dolomitic member	AQ	110 – 130	Mudstone to grainstone; crystalline limestone; chert	Massively bedded light gray, <i>Toucasia</i> abundant	Caves related to structure or bedding planes	Mostly not fabric; some bedding plane-fabric/water-yielding
	VIII			Basal nodular member	Karst AQ; not karst CU	50 – 60	Shaly, nodular limestone; mudstone and mitoid grainstone	Massive, nodular and mottled, <i>Eosagitta</i> rare	Large lateral caves at surface; a few caves near Cibola Creek	Fabric; stratigraphically controlled/large conduit flow at surface; no permeability in subsurface
		Lower confining unit	Upper member of the Glen Rose Limestone	CU; evaporite beds AQ	350 – 500	Yellowish tan, thinly bedded limestone and marl	Stair-step topography; alternating limestone and marl	Some surface cave development	Some water production at evaporite beds/relatively impermeable	

GEOLOGIC ASSESSMENT TABLE

PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

FGS-E09176

LOCATION			FEATURE CHARACTERISTICS											EVALUATION		PHYSICAL SETTING				
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)		TOPOGRAPHY
						X	Y	Z		10						< 40	> 40	< 1.6	≥ 1.6	
S-1	N29° 43' 42.6"	W98° 11' 17"	SC	20	Kep	1	1	1.5	-	-	-	-	O,F	7	27	27		Yes		Hillside
S-2	N29° 43' 42.2"	W98° 11' 15.8"	O ^{vg}	5	Kep	15	50		-	-	1	0.5	O,F,C	15	20	20		Yes		Hillside
S-3	N29° 43' 41.1"	W98° 11' 17"	SC	20	Kep	1	1	1.5	-	-	-	-	O,F	10	30	30		Yes		Hillside
S-4	N29° 43' 37.9"	W98° 11' 12.4"	SC	20	Kep	1	1	2	-	-	-	-	O,F	10	30	30		Yes		Hillside
S-5	N29° 43' 39.4"	W98° 11' 11.6"	SC	20	Kep	1	1	1.5					O,F	10	30	30		Yes		Hillside
S-6	N29° 43' 34.5"	W98° 11' 11"	O ^{vg}	5	Kep	25	75		45	-	4/1	.03/.03	O,F,C	19	24	24		Yes		Drainage
S-7	N29° 43' 33.5"	W98° 11' 7.97"	MB	30	Kep	3	3	2	-	-	-	-	X	7	37	37		Yes		Hillside
S-8	N29° 43' 33.4"	W98° 11' 7.37"	O ^{vg}	5	Kep	20	200				3-10	0.08-0.3	O,F,C	19	24	24		Yes		Cliff
S-9	N29° 43' 44.3"	W98° 11' 5.2"	O ^{vg}	5	Kep	20	40		33	10	1	0.25	O,F,C	19	34	34		Yes		Hillside
S-10	N29° 43' 41.9"	W98° 11' 4.85"	SC	20	Kep	1.5	1.5	2	-	-	-	-	O,F,N	12	32	32		Yes		Hillside
S-11	N29° 43' 36.6"	W98° 11' 4.18"	MB	30	Kep	3	3	2	-	-	-	-	X	7	37	37		Yes		Hillside
S-12	N29° 43' 38.3"	W98° 11' 3.72"	SC	20	Kep	1	1	1.5	-	-	-	-	O,F	12	32	32		Yes		Hillside

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 1 of 9

Frost GeoSciences

Geotechnical • Construction Materials • Forensics • Environmental

TCEQ 2-96 Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 4

GEOLOGIC ASSESSMENT TABLE

PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

FGS-E09176

LOCATION			FEATURE CHARACTERISTICS												EVALUATION			PHYSICAL SETTING		
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)		TOPOGRAPHY
						X	Y	Z		10						< 40	> 40	< 1.6	> 1.6	
S-13	N29° 43' 33.4"	W98° 11' 4.95"	SC	20	Kep	1	1	1.5	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-14	N29° 43' 32.6"	W98° 11' 4.96"	O ^{VRH}	5	Kep	15	40		25	10	3.5	0.12	O,F,C	15	30	30		Yes		Drainage
S-15	N29° 43' 30.5"	W98° 11' 3.15"	Z ^{VRH}	30	Kep	20	75		-	-	1.5	0.25	O,F,C	20	50		50		Yes	Drainage
S-16	N29° 43' 33.5"	W98° 11' 0.93"	SC	20	Kep	1	2	2	-	-	-	-	O,F	10	30	30		Yes		Hillside
S-17	N29° 43' 37.4"	W98° 10' 54.7"	SC	20	Kep	2	2	2					O,F	12	32	32		Yes		Hillside
S-18	N29° 43' 37.8"	W98° 10' 54.4"	SC	20	Kep	2	2	1.5	-	-	-	-	O,F,C	12	32	32			Yes	Hillside
S-19	N29° 43' 34.2"	W98° 11' 0.26"	SC	20	Kep	0.5	0.5	1.5	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-20	N29° 43' 39.1"	W98° 10' 53.6"	SC	20	Kep	2	2	2	-	-	-	-	O,F,C	12	32	32		Yes		Hillside
S-21	N29° 43' 39.8"	W98° 10' 59.5"	SF	20	Kep	15	30		45	10	1.2	0.25	O,F,C	20	50		50		Yes	Drainage
S-22	N29° 43' 40.8"	W98° 10' 52.9"	MB	30	Kep	3	3	?	-	-	-	-	X	7	37	37		Yes		Hillside
S-23	N29° 43' 42"	W98° 10' 44.4"	SC	20	Kep	0.5	4	1.5	-	-	-	-	O,F	15	35	35		Yes		Hillside
S-24	N29° 43' 38.3"	W98° 11' 3.72"	SC	20	Kep	0.5	4	1.5	-	-	-	-	O,F	15	35	35		Yes		Hillside

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 2 of 9

Frost GeoSciences

Geotechnical • Construction Materials • Forensics • Environmental

TCEQ 8586-Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 5

GEOLOGIC ASSESSMENT TABLE
PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

FGS-E09176

LOCATION			FEATURE CHARACTERISTICS												EVALUATION		PHYSICAL SETTING			
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)		TOPOGRAPHY
						X	Y	Z		10						< 40	> 40	<1.6	>1.6	
S-25	N29° 43' 40.7"	W98° 10' 58.6"	Z ^{VI} II	30	Kep	50	100		-	-	1-4	0.25	O,F,C	20	50		50	Yes		Drainage
S-26	N29° 43' 40.6"	W98° 11' 15.1"	SC	20	Kep	1	1	2	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-27	N29° 43' 41.1"	W98° 11' 0.076"	O ^{VI} I	5	Kep	20	60		-	-	2-6	0.2-0.5	O,F,C	12	17	17		Yes		Hillside
S-28	N29° 43' 41.1"	W98° 11' 0.83"	SC	20	Kep	1.5	1	2	-	-	-	-	O,F	10	30	30		Yes		Hillside
S-29	N29° 43' 41.3"	W98° 11' 1.09"	SC	20	Kep	1.5	4	1.5					O,F	15	35	35		Yes		Hillside
S-30	N29° 43' 44.3"	W98° 11' 1.81"	SC	20	Kep	1	1	2	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-31	N29° 43' 41.4"	W98° 10' 59.2"	MB	30	Kep	3	3	2	-	-	-	-	X	7	37	37		Yes		Hillside
S-32	N29° 43' 42.1"	W98° 10' 58.6"	SC	20	Kep	1.5	3	1.5	-	-	-	-	O,F	19	39	39		Yes		Hillside
S-33	N29° 43' 56.7"	W98° 10' 56.8"	SC	20	Kep	2	2	1.5	-	-	-	-	O,F,C	12	32	32		Yes		Hillside
S-34	N29° 43' 57.6"	W98° 10' 55.6"	SC	20	Kep	1	1	1	-	-	-	-	O,F	10	30	30		Yes		Hillside
S-35	N29° 43' 41.2"	W98° 10' 53.2"	SF ^I	20	Kep	10	15		78	10	1	0.20	O,F	20	50		50	Yes		Hillside
S-36	N29° 43' 50.6"	W98° 10' 53.9"	SC	20	Kep	1	0.5	1	-	-	-	-	O,F	10	30	30		Yes		Hillside

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 3 of 9

Frost GeoSciences
Geotechnical • Construction Materials • Forensics • Environmental

TCEQ-0585-Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 6

GEOLOGIC ASSESSMENT TABLE

PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

FGS-E09176

LOCATION			FEATURE CHARACTERISTICS											EVALUATION			PHYSICAL SETTING			
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT ³)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)		TOPOGRAPHY
						X	Y	Z		10						< 40	≥ 40	<1.6	≥1.6	
S-37	N29° 43' 59.1"	W98° 10' 53.4"	CVR	5	Kep	15	20		-	-	2-4	0.15	O,F	15	20	20		Yes		Drainage
S-38	N29° 43' 59.1"	W98° 10' 51.1"	Z ^{VI} PH	30	Kep	20	75		-	-	-	-	O,F	20	50		50		Yes	Drainage
S-39	N29° 43' 52"	W98° 10' 52.3"	SC	20	Kep	1	1	1.5	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-40	N29° 43' 41.1"	W98° 11' 0.83"	CD	5	Kep	4	5	1	-	-	-	-	O,F	9	14	14		Yes		Hillside
S-41	N29° 43' 54.8"	W98° 10' 50.8"	SC	20	Kep	1.5	3	1.5					O,F	15	35	35		Yes		Hillside
S-42	N29° 43' 50.4"	W98° 10' 50.1"	SC	20	Kep	1	1	2	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-43	N29° 43' 42.7"	W98° 10' 47.8"	MB	30	Kep	3	3	2	-	-	-	-	X	7	37	37		Yes		Hillside
S-44	N29° 43' 51.3"	W98° 10' 47.4"	SC	20	Kep	2	2	1.5	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-45	N29° 43' 53.4"	W98° 10' 47.7"	SC	20	Kep	2	2	1.5	-	-	-	-	O,F,C	12	32	32		Yes		Hillside
S-46	N29° 43' 50.7"	W98° 10' 48.8"	SF	20	Kep	2	10	2	-	-	-	-	O,F	19	39	39		Yes		Hillside
S-47	N29° 43' 50.7"	W98° 10' 49.1"	SC	20	Kep	1	0.5	1	-	-	-	-	O,F	10	30	30		Yes		Hillside
S-48	N29° 43' 50.6"	W98° 10' 49.2"	SC	20	Kep	2	1.5	2	-	-	-	-	O,F	10	30	30		Yes		Hillside

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY	
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed	

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 4 of 9

Frost GeoSciences
Geotechnical • Construction Materials • Forensics • Environmental

TCEQ-0585-Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 7

GEOLOGIC ASSESSMENT TABLE

PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

FGS-E09176

LOCATION			FEATURE CHARACTERISTICS												EVALUATION			PHYSICAL SETTING		
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)		TOPOGRAPHY
						X	Y	Z		10						< 40	≥ 40	< 1.6	≥ 1.6	
S-49	N29° 43' 49.2"	W98° 10' 44.1"	MB	30	Kep	3	3	?	-	-	-	-	X	7	37	37		Yes		Hillside
S-50	N29° 43' 45.7"	W98° 10' 43.5"	MB	30	Kep	3	3	?	-	-	-	-	X	7	37	37		Yes		Hillside
S-51	N29° 43' 58"	W98° 10' 46.6"	O ^{VHFR}	5	Kep	25	75		60	10	1-3	0.1-0.5	O,F	12	27	27		Yes		Hillside
S-52	N29° 43' 54"	W98° 10' 44.3"	O ^{VHFR}	5	Kep	50	75		40-55	10	1-4	0.1-0.5	O,F	19	34	34		Yes		Drainage
S-53	N29° 43' 52.9"	W98° 10' 44.9"	O ^{VH}	5	Kep	20	40		-	-	3-6	0.1-0.25	O,F,C	12	17	17		Yes		Hillside
S-54	N29° 43' 45.1"	W98° 10' 46.8"	SC	20	Kep	2	1	2	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-55	N29° 43' 41.8"	W98° 10' 44.5"	O ^{VH}	5	Kep	10	10		-	-	1-4	0.1-0.25	O,F,C	10	15	15		Yes		Hillside
S-56	N29° 43' 43.1"	W98° 10' 43.9"	SC	20	Kep	0.5	0.5	1	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-57	N29° 43' 43.1"	W98° 10' 44.2"	O ^{VHFR}	5	Kep	10	50		50-60	-	1-3	0.1-0.25	O,F,C	12	17	17		Yes		Hillside
S-58	N29° 43' 42.8"	W98° 10' 43.2"	O ^{VH}	5	Kep	10	50	1	-	-	-	-	O,F	12	17	17		Yes		Hillside
S-59	N29° 43' 41.2"	W98° 10' 53.2"	SC	20	Kep	1	0.5		-	-	-	-	O,F	12	32	32		Yes		Hillside
S-60	N29° 43' 50.6"	W98° 10' 53.9"	SC	20	Kep	1	0.5	1	-	-	-	-	O,F	10	30	30		Yes		Hillside

* **DATUM** 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY	
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed	

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 5 of 9

Frost GeoSciences

Geotechnical • Construction Materials • Forensics • Environmental

TCEQ-0585-Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 8

GEOLOGIC ASSESSMENT TABLE						PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres										FGS-E09176				
LOCATION			FEATURE CHARACTERISTICS											EVALUATION		PHYSICAL SETTING				
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)	TOPOGRAPHY	
						X	Y	Z		10						< 40	≥ 40	< 1.6	≥ 1.6	
S-61	N29° 43' 44.6"	W98° 10' 43.9"	Z ^{MB}	30	Kep	30	100		-	-	1-4	0.1-0.25	O,F,C	20	50		50		Yes	Drainage
S-62	N29° 43' 47"	W98° 10' 47.4"	SC	20	Kep	1	1	2	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-63	N29° 43' 46.5"	W98° 10' 42.3"	C	30	Kep	4	10	10	-	-	-	-	N	20	50		50		Yes	Cliff
S-64	N29° 43' 46.5"	W98° 10' 42.3"	O ^{MB}	5	Kep	15	75	10	-	-	-	-	O,F,C	15	20	20			Yes	Cliff
S-65	N29° 43' 47.5"	W98° 10' 42.8"	O ^{FB}	5	Kep	15	100						O,F	15	20	20			Yes	Drainage
S-66	N29° 43' 49.1"	W98° 10' 40.9"	SC	20	Kep	1	1	1	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-67	N29° 43' 49.1"	W98° 10' 41.7"	SC	20	Kep	1	0.75	1.5	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-68	N29° 43' 51.6"	W98° 10' 42.4"	SC	20	Kep	1	1	1	-	-	-	-	O,F	12	32	32		Yes		Hillside
S-69	N29° 43' 55"	W98° 10' 44"	O ^{MB}	5	Kep	15	20		18	-	1-4	0.1-0.25	O,F,C	12	17	17		Yes		Hillside
S-70	N29° 43' 55"	W98° 10' 44.2"	SC	20	Kep	3	1	1	-	-	-	-	O,F	20	40		40		Yes	Drainage
S-71	N29° 43' 55.1"	W98° 10' 43.6"	SC	20	Kep	4	4	1.5	-	-	-	-	O,F,C	20			40		Yes	Drainage
S-72	N29° 43' 56.3"	W98° 10' 38.6"	SC	20	Kep	1	1	1	-	-	-	-	O,F	12	32	32		Yes		Hillside

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY	
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed	

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 6 of 9

Frost GeoSciences

Geotechnical • Construction Materials • Forensics • Environmental

TCEQ-0585-Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 9

GEOLOGIC ASSESSMENT TABLE

PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

FGS-E09176

LOCATION			FEATURE CHARACTERISTICS											EVALUATION		PHYSICAL SETTING				
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10	11		12	
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)	TOPOGRAPHY	
						X	Y	Z		10						< 40	≥ 40	<1.6	≥1.6	
S-73	N29° 43' 55.8"	W98° 10' 42.4"	O ^{VB}	5	Kep	20	50		-	-	14	0.1-0.25	O,F,C	20	25	25			Yes	Drainage
S-74	N29° 43' 57.3"	W98° 10' 39.6"	O ^{VB}	5	Kep	20	50		-	-	14	0.1-0.25	O,F,C	20	25	25			Yes	Drainage
S-75	N29° 43' 58.8"	W98° 10' 41.1"	SC	20	Kep	1	1	1	-	-	-	-	O,F	12	32	32			Yes	Hillside
S-76	N29° 43' 8.48"	W98° 10' 40.5"	SC	20	Kep	2	1	1	-	-	-	-	O,F	12	32	32			Yes	Hillside
S-77	N29° 43' 59.8"	W98° 10' 37.9"	SC	20	Kep	1	1	1	-	-	-	-	O,F	12	32	32			Yes	Hillside
S-78	N29° 43' 57.5"	W98° 10' 34.5"	SC	20	Kep	5	5	1	-	-	-	-	O,F	19	39	39			Yes	Hillside
S-79	N29° 43' 58.5"	W98° 10' 31.3"	SC	20	Kep	1	1	1	-	-	-	-	O,F	12	32	32			Yes	Hillside
S-80	N29° 43' 58.4"	W98° 10' 30.5"	SC	20	Kep	1	1	1	-	-	-	-	O,F	12	32	32			Yes	Hillside
S-81	N29° 43' 59.3"	W98° 10' 31.3"	SH	20	Kep	10	10	1	-	-	-	-	O,F,V	20	40		40		Yes	Hillside
S-82	N29° 43' 57.7"	W98° 10' 30.1"	MB	30	Kep	3	3	?	-	-	-	-	X	7	37	37			Yes	Hillside
S-83	N29° 43' 59.2"	W98° 10' 27.3"	SC	20	Kep	1	1	3	-	-	-	-	O,F	12	32	32			Yes	Hillside
S-84	N29° 43' 58.9"	W98° 10' 26.4"	MB	30	Kep	3	3	?	-	-	-	-	X	7	37	37			Yes	Hillside

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY	
Cliff, Hillside, Floodplain, Streambed	

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 7 of 9

Frost GeoSciences

Geotechnical • Construction Materials • Forensics • Environmental

TCEQ-0585-Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 10

GEOLOGIC ASSESSMENT TABLE

PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres

FGS-E09176

LOCATION			FEATURE CHARACTERISTICS												EVALUATION		PHYSICAL SETTING			
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)		TOPOGRAPHY
						X	Y	Z		10						< 40	≥ 40	< 1.6	≥ 1.6	
S-85	N29° 43' 3.42"	W98° 10' 26.3"	Z ^{VISC}	30	Kep	20	90		-	-	1-4	0.1-0.5	O.F.C	25	55		55		Yes	Floodplain
S-86	N29° 44' 0.10"	W98° 10' 25"	SC	20	Kep	3	2	2	-	-	-	-	O.F	15	35	35		Yes		Hillside
S-87	N29° 43' 56.2"	W98° 10' 35"	MB	30	Kep	3	3	2	-	-	-	-	X	7	37	37		Yes		Hillside
S-88	N29° 44' 3.42"	W98° 10' 42.7"	SC	20	Kep	2	1	1	-	-	-	-	O.F	12	32	32		Yes		Hillside
S-89	N29° 44' 3.3"	W98° 10' 18.1"	Z ^{VISC}	30	Kep	15	40		-	-	1-5	0.1-1	O.F	20	50		50		Yes	Floodplain
S-90	N29° 44' 14.1"	W98° 10' 25.4"	SC	20	Kep	6	5	1	-	-	-	-	O.F	19	39	39		Yes		Hillside
S-91	N29° 44' 10.7"	W98° 10' 19.5"	SC	20	Kep	2	2	2	-	-	-	-	O.F	15	35	35		Yes		Hillside
S-92	N29° 44' 7.32"	W98° 10' 32.5"	SC	20	Kep	4	1	2	-	-	-	-	O.F	17	37	37		Yes		Hillside
S-93	N29° 44' 8.33"	W98° 10' 32.1"	SH	20	Kep	4	5	2	-	-	-	-	O.F.C	20	40		40	Yes		Hillside
S-94	N29° 44' 9.1"	W98° 10' 20"	O ^{VR}	5	Kep	10	20		41	-	1-2	0.25-0.33	O.F	19	24	24			Yes	Hillside
S-95	N29° 44' 7.42"	W98° 10' 17.4"	O ^{VR}	5	Kep	20	50		76	-	1-4	0.1-0.33	O.F.C	19	24	24			Yes	Hillside
S-96	N29° 44' 7.87"	W98° 10' 16.1"	SC	20	Kep	1	1	1	-	-	-	-	O.F	19	39	39		Yes		Floodplain

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



December 31, 2009

Sheet 8 of 9

Frost GeoSciences

Geotechnical • Construction Materials • Forensics • Environmental

TCEQ-0585-Table (Rev. 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 11

GEOLOGIC ASSESSMENT TABLE						PROJECT NAME: The Tschirhart Ranch Subdivision - 267.038 Acres												FGS-E09176			
LOCATION			FEATURE CHARACTERISTICS											EVALUATION		PHYSICAL SETTING					
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10	11		12		
FEATURE	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY	CATCHMENT AREA (ACRES)		TOPOGRAPHY		
						X	Y	Z		10						< 40	≥ 40	<1.6	≥1.6		
S-97	N29° 44' 7.71"	W98° 10' 16.6"	O ^{VI}	5	Kep	15	75		-	-	14	0.10.25	O,F,C	19	24	24		Yes	Hillside		
S-98	N29° 44' 14.6"	W98° 10' 30.2"	SC	20	Kep	1	3	2	-	-	-	-	O,F	12	32	32		Yes	Hillside		
S-99	N29° 44' 7.02"	W98° 10' 30.1"	SC	20	Kep	3	3	1.5	-	-	-	-	O,F	19	39	39		Yes	Hillside		
S-100	N29° 44' 5.02"	W98° 10' 17.5"	F	20	Kep				-	-	-	-	-	-	-	-	-		Yes	Streambed	
S-101	N29° 43' 52.9"	W98° 10' 41.5"	MB	30	Kep	3	3	7	-	-	-	-	X	7	37	37		Yes	Hillside		
S-102	N29° 43' 49.9"	W98° 10' 42.7"	MB	30	Kep	3	3	7	-	-	-	-	X	7	37	37		Yes	Hillside		
S-103	N29° 44' 9.16"	W98° 10' 19.1"	SC	20	Kep	2	3	2	-	-	-	-	O,F,C	15	35	35		Yes	Hillside		
S-104	N29° 44' 00.9"	W98° 10' 25.3"	SC	20	Kep	2	2	2	-	-	-	-	O,F	19	39	39		Yes	Floodplain		
S-501	N29° 44' 13.74"	W98° 10' 34.74"	O ^{VI}	5	Kep	10	30	-	-	-	1	0.5	F	7	12	12		Yes	Hillside		
S-502	N29° 44' 16.5"	W98° 10' 30.9"	MB	30	Kep	50	100	-	-	-	-	-	F	5	35	35		Yes	Hillside		

* DATUM 1927 North American Datum (NAD27)

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution Cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow Hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Signature

Steve M. Frost



Date December 31, 2009

Sheet 9 of 9

Frost GeoSciences

Geotechnical • Construction Materials • Forensics • Environmental

TCEQ 400.001, 10-1-04)

December 31, 2009
The Tschirhart Ranch Subdivision
Page 12

LOCATION

The project site is located along and north of State Highway 46, approximately 3/4 miles northwest of the intersection of State Highway 46 and F.M. 1863, in New Braunfels, Texas. An overall view of the area is shown on copies of the site plan, a street map, the U.S.G.S. Topographic Map, the Official Edwards Aquifer Recharge Zone Map, the FIRM Map, a geologic map, a 2003 Aerial Photograph at a scale of 1"=1000', a 2003 Aerial Photograph at a scale of 1"=600', and a 1973 Aerial Photograph at a scale of 1"=1000', Plates 1a, 2, 3, 4, 5, 6, 8, and 9 in Appendix A.

METHODOLOGY

The Geologic Assessment was conducted by Mr. Steve Frost, C.P.G., President and Senior Geologist with Frost GeoSciences, Inc.. Mr. Frost is a Licensed Professional Geoscientist in the State of Texas (License # 315), and is a Certified Professional Geologist with the American Institute of Professional Geologist (Certification # 10176).

Frost GeoSciences, Inc. researched the geology of the area near the intersection of State Highway 46 and F.M. 1863. The research included, but was not limited to, the Bureau of Economic Geology, Geologic Atlas of Texas, San Antonio Sheet, FEMA maps, Edwards Aquifer Recharge Zone Maps, U.S.G.S. 7.5 Minute Quadrangle Maps, the Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle, the U.S.G.S. Water-Resources Investigations Report 94-4117, and the U.S.D.A. Soil Survey of Comal & Hays Counties, Texas.

After reviewing the available information, a field investigation was performed to identify any geologic or man made potential recharge features. A transect spacing of approximately 50 feet, or less depending on vegetation thickness, was used to inspect the project area. A 2003 aerial photograph, in conjunction with a hand held Garmin eTrex Summit Global Positioning System with an Estimated Potential Error ranging from 15 to 18 feet, was used to navigate around the property and identify the locations of potential recharge features, as recommended in the "Instructions to Geologists", TCEQ-0585-Instructions (Rev.

10-1-04). The locations of any potential recharge features noted in the field were marked with blue and white flagging. The flagging is numbered with the same potential recharge feature I.D. # that is used on the Site Geologic Map in Appendix C of this report. The Site Geologic Map indicating the limits of the project site and the locations of potential recharge features is included in Appendix C. A copy of a 2003 Aerial Photograph at an approximate scale of 1"=600' indicating the limits of the project site and the locations of potential recharge features is included on Plate 8 in Appendix A. The Geologic Assessment Form, Stratigraphic Column, and the Geologic Assessment Table have been filled with the appropriate information for this project site and are included on pages 1-12 of this report.

RESEARCH & OBSERVATIONS

7.5 Minute Quadrangle Map Review

According to the U.S.G.S. 7.5 Minute Quadrangle Map, New Braunfels West, Texas Sheet (1988), the elevation across the project site ranges from 760 to 860 feet above mean sea level. The project site has a total relief of approximately 100 feet. Runoff from the project site flows to the southeast and north into Blieders Creek. Blieders Creek then flows to the northeast. Blieders Creek is located along the southeastern property line. State Highway 46 is located immediately southwest of the project site. The intersection of State Highway 46 and F.M. 1863 is located southeast of the project site. Huego Springs Loop Road is located northwest of the project site. A few areas of residential development are visible south and southwest of the project site. A landing strip is located east of the project site. A flood control - recharge dam is located northeast of the project site along Blieders Creek. A copy of the U.S.G.S. 7.5 Minute Quadrangle Map indicating the location of the project site is included on Plate 3 in Appendix A.

Recharge / Transition Zone

According to the Official Edwards Aquifer Recharge Zone Map, New Braunfels West, Texas Sheet (1988), the project site is located within the Recharge Zone of the Edwards Aquifer.

A copy of the Official Edwards Aquifer Recharge Zone Map indicating the location of the project site is included on Plate 4 in Appendix A.

100-Year Floodplain

According to the Federal Emergency Management Agency (FEMA), Flood Insurance Rate Map (FIRM) Panel #'s 4854630100C and 4854630105C, revised 09-29-86, the areas along Blieders Creek in the northeast portion of project site are located within Zone A of the 100-year flood. The remainder of the project site is located in Zone C. According to the panel legend, Zone A represents areas of the 100 year flood plain where base flood elevations and flood hazards factors are not determined. Zone C represents areas of minimal flooding. A copy of the above referenced FIRM panels indicating the location of the project site is included on Plate 5 in Appendix A.

Soils

According to the United States Department of Agriculture, Soil Conservation Service, Soil Survey of Comal & Hays Counties, Texas, (1977), the project site is located on the Rumble-Comfort Association (RUD), and the Comfort-Rock Complex (CrD). A copy of the 1973 aerial photograph (approximate scale: 1"=1000') from the U.S.D.A. Soil Survey of Comal & Hays Counties, Texas indicating the location of the project site and the soil types is included on Plate 9 in Appendix A.

The Rumble-Comfort Association consists of shallow and moderately deep soils on uplands in the Edwards Plateau Land Resource Area. The surface layer of the Rumble Soil is dark reddish brown very cherty clay loam about 10 inches thick. Rounded chert and limestone cobbles and gravel cover about 20 percent of the surface. The subsoil to a depth of 14 inches is dark reddish-brown very cherty clay, and to a depth of 28 inches it is dark reddish-brown extremely stony clay. The underlying material is indurated fractured limestone. The Comfort Soil is dark brown, neutral, extremely stony clay about 7 inches thick. The

subsoil to a depth of 12 inches is dark reddish-brown, mildly alkaline, extremely stony clay. The underlying material is indurated fractured limestone. The soil is noncalcareous throughout. The soils in this association are well drained. Surface runoff is medium, but varies due to the occurrence of caves, fracture zones, and sinks. Permeability is moderately slow. Water erosion is a moderate hazard.

This soil has a USDA Texture Classification of very cherty clay loam, stony clay, very stony clay, extremely stony clay, and weathered bedrock. The Unified Classification is GC, CL or SC. The AASHTO Classification is A-2-6, A-6, and A-2-7. This soil has an average permeability from 0.2 to 0.6 inches/hour.

The Comfort-Rock Outcrop Complex consists of shallow, clayey soils and Rock Outcrop on side slopes and on hilltops and ridge tops on uplands in the Edwards Plateau Land Resource Area. The Comfort Extremely Stony Clay makes up 49 to more than 95 percent of the complex, but on the average it makes up 70 percent. Rock Outcrop and areas of soil less than 4 inches deep make up 5 to 36 percent, but the average is 15 percent. Typically, the surface layer of the Comfort soil is dark brown extremely stony clay about 6 inches thick. Cobbles and stones as much as 4 feet across cover about 45 percent of the surface. The subsoil extends to a depth of 13 inches. It is dark reddish brown extremely stony clay. The underlying material is indurated fractured limestone. The soil is mildly alkaline and noncalcareous throughout. The Comfort Soil is well drained. Surface runoff is slow to medium. Permeability is slow, and the available water capacity is very low. Water erosion is a slight hazard.

This soil has a USDA Texture Classification of extremely stony clay, stony clay, very stony clay, and weathered bedrock. The Unified Classification is CH, GC, CL, or SC. The AASHTO Classification is A-2-7, and A-7-6. This soil has an average permeability from 0.6 to 0.2 inches/hour.

Narrative Description of the Site Geology

Based on a visual inspection of the ground surface, the overall potential for fluid flow from the project site into the Edwards Aquifer appears to be low to intermediate.

One hundred two features were noted on the project site at the time of the field investigation on April 5-14 and 21-28, 2005. Ninety natural karst features and 12 man-made features were noted on the project site at the time of the field investigation. According to the U.S. Geological Survey Water Resources Investigations 94-4117, a fault (S-100) is located along the southeastern property line. No obvious visual indications of the fault were noted on the project site at the time of the on-site inspection. The natural karst features noted on the site consisted of numerous solution cavities, rock outcrops, and zones of fractured rock, vuggy rock, and solution cavities. A number of the solution cavities appeared to have been dug out by burrowing animals. The man made features consisted of man hole covers associated with a sanitary sewer line crossing the project site. The locations of the Potential Recharge Features are identified on the Site Plan on Plate 1a in Appendix A, on the 2003 aerial photograph on Plate 8 in Appendix A, and on the Site Geologic Map provided in Appendix C. Color photographs of the project site and some of the potential recharge features are included in Appendix B.

Potential Recharge Feature (PRF) #S-1 is a small solution cavity infilled with fine soil and leaves. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 27 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 4 of this report.

Potential Recharge Feature #S-2 consists of an outcrop of vuggy limestone. The outcrop was about 15 feet wide and 50 feet long. The vugs were approximately 6 inches in size and occurred at a density of 1 vug per foot. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 20 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 4 of this report.

Potential Recharge Features #S-3 through #S-5 consist of the solution cavities noted on the project site at the time of the field investigation. PRF #S-4 and PRF #S-5 appeared to be dug out by a burrowing animal. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 30 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 4 of this report.

Potential Recharge Feature #S-6 is an outcrop of vuggy and fractured limestone noted within a natural drainage path. The outcrop is about 25 feet wide and 75 feet long. The vugs ranged in size from 1/2 inches to 1 inch with a density of 4 to 5 vugs per foot. The fractures were approximately an inch in width and occurred in a density of 1 fracture per foot. The general trend of the fractures was 45 degrees. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 24 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 4 of this report.

Potential Recharge Features #S-7, #S-11, #S-22, #S-31, #S-43, #S-49, #S-50, #S-82, #S-84, #S-87, S-101, and S-102 are man hole covers associated with a sanitary sewer line crossing the project site along the southeastern portion of the property. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 37 on the sensitivity scale in column 10 of the Geologic Assessment Table on Pages 4-12 of this report.

Potential Recharge Features #S-8 and #S-9 are outcrops of vuggy and fractured limestone. PRF #S-8 is a cliff of limestone along Blieders Creek. The cliff is ranges from 3 feet to 15 feet along the length of the outcrop. PRF #S-9 is a outcrop of fractured limestone about 20 feet wide and 40 feet long. The fractures are approximately 1 inch in width and occur at a density of 1 fracture per foot. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 24 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 4 of this report.

Potential Recharge Features # S-10, #S-12, and #S-13 are solution cavities. PRF #S-10 is a vertical feature that is about 18 inches around and extends vertically about 2 feet. PRF #S-12

is a solution cavity noted under a limestone boulder. The feature is about 1 foot wide and 1 foot long and extends about 18 inches downward. PRF #S-13 appears to have been dug out by a burrowing animal. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 32 on the sensitivity scale in column 10 of the Geologic Assessment Table on Pages 4 and 5 of this report.

Potential Recharge Feature #S-14 consists of an outcrop of vuggy and fractured limestone noted in a natural drainage path. The outcrop was about 15 feet wide and 40 feet long. The vugs were approximately 1 to 2 inches in size and occurred at a density of 3 to 5 vugs per foot. The fractures are about 1 in width and occur 1 to 2 fractures per foot. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 30 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 5 of this report.

Potential Recharge Feature #'s S-15, #S-85, and #S-89 are zones of vuggy rock and solution cavities. The Zones consist of large vugs ranging from 4 inches to 12 inches with several solution cavities ranging from 4 inches to 18 inches. The vugs and solution cavities are infilled with fine soils leaves and other organic materials. PRF#S-15 was noted in a natural drainage path. According to the FEMA, Flood Insurance Rate Map, PRF #S-85 and PRF #S-89 are located in the 100 year flood plain. Frost GeoSciences, Inc. rates these features as intermediate on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 50 to 55 on the sensitivity scale in column 10 of the Geologic Assessment Table on Pages 5 and 11 of this report.

Potential Recharge Features #S-16 through #S-20 are solution cavities noted on the site at the time of the field inspection. PRF #S-16 appears to have been dug out by a burrowing animal. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 32 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 5 of this report.

Potential Recharge Features #S-21 and #S-35 appear to be outcrops of solution enlarged fractures. PRF #S-21 is about 15 feet wide and 30 feet long. The fractures are about 1 to 2 inches in width and occur at a density of 1 to 2 fractures per foot. The dominate trend of the

fractures was about 45 degrees. The outcrop was noted in a natural drainage path. PRF #S-35 is about 10 feet wide and 15 feet long. The fractures are about 2 to 4 inches wide and occur at about 1 to 2 fractures per foot. The dominate trend of the fractures was about 78 degrees. Frost GeoSciences, Inc. rates this feature as intermediate on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 50 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 5 and 6 of this report.

Potential Recharge Features #S-23 and #S-24 are elongated solution cavities approximately 6 inches in width and 4 feet in length. The features are infilled with fine soils and leaves. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 35 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 5 of this report.

Potential Recharge Features #S-25, #S-38, and #S-61 are zones of vuggy and fractured rock. The widths of the zones range from 30 to 50 feet and the lengths range from 75 to 100 feet. Each of the outcrop zones were noted in natural drainage paths. The vugs ranged in size from 1 inch to 3 inches and occurred at a density of 1 to 4 per foot. The fractures ranged in size from 1 to 2 inches in width and occurred at a density of 1 to 3 per foot. The orientation of the fractures varied. Frost GeoSciences, Inc. rates these features as intermediate on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score a 50 on the sensitivity scale in column 10 of the Geologic Assessment Table on Pages 6, 7, and 9 of this report.

Potential Recharge Features #S-26, #S-28 through #S-30, and #S-32 through #S-34 are solution cavities noted on the project site at the time of the field inspection. The features are infilled with fine soils and leaves. The features range in size from 12 inches to 18 inches wide and 1 to 4 feet in length. The features were about 18 inches to 2 feet deep. PRF #S-26, PRF #S-28, and PRF #S-30 appeared to be dug out by a burrowing animal. PRF #S-29 is an elongated solution cavity. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 30 to 39 on the sensitivity

scale in column 10 of the Geologic Assessment Table on Page 6 of this report.

Potential Recharge Feature #S-27 is an outcrop of vuggy rock typical of the outcrops noted on the project site at the time of the field investigation. The outcrop is about 20 feet wide and 60 feet long. The vugs were 2 to 6 inches in size and occur at a density of 2 to 3 per foot. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 17 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 5 of this report.

Potential Recharge Features #S-36, #S-39, #S-41, #S-42, #S-44, #S-45, #S-47, and #S-48 are solution cavities noted on the project site at the time of the field investigation. The features were infilled with fine soils and leaves and twigs. PRF #S-42 and PRF #S-48 appear to have been dug out by burrowing animals at one time. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 30 to 32 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 6 and 7 of this report.

Potential Recharge Feature #S-37 is a outcrop of vuggy rock noted on the project site at the time of the field investigation. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 20 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 7 of this report.

Potential Recharge Feature #S-40 is a closed depression about 4 feet wide and 5 feet long. The feature is about 1 foot deep and may be the result of a tree removal. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 14 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 5 of this report.

Potential Recharge Feature #S-46 is a solution enlarged fracture about 2 feet wide and 10 feet long. The feature appears to be a few solution cavities in a row. The feature appears to be about 2 feet deep and infilled with soil, leaves, twigs, and gravel. Frost GeoSciences, Inc. rates this

feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 39 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 7 of this report.

Potential Recharge Features #S-51, #S-52, and #S-57 are outcrops of vuggy and fractured rock. PRF #S-52 is located in a natural drainage path. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 17 to 34 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 8 of this report.

Potential Recharge Features #S-53, #S-55, and #S-58 are outcrops of vuggy rock noted on the project site at the time of the field inspection. The outcrops all have vugs ranging in size from 1 to 3 inches with a density ranging from 3 to 6 vugs per foot. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 15 to 17 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 8 of this report.

Potential Recharge Features #S-54, #S-56, #S-59, #S-60, #S-62, and #S-66 through #S-68 are solution cavities noted on the project site at the time of the field investigation. The features were infilled with fine soils and leaves and twigs. The size of the features range in size from 6 inches to 2 feet wide, 6 inches to 2 feet long, and 1 to 2 feet deep. PRF #S-54 appears to have been dug out by burrowing animals at one time. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 30 to 32 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 8 and 9 of this report.

Potential Recharge Feature #S-63 is a cave noted in the wall of a cliff. The cliff was noted along a natural drainage path. The opening of the cave was about 4 feet tall and 10 feet wide. The cave extended horizontally approximately 10 feet into the cliff. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). This feature scores a 20 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 9 of this report.

Potential Recharge Features #S-65 and #S-69 are outcrops of vuggy and fractured rock noted on the project site at the time of the field inspection. #S-65 have fractures ranging in size from 1 to 2 inches wide and the fractures occur about 1 to 2 fractures per foot. #S-69 have vugs ranging in size from 1 to 3 inches with a density ranging from 3 to 6 vugs per foot. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 17 to 20 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 8 of this report.

Potential Recharge Features #S-70 and #S-71 are solution cavities noted in a natural drainage path. The features were infilled with fine soils and leaves and twigs. Frost GeoSciences, Inc. rates these features as intermediate on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score 40 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 8 and 9 of this report.

Potential Recharge Features #S-72, #S-75 through #S-80, and #S-83 are solution cavities noted on the project site at the time of the field investigation. The features were infilled with fine soils and leaves and twigs. The size of the features range in size from 6 inches to 2 feet wide, 6 inches to 2 feet long, and 1 to 2 feet deep. PRF #S-75 appears to have been dug out by a burrowing animal at one time. PRF #S-78 is about 5 feet wide, 5 feet long and 1 foot deep. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 32 to 39 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 9 and 10 of this report.

Potential Recharge Features #S-73 and #S-74 are outcrops of vuggy and fractured rock noted on the project site at the time of the field inspection. PRF #S-73 have vugs ranging in size from 1 to 3 inches with a density ranging from 3 to 6 vugs per foot. PRF #S-74 have fractures ranging in size from 1 to 2 inches wide and the fractures occur about 1 to 2 fractures per foot. Frost GeoSciences, Inc. rates these features as intermediate on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score 25 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 10 of this report.

Potential Recharge Features #S-81 and #S-93 are sinkholes. PRF S#-81 is about 10 feet around and 1 foot deep. A tree was noted growing in the middle of the feature. The feature was infilled with fine soils, coarse sand, cobbles, and with grass and shrubs. PRF #S-93 is 4 feet wide, 5 feet long, and 2 feet deep. The feature is infilled with coarse soils and gravel as well as leaves and twigs. Frost GeoSciences, Inc. rates these features as intermediate on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score 40 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 10 and 11 of this report.

Potential Recharge Features #S-86, #S-88, and #S-90 through #S-92 are solution cavities noted on the project site at the time of the field investigation. The features were infilled with fine soils and leaves and twigs. The size of features PRF #S-86, PRF #S-88, PRF #S-91 and PRF #S-92 range in size from 1 foot to 4 feet wide, 1 foot to 2 feet long, and 1 to 2 feet deep. PRF #S-90 is about 6 feet wide, 5 feet long and 1 foot deep. PRF #S-92 appears to have been dug out by a burrowing animal at one time. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 32 to 39 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 11 of this report.

Potential Recharge Features #S-94, #S-95 and #S-97 are outcrops of vuggy rock noted on the project site at the time of the field inspection. The outcrops have vugs ranging in size from 1 to 3 inches with a density ranging from 3 to 6 vugs per foot. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features score 24 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 10 of this report.

Potential Recharge Features #S-96, #S-98, and #S-99 are solution cavities noted on the project site at the time of the field investigation. The features were infilled with fine soils and leaves and twigs. According to the FEMA, Flood Insurance Rate Map, PRF #S-96 are located in the 100 year flood plain. PRF #S-98 and PRF #S-99 appears to have been dug out by a burrowing animal at one time. Frost GeoSciences, Inc. rates these features as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 5-01-02). These features range in score from 32 to 39 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 11 and 12 of this report.

Potential Recharge Feature #S-I03 consist of three small solution cavities in a limestone boulder. The features are infilled with leaves and fine soils. The small cavities range in size from 8 inches to 18 inches wide and 12 to 18 inches in length. The general overall width and length of the feature is approximately 2 feet by 3 feet. The overall depth of the feature was about 18 inches to 2 feet deep. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). This feature scores a 35 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 12 of this letter.

Potential Recharge Feature #S-I04 is solution cavity within a closed depression. The solution cavity was approximately 2 feet wide and 2 feet long. The closed depression was approximately 3 feet wide and 4 feet long. The overall depth appears to be 18 inches to 2 feet. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). This feature scores a 39 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 12 of this report.

Potential Recharge Feature #S-501 is an outcrop of vuggy limestone. The vugs are up to 6 inches and spaced approximately 1 per foot. These vugs are infilled with dark clay and would allow little or no fluid flow into the subsurface. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). This feature scores a 12 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 12 of this report.

Potential Recharge Feature #S-502 is an area of cleared vegetation that appears to have been used to have a line of sight from a deer blind to a feeder. No indications of infiltration were noted within the cleared area. Frost GeoSciences, Inc. rates this feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). This feature scores a 35 on the sensitivity scale in column 10 of the Geologic Assessment Table on Page 12 of this report.

According to the U.S. Geological Survey Water Resources Investigations 94-4117, Potential Recharge Feature #S-I00 is a fault located along the southeastern property line. No obvious visual indications of the fault were noted on the project site at the time of the on-site inspection.

The project site supports a dense stand of vegetative cover with a several open grassy areas. Overall vegetation on the project site consists of ashe juniper (*Juniperus ashei*), live oak (*Quercus virginiana*), cedar elm (*Ulmus crassifolia*), and mesquite (*Prosopis glandulosa*), with Texas persimmon (*Diospyros texana*), agarita (*Berberis trifoliolata*), huisache (*Acacia farnesiana*), sage (*Leucophyllum*), whitebrush (*Aloysia gratissima*), Yucca, mountain laurel, and prickly pear cactus (*Opuntia lindheimeri*).

According to the site plan provided by Schultz Group, Inc., the surveyed elevations on the project site range from 760 to 860 feet. A copy of the site plan indicating the boundary of the project site and the elevations is included on the Site Plan on Plate 1a in Appendix A and the Site Geologic Map in Appendix C of this report.

According to the U.S. Geological Survey Water Resources Investigations 94-4117, the project site is located on the Cyclic and Marine Member and the Leached and Collapsed Member of the Cretaceous Edwards Person Limestone.

The Cyclic and Marine Member of the Edwards Person Limestone consists of mudstone to packstone with milliolid grainstone and chert. This member occurs as thin graded cycles of massive to relatively thin beds with some crossbeds. Typically, cavern development in this member is common, but occurs mainly in the subsurface. The caverns within this member might be associated with earlier episodes of karst development.

The Leached and Collapsed Member of the Cretaceous Edwards Person Limestone consists of crystalline limestone, mudstone, and grainstone with chert and collapsed breccia. Bioturbated iron-stained beds are common and are separated by massive limestone beds with stromatolitic limestone. This member forms extensive lateral karst development with large rooms. The overall thickness of this member ranges from 70 to 90 feet thick.

A copy of the U.S.G.S. Water Resources Investigation 94-4117 indicating the location of the project site is included on Plate 6 in Appendix A.

BEST MANAGEMENT PRACTICE (BMP)

Based on a visual inspection of the ground surface and the research performed for this project, the overall potential for fluid flow from the project site into the Edwards Aquifer appears to be low to intermediate. According to the U.S. Geological Survey Water Resources Investigations 94-4117, a fault located along the southeastern property line. No obvious visual indications of the fault were noted on the project site at the time of the on-site inspection. However, the potential always exists to encounter subsurface features that lack a surface expression. Construction personnel should be informed of the potential to encounter subsurface karst features associated with the fault, vuggy outcrops, or outcrops zones during excavating activities. Construction personnel should also be informed of the proper protocol to follow in the event that a solution cavity and/or cave is encountered during the excavation and development of the property.


DISCLAIMER

This report has been prepared in general accordance with the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04) by a Licensed Texas Professional Geoscientist. All areas of the project site were carefully inspected for features that could contribute to the recharge of the Edwards Aquifer, however, this survey cannot preclude the presence of subsurface karst features that lack surface expression. This report is not intended to be a definitive investigation of all possible geologic or karst features at this site. All conclusions, opinions, and recommendations for Best Management Practices (BMP's) in this report are based on information obtained while researching the project, and on the site conditions at the time of our field investigation.

This report has been prepared for the exclusive use of The Schultz Group. This report is based on available known records, a visual inspection of the project site, and the work generally accepted for a Geologic Assessment for Regulated Activities / Developments on the Edwards Aquifer Recharge / Transition Zone, relating to 30 TAC §213.5(b)(3), effective June 1, 1999.

REFERENCES

- 1) U.S.G.S. 7.5 Minute Quadrangle Map, New Braunfels West, Texas Sheet (1988).
- 2) Official Edwards Aquifer Recharge Zone Map, New Braunfels West, Texas Sheet (1996).
- 3) Small, Ted A., and Hanson, John A., 1994, Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Outcrop, Comal County, Texas.
U.S. Geological Survey Water Resources Investigations 94-4117.
- 4) Barnes, V.L., 1983, Geologic Atlas of Texas, San Antonio Sheet, Bureau of Economic Geology, The University of Texas at Austin, Texas.
- 5) Federal Emergency Management Agency (FEMA), May 15, 1991, Comal County, Texas and Incorporated Areas, Flood Insurance Rate Map (FIRM), Panel #'s 4854630100C and 4854630105C, FEMA, Washington D.C.
- 6) U.S.D.A. Soil Conservation Service, Soil Survey of Comal and Hayes County, Texas (1984).
- 7) TCEQ-0585-Instructions (Rev. 10-1-04), "Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zone".
- 8) Collins, Edward, W., 2000, Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle, Bureau of Economic Geology, The University of Texas at Austin, Texas.



1 inch = 600 feet

PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas


Site Plan with PRF's

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas


Street Map

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas


U.S.G.S. 7.5 Minute Quadrangle Map
New Braunfels West, Texas Sheet (1988)

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas


Official Edwards Aquifer Recharge Zone Map
New Braunfels West, Texas Sheet 1988

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas

Flood Insurance Rate Map (FIRM)


Community Panel #'s
4854630100C & 4854630105C (9-29-1986)

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas

United States Geologic Survey
Water Resources Investigations #94-4117
Geologic Map of Comal County, Texas

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas

2009 Aerial Photograph
LandisCor Aerial Information

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
The Tschirhart Ranch Subdivision
New Braunfels, Texas


1973 Aerial Photograph
United States Department of Agriculture

PROJECT NO.:

FGS-E09176

DATE:

December 31, 2009



PROJECT NAME: Geologic Site Assessment (WPAP) for Regulated Activities / Development on the Edwards Aquifer Recharge / Transition Zone The Tschirhart Ranch Subdivision New Braunfels, Texas		2009 Aerial Photograph with Potential Recharge Feature Locations LandisCor Aerial Information	
PROJECT NO.: FGS-E09176		DATE: December 31, 2009	



View of potential recharge feature # S-1.



Typical view of the vegetative cover noted near S-1.



View of potential recharge feature # S-2.




Typical view of the vegetative cover noted near S-2.



View of potential recharge feature # S-3.



Typical view of the vegetative cover noted near S-3.



View of potential recharge feature # S-4.



Typical view of vegetative cover noted near S-4.



View of potential recharge feature # S-5.



Typical view of the vegetative cover noted near S-5..



View of Potential Recharge Feature # S-6.




View of Potential Recharge Feature # S-7.



View of Potential Recharge Feature # S-8.



View of Potential Recharge Feature # S-8.



View of Potential Recharge Feature # S-9.



Typical view of the vegetative cover noted near S-9.



View of Potential Recharge Feature # S-10.



View of the interior of S-10.



Typical view of the vegetative cover noted near S-10.




View of Potential Recharge Feature # S-11.



View of Potential Recharge Feature # S-12.



View of Potential Recharge Feature # S-13.



Typical view of the vegetative cover noted near S-13.



View of Potential Recharge Feature # S-14.



Typical view of the vegetative cover noted near S-14.



Typical view of the vegetative cover noted near S-15.



View to the east along the Potential Recharge Feature # S-15.



View to the west along the Potential Recharge Feature # S-15.



View of Potential Recharge Feature # S-19.




Typical view of the vegetative cover noted near S-19.



View of Potential Recharge Feature # S-21.




Typical view of the vegetative cover noted near S-21.



View of Potential Recharge Feature # S-23.




Typical view of the vegetative cover noted near S-23.



View of Potential Recharge Feature # S-24.



Typical view of the vegetative cover noted near S-24.



View of Potential Recharge Feature # S-25.



Typical view of the vegetative cover noted near S-25.



View of Potential Recharge Feature # S-26.



Typical view of the vegetative cover noted near S-26.




View of Potential Recharge Feature # S-27.




View of Potential Recharge Feature # S-27.



Typical view of the vegetative cover noted near S-27.



View of Potential Recharge Feature # S-28.



View of Potential Recharge Feature # S-29.




Typical view of the vegetative cover noted near S-29.



View of Potential Recharge Feature # S-30.



Typical view of the vegetative cover noted near S-30.



View of Potential Recharge Feature # S-32.



Typical view of the vegetative cover noted near S-32.



View of Potential Recharge Feature # S-34.



Typical view of the vegetative cover noted near S-34.



View of Potential Recharge Feature # S-35.



Typical view of the vegetative cover noted near S-35.



View of Potential Recharge Feature # S-36.



Typical view of the vegetative cover noted near S-36.



View of Potential Recharge Feature # S-37.



Typical view of the vegetative cover noted near S-37.



View to the east along the rock outcrop of Potential Recharge Feature # S-38.




View to the west along the rock outcrop of Potential Recharge Feature # S-38.



View of Potential Recharge Feature # S-39.



Typical view of the vegetative cover noted near S-39.



View of Potential Recharge Feature # S-40.



Typical view of the vegetative cover noted near S-40.



View of Potential Recharge Feature # S-42.



Typical view of the vegetative cover noted near S-42.



View of Potential Recharge Feature # S-46.



Typical view of the vegetative cover noted near S-46.



View of Potential Recharge Feature # S-47.



View of Potential Recharge Feature # S-48.



View of Potential Recharge Feature # S-52.




Typical view of the vegetative cover noted near S-52.



View of Potential Recharge Feature # S-53.



Typical view of the vegetative cover noted near S-53.



View of Potential Recharge Feature # S-54.



Typical view of the vegetative cover noted near S-54.



View of Potential Recharge Feature # S-55.



Typical view of the vegetative cover noted near S-55.



View of Potential Recharge Feature # S-56.



Typical view of the vegetative cover noted near S-56.



View of Potential Recharge Feature # S-57.



View of Potential Recharge Feature # S-58.



Typical view of the vegetative cover noted near S-58.



View of Potential Recharge Feature # S-59.



View of Potential Recharge Feature # S-61.




Typical view of the vegetative cover noted near S-61.



Typical view of the vegetative cover noted near S-61.



View of Potential Recharge Feature # S-63.



View of Potential Recharge Feature # S-64.



Typical view of the vegetative cover noted near S-64.



View of Potential Recharge Feature # S-65.



View of Potential Recharge Feature # S-65.



View of Potential Recharge Feature # S-66.



Typical view of the vegetative cover noted near S-66.



View of Potential Recharge Feature # S-67.



Typical view of the vegetative cover noted near S-67.



View of Potential Recharge Feature # S-68.



Typical view of the vegetative cover noted near S-68.



View of Potential Recharge Feature # S-69.



View of Potential Recharge Feature # S-69.



View of Potential Recharge Feature # S-70.



View of Potential Recharge Feature # S-72.



Typical view of the vegetative cover noted near S-72.



View of Potential Recharge Feature # S-73.



View of Potential Recharge Feature # S-74.



View of Potential Recharge Feature # S-74.



View of Potential Recharge Feature # S-75.



Typical view of the vegetative cover noted near S-75.



View of Potential Recharge Feature # S-77.



Typical view of the vegetative cover noted near S-77.



View of Potential Recharge Feature # S-78.



View of Potential Recharge Feature # S-78.



View of Potential Recharge Feature # S-79.



View of Potential Recharge Feature # S-80.



View of Potential Recharge Feature # S-81.




View of Potential Recharge Feature # S-81.



View of Potential Recharge Feature # S-83.



View of Potential Recharge Feature # S-85.



View of Potential Recharge Feature # S-85.



View of Potential Recharge Feature # S-86.



View of Potential Recharge Feature # S-88.



View of Potential Recharge Feature # S-89.




View of Potential Recharge Feature # S-89.



View of Potential Recharge Feature # S-89.



View of Potential Recharge Feature # S-90.



View of Potential Recharge Feature # S-91.



View of Potential Recharge Feature # S-92.



Typical view of the vegetative cover noted near S-92.



View of Potential Recharge Feature # S-93.




Typical view of the vegetative cover noted near S-93.



View of Potential Recharge Feature # S-94.



View of Potential recharge Feature # S-95.



Typical view of the vegetative cover noted near S-95.



View of Potential Recharge Feature # S-96.



View of Potential Recharge Feature # S-97.



Typical view of the vegetative cover noted near S-97.



View of Potential Recharge Feature # S-98.




Typical view of the vegetative cover noted near S-98.




View of Potential Recharge Feature # S-99.



Typical view of the vegetative cover noted near S-99.



View of Potential Recharge Feature # S-103.



Site Geologic Map

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
for the
Tschirhart Ranch Subdivision
267.038 Acres
New Braunfels, Texas

Frost GeoSciences, Inc. Control # FGS-E09176

Legend


- Fill - Fill Material
- Qal - Alluvium
- Kau - Austin Chalk
- Kef - Eagle Ford Shale
- Kbu - Buda Limestone
- Kdr - Del Rio Clay
- Kgt - Georgetown Limestone
- Kep - Edwards Person Limestone
- Kek - Edwards Kainer Limestone
- Kgr - Glen Rose Formation
- S# - Potential Recharge Feature (PRF)
- - - - - Formation Contact
- 100-Year Floodplain - Zone A
- 100-Year Floodplain - Zone AE
- Other Flood Hazard Area - Zone X (shaded)

Floodplain Information Obtained From:
FIRM: Flood Insurance Rate Map
Comal County, Texas: Panel # 4854630100C, Revised 2/29/86
Comal County, Texas: Panel # 4854630105C, Revised 2/29/86

Fault Information Obtained From:
Bureau of Economic Geology, Geologic Atlas of Texas, San Antonio Sheet (1983)
U.S. Geological Survey, Water Resources Investigations Report 94-4117 (1994)
Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle (2000)



Steve Frost
Signature of Texas Licensed Geoscientist
Steve Frost, TPG# 315, AIPG # 10176



Modification of a Previously Approved Plan
for Regulated Activities on the
Edwards Aquifer Recharge Zone and Transition Zone
and Relating to 30 TAC 213.4(j), Effective June 1, 1999

1. Current Regulated Entity Name: Water Pollution Abatement Plan for Tschirhart Ranch Subdivision
Original Regulated Entity Name: Manor Creek Subdivision
Assigned Regulated Entity Numbers (RN): 1) _____, 2) _____, 3) _____

☒ The applicant has not changed and the Customer Number (CN) is: CN 601213523
☐ The applicant has changed. A new Core Data Form has been provided.
2. ☒ **Attachment A: Original Approval Letter and Approved Modification Letters:** A copy of the original approval letter and copies any letters approving modification are found at the end of this form.
3. A modification of a previously approved plan is requested for (check all that apply):

☐ physical or operational modification of any water pollution abatement structure(s) including but not limited to ponds, dams, berms, sewage treatment plants, and diversionary structures;
☐ change in the nature or character of the regulated activity from that which was originally approved or a change which would significantly impact the ability of the plan to prevent pollution of the Edwards Aquifer;
☒ development of land previously identified as undeveloped in the original water pollution abatement plan;
☐ physical modification of the approved organized sewage collection system;
☐ physical modification of the approved underground storage tank system;
☐ physical modification of the approved aboveground storage tank system.
4. Summary of Proposed Modifications (select plan type being modified). If the approved plan has been modified more than once, copy the appropriate table below, as necessary, and complete the information for each additional modification.

WPAP Modification Summary	Approved Project	Proposed Modification
Acres	<u>252.038</u>	<u>266.916</u>
Type of Development	<u>Residential</u>	<u>Residential</u>
Number of Residential Lots	<u>343</u>	<u>340</u>
Impervious Cover (acres)	<u>50.29</u>	<u>53.141</u>
Impervious Cover (%)	<u>19.95%</u>	<u>19.91%</u>
Permanent BMPs	<u>Vegetative Buffers</u>	<u>Vegetative Buffers</u>
Other	_____	_____
SCS Modification Summary	Approved Project	Proposed Modification
Linear Feet	_____	_____
Pipe Diameter	_____	_____
Other	_____	_____
AST Modification Summary	Approved Project	Proposed Modification
Number of ASTs	_____	_____
Volume of ASTs	_____	_____
Other	_____	_____

UST Modification Summary

Approved Project

Proposed Modification

Number of USTs

Volume of USTs


Other

5. X **Attachment B: Narrative of Proposed Modification.** A narrative description of the nature of the proposed modification is provided at the end of this form. It discusses what was approved, including previous modifications, and how this proposed modification will change the approved plan.
6. X **Attachment C: Current site plan of the approved project.** A current site plan showing the existing site development (i.e., current site layout) at the time this application for modification is provided at the end of this form. A site plan detailing the changes proposed in the submitted modification is required elsewhere.
- ____ The approved construction has not commenced. The original approval letter, and any subsequent modification approval letters are included as Attachment A to document that the approval has not expired.
- ____ The approved construction has commenced and has been completed. Attachment C illustrates that the site was constructed as approved.
- ____ The approved construction has commenced and has been completed. Attachment C illustrates that the site was **not** constructed as approved.
- ____ The approved construction has commenced and has **not** been completed. Attachment C illustrates that, thus far, the site was constructed as approved.
- X The approved construction has commenced and has **not** been completed. Attachment C illustrates that, thus far, the site was **not** constructed as approved.
7. X The acreage of the approved plan has increased. A Geologic Assessment has been provided for the new acreage.
- ____ Acreage has not been added to **or** removed from the approved plan.
8. X One (1) original and 3 4 copies of the complete application has been provided.


To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This request for a **MODIFICATION TO A PREVIOUSLY APPROVED PLAN** is hereby submitted for TCEQ review and executive director approval. The request was prepared by:

Michael G. Short, P.E.

Print Name of Customer/Agent


Signature of Customer/Agent2/11/10
Date

Kathleen Hartnett White, *Chairman*
R. B. "Ralph" Marquez, *Commissioner*
Larry R. Soward, *Commissioner*
Glenn Shankle, *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

April 4, 2006

Mr. Timothy D. Pruski
Continental Homes of Texas
211 N. Loop 1604 East, Suite 130
San Antonio, TX 78232

Re: Edwards Aquifer, Comal County
NAME OF PROJECT: Manor Creek (Tschirhart Ranch) ; Located on the north side of State Highway 46, approximately 2 miles west of the intersection of Loop 337 and State Highway 46; New Braunfels, Texas
TYPE OF PLAN: Request for Approval of a Water Pollution Abatement Plan (WPAP); 30 Texas Administrative Code (TAC) Chapter 213 Edwards Aquifer
Edwards Aquifer Protection Program ID No. 2439.00
Investigation Number: 449964
Regulated Entity Number: RN104801568

Dear Mr. Pruski:

The Texas Commission on Environmental Quality (TCEQ) has completed its review of the WPAP application for the referenced project submitted to the San Antonio Regional Office by The Schultz Group, Inc. on behalf of Continental Homes of Texas on December 7, 2007. Final review of the WPAP application was completed after additional material was received on March 31, 2006. As presented to the TCEQ, the Temporary and Permanent Best Management Practices (BMPs) and construction plans were prepared by a Texas Licensed Professional Engineer to be in general compliance with the requirements of 30 TAC Chapter 213. These planning materials were sealed, signed, and dated by a Texas Licensed Professional Engineer. Therefore, based on the engineer's concurrence of compliance, the planning materials for construction of the proposed project and pollution abatement measures are hereby approved subject to applicable state rules and the conditions in this letter. The applicant or a person affected may file with the chief clerk a motion for reconsideration of the executive director's final action on this Edwards Aquifer protection plan. A motion for reconsideration must be filed no later than 23 days after the date of this approval letter. *This approval expires two (2) years from the date of this letter unless, prior to the expiration date, more than 10 percent of the construction has commenced on the project or an extension of time has been requested.*

PROJECT DESCRIPTION

The proposed single family residential project will have an area of approximately 252.038 acres. It will include 343 lots, roads, and utilities. The impervious cover will be 50.29 acres (19.95 percent). Project wastewater will be disposed of by conveyance to the existing Gruene Road Wastewater Treatment Plant owned by the New Braunfels Utilities.

PERMANENT POLLUTION ABATEMENT MEASURES

Since this single-family residential project will not have more than 20 percent impervious cover, an exemption from permanent BMPs is approved.

REPLY TO: REGION 13 • 14250 JUDSON RD. • SAN ANTONIO, TEXAS 78233-4480 • 210/490-3096 • FAX 210/545-4329

P.O. Box 13087 • Austin, Texas 78711-3087 • 512/239-1000 • Internet address: www.tceq.state.tx.us

cc: enclosed - none cc: hand

GEOLOGY

According to the geologic assessment included with the application and additional information submitted during the review, 104 geologic and man-made features were identified on the site. Thirteen of the features, S15, S21, S25, S35, S38, S61, S63, S70, S71, S81, S85, S89, and S93, were initially assessed as sensitive. Two of the sensitive features, S-38 and S-93, received additional evaluation by the geologist, who determined the features not to be sensitive. The San Antonio Regional Office site inspection of March 22, 2006, revealed that the site is generally as described by the geologic assessment.

SPECIAL CONDITIONS

- I. If the impervious cover ever increases above 20 percent or the land use changes, the exemption for the whole site may no longer apply and the property owner must notify the San Antonio Regional Office of these changes.
- II. Intentional discharges of sediment laden stormwater are not allowed. If dewatering becomes necessary, the discharge will be filtered through appropriately selected best management practices. These may include vegetative filter strips, sediment traps, rock berms, silt fence rings, etc.
- III. As proposed, a 50 foot natural buffer will be provided around geologic features assessed as sensitive.

STANDARD CONDITIONS

1. Pursuant to Chapter 7 Subchapter C of the Texas Water Code, any violations of the requirements in 30 TAC Chapter 213 may result in administrative penalties

Prior to Commencement of Construction:

2. Within 60 days of receiving written approval of an Edwards Aquifer protection plan, the applicant must submit to the San Antonio Regional Office, proof of recordation of notice in the county deed records, with the volume and page number(s) of the county deed records of the county in which the property is located. A description of the property boundaries shall be included in the deed recordation in the county deed records. A suggested form (Deed Recordation Affidavit, TNRCC-0625) that you may use to deed record the approved WPAP is enclosed.
3. All contractors conducting regulated activities at the referenced project location shall be provided a copy of this notice of approval. At least one complete copy of the approved WPAP and this notice of approval shall be maintained at the project location until all regulated activities are completed.
4. Modification to the activities described in the referenced WPAP application following the date of approval may require the submittal of a plan to modify this approval, including the payment of appropriate fees and all information necessary for its review and approval prior to initiating construction of the modifications.
5. The applicant must provide written notification of intent to commence construction, replacement, or rehabilitation of the referenced project. Notification must be submitted to the San Antonio Regional Office no later than 48 hours prior to commencement of the regulated activity. Written notification must include the date on which the regulated activity will commence, the name of the approved plan and program ID number for the regulated activity, and the name of the prime

contractor with the name and telephone number of the contact person. The executive director will use the notification to determine if the approved plan is eligible for an extension.

6. Temporary erosion and sedimentation (E&S) controls, i.e., silt fences, rock berms, stabilized construction entrances, or other controls described in the approved WPAP, must be installed prior to construction and maintained during construction. Temporary E&S controls may be removed when vegetation is established and the construction area is stabilized. If a water quality pond is proposed, it shall be used as a sedimentation basin during construction. The TCEQ may monitor stormwater discharges from the site to evaluate the adequacy of temporary E&S control measures. Additional controls may be necessary if excessive solids are being discharged from the site.
7. All borings with depths greater than or equal to 20 feet must be plugged with non-shrink grout from the bottom of the hole to within three (3) feet of the surface. The remainder of the hole must be backfilled with cuttings from the boring. All borings less than 20 feet must be backfilled with cuttings from the boring. All borings must be backfilled or plugged within four (4) days of completion of the drilling operation. Voids may be filled with gravel.

During Construction:

8. During the course of regulated activities related to this project, the applicant or agent shall comply with all applicable provisions of 30 TAC Chapter 213, Edwards Aquifer. The applicant shall remain responsible for the provisions and conditions of this approval until such responsibility is legally transferred to another person or entity.
9. If any sensitive feature (caves, solution cavities, sink holes, etc.) is discovered during construction, all regulated activities near the feature must be suspended immediately. The applicant or his agent must immediately notify the San Antonio Regional Office of the discovery of the feature. Regulated activities near the feature may not proceed until the executive director has reviewed and approved the methods proposed to protect the feature and the aquifer from potentially adverse impacts to water quality. The plan must be sealed, signed, and dated by a Texas Licensed Professional Engineer.
10. No wells exist on the site. All water wells, including injection, dewatering, and monitoring wells must be in compliance with the requirements of the Texas Department of Licensing and Regulation under Title 16 TAC Chapter 76 (relating to Water Well Drillers and Pump Installers) and all other locally applicable rules, as appropriate.
11. If sediment escapes the construction site, the sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50 percent. Litter, construction debris, and construction chemicals shall be prevented from becoming stormwater discharge pollutants.
12. The following records shall be maintained and made available to the executive director upon request: the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
13. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, and construction activities will not resume within 21 days. When the initiation of stabilization measures by the 14th day is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable.

Mr. Timothy D. Pruski

Page 4


April 4, 2006

After Completion of Construction:

14. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the San Antonio Regional Office within 30 days of site completion.
15. The applicant shall be responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. The regulated entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred. A copy of the transfer of responsibility must be filed with the executive director through the San Antonio Regional Office within 30 days of the transfer. A copy of the transfer form (TNRCC-10263) is enclosed.
16. Upon legal transfer of this property, the new owner(s) is required to comply with all terms of the approved Edwards Aquifer protection plan. If the new owner intends to commence any new regulated activity on the site, a new Edwards Aquifer protection plan that specifically addresses the new activity must be submitted to the executive director. Approval of the plan for the new regulated activity by the executive director is required prior to commencement of the new regulated activity.
17. An Edwards Aquifer protection plan approval or extension will expire and no extension will be granted if more than 50 percent of the total construction has not been completed within ten years from the initial approval of a plan. A new Edwards Aquifer protection plan must be submitted to the San Antonio Regional Office with the appropriate fees for review and approval by the executive director prior to commencing any additional regulated activities.
18. At project locations where construction is initiated and abandoned, or not completed, the site shall be returned to a condition such that the aquifer is protected from potential contamination.

If you have any questions or require additional information, please contact Lynn M. Bumgardner of the Edwards Aquifer Protection Program of the San Antonio Regional Office at 210.403.4023.

Sincerely,



for Glenn Shankle

Executive Director

Texas Commissioner on Environmental Quality

GS/EMB/eg

Enclosures: Deed Recordation Affidavit, TNRCC-0625
Change in Responsibility for Maintenance on Permanent BMPs, TNRCC-10263

cc Mr. Stephen E. Schultz, The Schultz Group, Inc.
Mr. Michael Short, City of New Braunfels
Mr. Tom Hornseth, Comal County
Mr. Robert J. Potts, Edwards Aquifer Authority
TCEQ Central Records, Building E, MC 212

Attachment B - Narrative of Proposed Modification

The project was previously titled Tschirhart Ranch Subdivision, it has since become known as Manor Creek. The original proposed project consisted of 252.038 acres of land that was to be developed into a 343 lot residential subdivision. Each individual residential lot was to contain approximately 3,860 square feet of impervious cover which included a building structure and a concrete driveway. There was to be approximately 6,800 L.F. of street in a 60' R.O.W. The overall developed project was to consist of less than 20% impervious cover, so that structural BMP's would not be required. The permanent BMP's around the sensitive features consist of native vegetation for a minimum of 50 feet around each feature.


Unit one has been constructed and the impervious cover has exceeded the 3,860 square feet of impervious cover allowed for each lot. As a result the owner has purchased an additional 15.001 acres to keep the impervious cover for the site under 20%. The impervious cover for lots within Units 2-6 have been reconfigured to contain approximately 3,662 square feet of impervious cover for interior lots and 3,865 square feet for optional corner lots which includes all proposed typical building structures and a concrete driveway. With the addition of the 15.001 acres and a reduction of area given an existing TxDOT dedication of 0.123 acres this development will have less than 20% impervious cover; therefore, no structural BMP's are required. The 50 foot vegetative buffer around sensitive features will be maintained.

Additional Items Changed

- a. FEMA Flood Plain has been updated with the new FEMA Flood Plain maps approved September 2009
- b. The south entrance from State Hwy 46 has been adjusted in anticipation of a future TxDOT drainage structure.
- c. In Unit III Varrelman Road has been shifted slightly north.
- d. In Unit V Liermann Avenue was shifted slightly south.
- e. 15.001 Acres have been added to the original tract and a dedication of 0.123 acres to TxDOT has occurred at the Hamburg entrance. The total area for the site is now 266.916 acres.
- f. Three lots have been combined in Unit II for a future Community Center. Making the total acreage outside the Community Center 265.836 acres.

These changes have been included in the new impervious cover calculations.

Attachment C
Current Site Plan




REVISIONS	
DATE	DESCRIPTION
03/31/06	REVISED SITE FEATURES/AREAS TO BE DISTURBED.

SALES OF TEXAS
JOHN J. MOY, JR.
87835
PROFESSIONAL ENGINEER
P.E.
03/31/06


SITE PLAN OF
TSCHIRHART RANCH SUBDIVISION
NEW BRAUNFELS, TEXAS

THE Schultz Group, INC.
CONSULTING ENGINEERS & LAND SURVEYORS
2461 LOOP 337 NEW BRAUNFELS, TEXAS 78130
PHONE (830) 606-3913 FAX (830) 625-2204

DRAWN BY: D.C.
CHECKED BY: J.J.M.
DATE: DECEMBER 2005
JOB NO.: 110205
S-1



NATIVE BUFFER ZONE NOTE:
BUFFER ZONES AROUND A POINT RECHARGE FEATURE OR CLUSTER OF CONTIGUOUS POINT RECHARGE FEATURES SHALL BE MAINTAINED IN A NATURAL STATE TO THE MAXIMUM PRACTICAL EXTENT. THIS IMPLIES A CONSTRUCTION-FREE ZONE. WHEN ALL OR A PORTION OF THE BUFFER FOR A SENSITIVE FEATURE IS LOCATED WITHIN THE YARD OF A RESIDENTIAL TRACT, IT SHOULD BE SEPARATED BY A BARRIER, SUCH AS A FENCE, FROM CONVENTIONAL LANDSCAPING AND MAINTAINED IN THE NATURAL STATE. THE "NATURAL STATE" OF A BUFFER WILL TYPICALLY BE A COMBINATION OF DENSE NATIVE GRASSES, SHRUBS AND TREES.



THE AMOUNT AND TYPE OF IMPERVIOUS COVER EXPECTED AFTER CONSTRUCTION ARE SHOWN BELOW:

Impervious Cover of Proposed Project	Sq. Ft. Sq.	FL/Acre	Acre
Structures/Rooftops	1,131,900	+ 43,560 =	25.98
Street & Driveways	1,037,065	+ 43,560 =	23.81
Other paved surfaces/Drainage	21924	+ 43,560 =	0.50
Total Impervious Cover	2,190,889	+ 43,560 =	50.29
Total Impervious Cover + Total Acreage x 100 =			
19.95 %			

TOTAL SITE ACREAGE = 252.038 AC.
TOTAL NUMBER OF RESIDENTIAL LOTS = 343

**** NOTE ****
THIS SITE WILL BE USED FOR A LOW DENSITY SINGLE-FAMILY RESIDENTIAL DEVELOPMENT AND HAS 20% OR LESS IMPERVIOUS COVER. THEREFORE, NO OTHER PERMANENT BMP'S WITH SUPPORTING CALCULATIONS ARE REQUIRED / PRESENT.

- LEGEND:**
- MANMADE FEATURE (EXISTING SEWER MANHOLE)
 - GEOLOGIC FEATURE
 - 50 FT. MIN. NATURAL VEGETATIVE BUFFER ZONE AROUND SENSITIVE GEOLOGIC FEATURE w/ TEMPORARY HIGH SERVICE ROCK BERM AROUND PERIMETER
 - SILT FENCE
 - ROCK BERM
 - TEMPORARY CONSTRUCTION ENTRANCE / EXIT
 - CHANNEL IMPROVEMENTS/BRUSH CLEARING AREA TO BE DISTURBED w/ SOIL STABILIZATION WHERE ROCK IS NOT ENCOUNTERED.
 - AREAS TO BE DISTURBED (PROPOSED R.O.W.'s w/ SOIL STABILIZED PARKWAYS)
 - AREAS TO BE DISTURBED (PROPOSED CHANNEL IMPROVEMENTS w/ SOIL STABILIZATION)

Water Pollution Abatement Plan Application
for Regulated Activities
on the Edwards Aquifer Recharge Zone
and Relating to 30 TAC §213.5(b), Effective June 1, 1999

REGULATED ENTITY NAME: Manor Creek Subdivision

REGULATED ENTITY INFORMATION

1. The type of project is:
☒ Residential: # of Lots: 340
☐ Residential: # of Living Unit Equivalents: _____
☐ Commercial
☐ Industrial
☐ Other: _____
2. Total site acreage (size of property): 266.916
3. Projected population: 858
4. The amount and type of impervious cover expected after construction are shown below:

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	956,627	÷ 43,560 =	21.961
Streets & Driveways/Sidewalks	1,336,252	÷ 43,560 =	30.676
Other paved surfaces/Drainage	21,924	÷ 43,560 =	0.503
Total Impervious Cover	2,314,803	÷ 43,560 =	53.141
Total Impervious Cover ÷ Total Acreage x 100 =			19.91

5. ☒ **ATTACHMENT A - Factors Affecting Water Quality.** A description of any factors that could affect surface water and groundwater quality is provided at the end of this form.
6. ☒ Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

FOR ROAD PROJECTS ONLY N/A

Complete questions 7-12 if this application is exclusively for a road project.

7. Type of project:
N/A TXDOT road project.
N/A County road or roads built to county specifications.
N/A City thoroughfare or roads to be dedicated to a municipality.
N/A Street or road providing access to private driveways.
8. Type of pavement or road surface to be used:
N/A Concrete
N/A Asphaltic concrete pavement
N/A Other: _____

9. Length of Right of Way (R.O.W.): _____ feet.
 Width of R.O.W.: _____ feet.
 $L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$
10. Length of pavement area: _____ feet.
 Width of pavement area: _____ feet.
 $L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$
 Pavement area _____ acres \div R.O.W. area _____ acres $\times 100 = \text{_____ \%}$ impervious cover.
11. N/A A rest stop will be included in this project.
N/A A rest stop will **not** be included in this project.
12. N/A Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

STORMWATER TO BE GENERATED BY THE PROPOSED PROJECT

13. **ATTACHMENT B - Volume and Character of Stormwater.** A description of the volume and character (quality) of the stormwater runoff which is expected to occur from the proposed project is provided at the end of this form. The estimates of stormwater runoff quality and quantity should be based on area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

WASTEWATER TO BE GENERATED BY THE PROPOSED PROJECT

14. The character and volume of wastewater is shown below:
- | | |
|----------------------------|-------------------------------|
| <u>100%</u> Domestic | <u>102,900</u> gallons/day |
| <u> </u> % Industrial | <u> </u> gallons/day |
| <u> </u> % Commingled | <u> </u> gallons/day |
| TOTAL | <u>102,900</u> gallons/day |
15. Wastewater will be disposed of by:
 On-Site Sewage Facility (OSSF/Septic Tank):
ATTACHMENT C - Suitability Letter from Authorized Agent. An on-site sewage facility will be used to treat and dispose of the wastewater. The appropriate licensing authority's (authorized agent) written approval is provided at the end of this form. It states that the land is suitable for the use of an on-site sewage facility or identifies areas that are not suitable.
 Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.
- X **Sewage Collection System (Sewer Lines):**
X Private service laterals from the wastewater generating facilities will be connected to an existing SCS.
 Private service laterals from the wastewater generating facilities will be connected to a proposed SCS.
 The SCS was previously submitted on _____.
 The SCS was submitted with this application.

- ☐ The SCS will be submitted at a later date. The owner is aware that the SCS may not be installed prior to executive director approval.

The sewage collection system will convey the wastewater to the Gruene Road (name) Treatment Plant. The treatment facility is:

- ☒ existing.
☐ proposed.

16. ☒ All private service laterals will be inspected as required in 30 TAC §213.5.

SITE PLAN REQUIREMENTS

Items 17 through 27 must be included on the Site Plan.

17. The Site Plan must have a minimum scale of 1" = 400'.
Site Plan Scale: 1" = 200'.

18. 100-year floodplain boundaries
☒ Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.
☐ No part of the project site is located within the 100-year floodplain.

The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s):

Flood Insurance Rate Map – Comal County Texas, Community Panel 48091C0435F dated September 2, 2009

19. ☐ The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Show lots, recreation centers, buildings, roads, etc.
☒ The layout of the development is shown with existing contours. Finished topographic contours will not differ from the existing topographic configuration and are not shown.

20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):
☐ There are (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)
☐ The wells are not in use and have been properly abandoned.
☐ The wells are not in use and will be properly abandoned.
☐ The wells are in use and comply with 30 TAC §238.
☒ There are no wells or test holes of any kind known to exist on the project site.

21. Geologic or manmade features which are on the site:
☒ All **sensitive and possibly sensitive** geologic or manmade features identified in the Geologic Assessment are shown and labeled.
☐ No **sensitive and possibly sensitive** geologic or manmade features were identified in the Geologic Assessment.
☐ **ATTACHMENT D - Exception to the Required Geologic Assessment.** An exception to the Geologic Assessment requirement is requested and explained in ATTACHMENT D provided at the end of this form. Geologic or manmade features were found and are shown and labeled.
☐ **ATTACHMENT D - Exception to the Required Geologic Assessment.** An exception to the Geologic Assessment requirement is requested and explained in ATTACHMENT D provided at the end of this form. No geologic or manmade features were found.

22. X The drainage patterns and approximate slopes anticipated after major grading activities.
23. X Areas of soil disturbance and areas which will not be disturbed.
24. X Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
25. X Locations where soil stabilization practices are expected to occur.
26. N/A Surface waters (including wetlands).
27. X Locations where stormwater discharges to surface water or sensitive features.
— There will be no discharges to surface water or sensitive features.

ADMINISTRATIVE INFORMATION

28. X One (1) original and three ~~(3)~~ (4) copies of the completed application have been provided.
29. X Any modification of this WPAP will require TCEQ executive director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **WATER POLLUTION ABATEMENT PLAN APPLICATION FORM** is hereby submitted for TCEQ review and executive director approval. The form was prepared by:

Michael G. Short, P.E.
Print Name of Customer/Agent


Signature of Customer/Agent

2/11/10
Date

WATER POLLUTION ABATEMENT PLAN APPLICATION

5. ATTACHMENT A - Factors Affecting Water Quality.

The various facets of construction involved with this project will consist of site clearing, site grading, utility service lines, building structure, driveways, etc. for this 266.916 project site. The disturbance of the existing site during construction are factors that could affect surface water and groundwater quality. To assist in the preservation of the quality of surface water exiting the site during construction, which in turns assists in the preservation the groundwater quality, temporary pollution controls will be installed. Some possible sources of contamination during construction would be from machinery or equipment in the form of oil or fuel. Containment and cleanup is addressed in the Temporary Pollution Control section of this submittal.

13. ATTACHMENT B - Volume and Character of Stormwater.


The stormwater runoff generated from this site will consist of rooftops, concrete driveways, paved streets and landscape areas. The runoff will be of a domestic nature and may contain small amounts of oil, suspended solids, fertilizers, and household pesticides. This is a low density single family development with less than 20% impervious cover. Therefore, no structural permanent Best Management Practices are being proposed to capture a specific volume of storm water runoff. However, the sensitive features located on the site will be protected by native environment buffer zones which are shown on the Site Plan. The average Pre-Construction runoff coefficient for the site is $C_{pre} = 0.36$ and the average Post-Construction runoff coefficient is $C_{post} = 0.53$.

SITE PLAN

NATIVE BUFFER ZONE NOTE:

BUFFER ZONES AROUND A POINT RECHARGE FEATURE OR CLUSTER OF CONTIGUOUS POINT RECHARGE FEATURES SHALL BE MAINTAINED IN A NATURAL STATE TO THE MAXIMUM PRACTICAL EXTENT. THIS IMPLIES A CONSTRUCTION-FREE ZONE. WHEN ALL OR A PORTION OF THE BUFFER FOR A SENSITIVE FEATURE IS LOCATED WITHIN THE YARD OF A RESIDENTIAL TRACT, IT SHOULD BE SEPARATED BY A BARRIER, SUCH AS A FENCE, FROM CONVENTIONAL LANDSCAPING AND MAINTAINED IN THE NATURAL STATE. THE "NATURAL STATE" OF A BUFFER WILL TYPICALLY BE A COMBINATION OF DENSE NATIVE GRASSES, SHRUBS AND TREES.

SCALE IN FEET
200 100 0 200
SCALE: 1" = 200' HORIZ.



LEGEND:

- MANMADE FEATURE (EXISTING SEWER MANHOLE)
- GEOLOGIC FEATURE
- 50 FT. MIN. NATURAL VEGETATIVE BUFFER ZONE AROUND SENSITIVE GEOLOGIC FEATURE w/ TEMPORARY HIGH SERVICE ROCK BERM AROUND PERIMETER
- SILT FENCE
- ROCK BERM
- TEMPORARY CONSTRUCTION ENTRANCE / EXIT
- CHANNEL IMPROVEMENTS/BRUSH CLEARING AREA TO BE DISTURBED w/ SOIL STABILIZATION WHERE ROCK IS NOT ENCOUNTERED.
- AREAS TO BE DISTURBED (PROPOSED R.O.W.'s w/ SOIL STABILIZED PARKWAYS)
- AREAS TO BE DISTURBED (PROPOSED CHANNEL IMPROVEMENTS w/ SOIL STABILIZATION)


IMPERVIOUS COVER SUMMARY

IMPERVIOUS COVER OF PROPOSED PROJECT	SQUARE-FEET	ACRES
STRUCTURES / ROOF TOPS UNIT 1	307,314	7.055
DRIVEWAYS / SIDEWALKS UNIT 1	174,150	3.998
STRUCTURES / ROOF TOPS UNITS 2-6	649,313	14.924
DRIVEWAYS / SIDEWALKS UNITS 2-6	305,235	7.007
STREETS	856,867	19.671
OTHER PAVED SURFACES / DRAINAGE	21,924	0.503
TOTAL / IMPERVIOUS COVER	2,314,803	53.141



TOTAL SITE ACREAGE = 266.916 AC.
TOTAL IMPERVIOUS COVER + TOTAL ACREAGE = 19.91%
TOTAL NUMBER OF RESIDENTIAL LOTS = 340

** NOTE **

THIS SITE WILL BE USED FOR A LOW DENSITY SINGLE- FAMILY RESIDENTIAL DEVELOPMENT AND HAS 20% OR LESS IMPERVIOUS COVER. THEREFORE, NO OTHER PERMANENT BMP'S WITH SUPPORTING CALCULATIONS ARE REQUIRED / PRESENT.



- NOTE:
- TOTAL IMPERVIOUS COVER FOR UNIT 1 SHALL NOT EXCEED 481,464 SF FOR ALL 81 LOTS.
 - IMPERVIOUS COVER CALCULATED TO THE BACK OF CURB AND INCLUDES THE TYPICAL DRIVEWAY AND SIDEWALKS.
 - TOTAL IMPERVIOUS COVER FOR UNIT 2-6 SHALL NOT EXCEED 954,548 SF FOR ALL 259 LOTS (30 CORNER LOTS, 229 INTERIOR LOTS)



REVISIONS

DESCRIPTION

DATE

SITE PLAN

OF

MANOR CREEK SUBDIVISION
NEW BRAUNFELS, TEXAS

THE **Schultz Group, INC.**
CONSULTING ENGINEERS & LAND SURVEYORS
2461 LOOP 337 NEW BRAUNFELS, TEXAS 78130
PHONE (830) 606-3913 FAX (830) 625-2204

DRAWN BY: D.C.
CHECKED BY: M.G.S.
DATE: NOVEMBER 2009
JOB NO.: 110109

S-1

Temporary Stormwater Section
for Regulated Activities
on the Edwards Aquifer Recharge Zone
and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

REGULATED ENTITY NAME: Manor Creek Subdivision

POTENTIAL SOURCES OF CONTAMINATION

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:
 - ☐ Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.
 - ☐ Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
 - ☐ Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An **Aboveground Storage Tank Facility Plan** application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
 - ☒ Fuels and hazardous substances will not be stored on-site.
2. ☒ **ATTACHMENT A - Spill Response Actions.** A description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is provided at the end of this form.
3. ☒ Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
4. ☒ **ATTACHMENT B - Potential Sources of Contamination.** Describe in an attachment at the end of this form any other activities or processes which may be a potential source of contamination.
 - ☐ There are no other potential sources of contamination.

SEQUENCE OF CONSTRUCTION

5. ☒ **ATTACHMENT C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is provided at the end of this form. For each activity described, an estimate of the total area of the site to be disturbed by each activity is given.
6. ☒ Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: **Bleiders Creek**

TEMPORARY BEST MANAGEMENT PRACTICES (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. **All structural BMPs must be shown on the site plan.**

7. X **ATTACHMENT D - Temporary Best Management Practices and Measures.** A description of the TBMPs and measures that will be used during and after construction are provided at the end of this form. For each activity listed in the sequence of construction, include appropriate control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- X TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information has been provided in the attachment at the end of this form
- a. A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
 - b. A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
 - c. A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
 - d. A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- N/A **ATTACHMENT E - Request to Temporarily Seal a Feature.** A request to temporarily seal a feature is provided at the end of this form. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
- X There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. X **ATTACHMENT F - Structural Practices.** Describe the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site. Placement of structural practices in floodplains has been avoided.
10. X **ATTACHMENT G - Drainage Area Map.** A drainage area map is provided at the end of this form to support the following requirements.

- ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
- ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
- ☒ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
- ☐ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

11. N/A **ATTACHMENT H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure has been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are provided as at the end of this form.
12. X **ATTACHMENT I - Inspection and Maintenance for BMPs.** A plan for the inspection of temporary BMPs and measures and for their timely maintenance, repair, and, if necessary, retrofit is provided at the end of this form. A description of documentation procedures and recordkeeping practices is included in the plan.
13. X All control measures must be properly selected, installed, and maintained in accordance with the manufacturers specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicates a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. X If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. X Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. X Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

SOIL STABILIZATION PRACTICES

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. X **ATTACHMENT J - Schedule of Interim and Permanent Soil Stabilization Practices.** A schedule of the interim and permanent soil stabilization practices for the site is attached at the end of this form.
18. X Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19. X Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

ADMINISTRATIVE INFORMATION

20. X All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21. X If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22. X Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.


To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **TEMPORARY STORMWATER SECTION** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Michael G. Short, P.E.

Print Name of Customer/Agent



Signature of Customer/Agent



Date

TEMPORARY STORMWATER SECTION

2. ATTACHMENT A -Spill Response Actions.

The following includes a copy of Section 1.4.16 of the TCEQ "Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices" Pages 1-118 through 1-121, Spill Prevention and Control. The following is made part of the spill response action plan. In addition in the event of a significant hazardous spill the contractor or construction personnel shall notify TCEQ by telephone as soon as possible and within 24-hours at (512)339-2929 (Austin) or (210)490-3096 (San Antonio) between 8 am and 5 pm or after hours contact the Environmental Release Hotline at 1-800-832-8224. The contractor shall have available at the construction site all emergency numbers to include the Edwards Aquifer Authority (210) 222-2204 or 1-800-292-1047 and the National Response Center (202) 267-2675 or 1-800-424-8802.

4. ATTACHMENT B -Potential Sources of Contamination.

There is a potential for contamination as result of servicing and operating construction equipment (oil, gas, etc), from construction materials (concrete, etc), and from portable toilet facilities.

5. ATTACHMENT C - Sequence of Major Activities.

The following is a sequence of major activities which will involve soil disturbance along with an estimate of the area of the site to be disturbed by each activity:

Sequence No.	Description of Soil Disturbing Activity	Estimated Area to be Disturbed by each Activity (Acres) (Total)
1	Clearing and Grubbing (Street/Drainage)	47
2	Excavation and Grading (Streets/Drainage)	47
3	Underground Utility Service Installation	30
4	Final Structures Installation (Including Houses & Driveways)	31

7. ATTACHMENT D - Temporary Best Management Practices and Measures.

The Temporary Best Management Practices (TBMP) that will be used for this project are silt fences, rock berms, high service rock berms and a temporary construction entrance/exit. The temporary controls will be installed prior to construction and shall be maintained during construction by the contractor. The controls shall be removed by the contractor when vegetation is established and the construction area is stabilized.



RG-348
Revised July 2005

Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices

printed on
recycled paper

Field Operations Division

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

1.4.16 Spill Prevention and Control

The objective of this section is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees.

The following steps will help reduce the stormwater impacts of leaks and spills:

Education

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a “significant spill” is for each material they use, and what is the appropriate response for “significant” and “insignificant” spills. Employees should also be aware of when spill must be reported to the TCEQ. Information available in 30 TAC 327.4 and 40 CFR 302.4.
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor’s superintendent or representative oversee and enforce proper spill prevention and control measures.

General Measures

- (1) To the extent that the work can be accomplished safely, spills of oil, petroleum products, substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.
- (6) Spills should be covered and protected from stormwater runoff during rainfall to the extent that it doesn’t compromise clean up activities.
- (7) Do not bury or wash spills with water.

- (8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.
- (9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.
- (10) Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.
- (11) Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.
- (12) Keep waste storage areas clean, well organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

Cleanup

- (1) Clean up leaks and spills immediately.
- (2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.
- (3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

Minor Spills

- (1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.
- (2) Use absorbent materials on small spills rather than hosing down or burying the spill.
- (3) Absorbent materials should be promptly removed and disposed of properly.
- (4) Follow the practice below for a minor spill:
- (5) Contain the spread of the spill.
- (6) Recover spilled materials.
- (7) Clean the contaminated area and properly dispose of contaminated materials.

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman immediately.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities:

- (1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
- (2) For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110, 119, and 302, the contractor should notify the National Response Center at (800) 424-8802.
- (3) Notification should first be made by telephone and followed up with a written report.
- (4) The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.
- (5) Other agencies which may need to be consulted include, but are not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc.

More information on spill rules and appropriate responses is available on the TCEQ website at: http://www.tnrc.state.tx.us/enforcement/emergency_response.html

Vehicle and Equipment Maintenance

- (1) If maintenance must occur onsite, use a designated area and a secondary containment, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.
- (2) Regularly inspect onsite vehicles and equipment for leaks and repair immediately.
- (3) Check incoming vehicles and equipment (including delivery trucks, and employee and subcontractor vehicles) for leaking oil and fluids. Do not allow leaking vehicles or equipment onsite.
- (4) Always use secondary containment, such as a drain pan or drop cloth, to catch spills or leaks when removing or changing fluids.
- (5) Place drip pans or absorbent materials under paving equipment when not in use.
- (6) Use absorbent materials on small spills rather than hosing down or burying the spill. Remove the absorbent materials promptly and dispose of properly.
- (7) Promptly transfer used fluids to the proper waste or recycling drums. Don't leave full drip pans or other open containers lying around.
- (8) Oil filters disposed of in trashcans or dumpsters can leak oil and pollute stormwater. Place the oil filter in a funnel over a waste oil-recycling drum to drain excess oil before disposal. Oil filters can also be recycled. Ask the oil supplier or recycler about recycling oil filters.
- (9) Store cracked batteries in a non-leaking secondary container. Do this with all cracked batteries even if you think all the acid has drained out. If you drop a battery, treat it as if it is cracked. Put it into the containment area until you are sure it is not leaking.

Vehicle and Equipment Fueling

- (1) If fueling must occur on site, use designated areas, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.
- (2) Discourage "topping off" of fuel tanks.
- (3) Always use secondary containment, such as a drain pan, when fueling to catch spills/ leaks.

utility construction, silt fences shall be installed down gradient of all proposed home building and driveway construction operations to contain any sediment from leaving the individual lots. The temporary construction entrance/exit shall be adjusted/relocated prior to the construction of each new unit of development and will be removed just prior to final pavement placement.

- a. Stormwater that is flowing upstream of the project limits in the Bleider's Creek will continue to pass through the project limits in its current manner. All other stormwater that originates upgradient of the project site will be allowed to enter the property limits but will then be directed around the disturbed areas via interceptor swales in association with each unit of construction. The stormwater runoff will be conveyed via these swales that will be cut around the perimeter of the site and rock berms will be installed in these swales to control the sediment from the disturbed areas. The rock berms will slow the velocity of the water down and the sediment will settle out. It will be the contractors responsibility to remove the sediment that builds up after significant rainfall events. The swales will be vegetated/landscaped in the final conditions of the site.
- b. Stormwater that originates on-site will be filtered by silt fences and/or rock berms on the downgradient side of the property. The silt fences and rock berms will slow the velocity of the water down and the sediment will settle out. It will be the contractors responsibility to remove the sediment that builds up after significant rainfall events. There will be no contaminated/polluted runoff coming off this site other than sediment which will be handled with silt fence, rock berms and the temporary construction entrance/exit.
- c. Stormwater runoff that originates on-site and upgradient of the site will be filtered by silt fences and rock berms on the downgradient side of the property. The silt fences and rock berms will slow the velocity of the water down and the sediment will settle out. It will be the contractors responsibility to remove the sediment that builds up after significant rainfall events. The silt fences and rock berms will capture the sediment that would otherwise be conveyed to streams, sensitive features, etc.
- d. There were eleven sensitive features located on the site. These features are S-15, 21, 25, 35, 61, 63, 70, 71, 81, 85 and 89. The majority of these sensitive features are located along the banks of very defined natural channels with drainage areas greater than 1.6 acres. The predominant recharge of these features appears to be the natural water way that drains to these locations with limited drainage contributing via sheet flow. There will be a 50 ft. native environment buffer zone around each sensitive feature and each will be protected during construction by the installation of high service rock berms around the 50' perimeter. There are no sensitive features being proposed to be sealed and the non-sensitive features are either located in the proposed yards of platted lots which will be covered by topsoil and grass or they will be covered by concrete (house pad/driveway).

9. ATTACHMENT F - Structural Practices.

The structural practices that will be used for temporary control of erosion/sediment on this site are silt fences, rock berms, high service rock berms and a temporary construction entrance/exit. Interceptor swales will be excavated around the sides of the property that will prevent upgradient runoff from flowing across the disturbed areas. These swales will outfall to areas that are controlled with by rock berms and the runoff will be filtered before leaving the property. These minor swales will be excavated to the extent that the stormwater will not enter disturbed areas during construction.

10. ATTACHMENT G - Drainage Area Map.

The drainage area map has been enclosed and is located at the end of this section.

12. ATTACHMENT I - Inspection and Maintenance for BMP's.

Silt Fence Inspection and Maintenance Guidelines:

- a. Inspect all fencing weekly, and after any rainfall.
- b. Remove sediment when buildup reaches 6 inches, or install a second line of fencing parallel to the old fence.
- c. Replace any torn fabric or install a second line of fencing parallel to the torn section.
- d. Replace or repair any sections crushed or collapsed in the course of construction activity. If a section of fence is obstructing vehicular access, relocate it to a spot where it will provide equal protection, but will not obstruct vehicles.

Rock Berm Inspection and Maintenance Guidelines:

- a. Inspection shall be made weekly and after each rainfall by the contractor.
- b. Remove sediment and other debris when buildup reaches 6 inches and dispose of the accumulated silt in an approved site and in such a manner as to not contribute to additional siltation.
- c. Repair any loose wire sheathing.
- d. The berm shall be reshaped as needed during inspection.
- e. The berm shall be replaced when the structure ceases to function as intended due to silt accumulation among the rocks, washout, construction traffic damage, etc.
- f. The rock berm shall be left in place until all upstream areas are stabilized and accumulated silt removed.

High Service Rock Berm Inspection and Maintenance Guidelines:

- a. Inspection shall be made weekly and after each rainfall by the contractor.
- b. Remove sediment and other debris when buildup reaches 6 inches and dispose of the accumulated silt in an approved site and in such a manner as to not contribute to additional siltation.
- c. Repair any loose wire sheathing.
- d. The berm shall be reshaped as needed during inspection.
- e. The berm shall be replaced when the structure ceases to function as intended due to silt accumulation among the rocks, washout, construction traffic damage, etc.
- f. The rock berm shall be left in place until all upstream areas are stabilized and accumulated silt removed.

Temporary Construction Entrance/Exit:

- a. The entrance shall be maintained in a condition, which will prevent tracking or flowing of sediment onto public rights-of-way.
- b. All sediment spilled, dropped, washed or tracked on to public rights-of-way shall be removed immediately by the contractor.
- c. When necessary, wheels shall be cleaned to remove sediment prior to entrance onto public right-of-way.
- d. When washing is required, it shall be done on an area stabilized with crushed stone that drains into an approved sediment trap or sediment basin.
- e. All sediment shall be prevented from entering any storm drain, ditch or water course by using approved methods.

TEMPORARY CONSTRUCTION ENTRANCE/EXIT
INSPECTION FORM

GENERAL NOTES

1. STONE SIZE - 4 TO 8 INCHES CRUSHED ROCK.
2. LENGTH - AS EFFECTIVE, BUT NOT LESS THAN 50 FEET.
3. THICKNESS - NOT LESS THAN 8 INCHES.
4. WIDTH - NOT LESS THAN 12 FEET.
5. WASHING - WHEN NECESSARY, WHEELS SHALL BE CLEANED TO REMOVE SEDIMENT PRIOR TO ENTRANCE ONTO PUBLIC ROADWAY. WHEN WASHING IS REQUIRED, IT SHALL BE DONE SO THAT NO SEDIMENT LEAVES THE SITE. ALL UNFILTERED SEDIMENT SHALL BE PREVENTED FROM ENTERING ANY STORM DRAIN, DITCH OR WATERCOURSE.
6. MAINTENANCE - THE ENTRANCE SHALL BE MAINTAINED IN CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC ROADWAYS. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND, AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC ROADWAY MUST BE REMOVED IMMEDIATELY.
7. DRAINAGE - ENTRANCE MUST BE PROPERLY GRADED TO PREVENT RUNOFF FROM LEAVING THE CONSTRUCTION SITE.

INSPECTION REPORT

DATE: _____

SIGNATURE: _____

DOES MUCH SEDIMENT GET TRACKED ONTO ROAD?	IS THE GRAVEL CLEAN OR IS IT FILLED WITH SEDIMENT?	DOES ALL TRAFFIC USE THE STABILIZED ENTRANCE TO LEAVE THE SITE?

MAINTENANCE REQUIRED FOR STABILIZED CONSTRUCTION ENTRANCE:

TO BE PERFORMED BY: _____ ON OR BEFORE: _____

SILT FENCE
INSPECTION FORM

GENERAL NOTES

1. STEEL POSTS WHICH SUPPORT THE SILT FENCE SHALL BE INSTALLED ON A SLIGHT ANGLE TOWARD THE ANTICIPATED RUNOFF SOURCE. POST MUST BE EMBEDDED A MINIMUM OF ONE FOOT DEEP AND SPACED NOT MORE THAN 8 FEET ON CENTER. WHERE WATER CONCENTRATES, THE MAXIMUM SPACING SHOULD BE 6 FEET.
2. THE TOE OF THE SILT FENCE SHALL BE TRENCHED IN WITH A SPADE OR MECHANICAL TRENCHER, SO THAT THE DOWNSLOPE FACE OF THE TRENCH IS FLAT AND PERPENDICULAR TO THE LINE OF FLOW. WHERE FENCE CANNOT BE TRENCHED IN (E.G., PAVEMENT), WEIGHT FABRIC FLAP WITH WASHED GRAVEL ON UPHILL SIDE TO PREVENT FLOW UNDER FENCE.
3. THE TRENCH MUST BE A MINIMUM OF 6 INCHES DEEP AND 6 INCHES WIDE TO ALLOW FOR THE SILT FENCE FABRIC TO BE LAID IN THE GROUND AND BACKFILLED AND COMPACTED.
4. SILT FENCE SHOULD BE SECURELY FASTENED TO EACH STEEL SUPPORT POST AND TO WOVEN WIRE, WHICH IN TURN ATTACHED TO THE STEEL FENCE POST. THERE SHALL BE A 3 FOOT DOUBLE OVERLAP, SECURELY FASTENED WHERE ENDS OF FABRIC MEET.
5. SILT FENCE SHALL BE REMOVED WHEN THE SITE IS COMPLETELY STABILIZED SO AS NOT TO BLOCK OR IMPEDE STORM FLOW OR DRAINAGE.
6. ACCUMULATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF 6 INCHES. THE SILT SHALL BE DISPOSED OF IN AN APPROVED SITE AND IN SUCH A MANNER AS TO NOT CONTRIBUTE TO ADDITIONAL SILTATION.

INSPECTION REPORT

DATE: _____

SIGNATURE: _____

IS THE BOTTOM OF THE FABRIC STILL BURIED ?	IS THE FABRIC TORN OR SAGGING ?	ARE THE POSTS TIPPED OVER ?	HOW DEEP IS THE SEDIMENT?

MAINTENANCE REQUIRED FOR SILT FENCE:

TO BE PERFORMED BY: _____ ON OR BEFORE: _____

ROCK BERMS
INSPECTION FORM

GENERAL NOTES:

1. WOVEN WIRE SHEATHING SHALL BE PERPENDICULAR TO THE FLOW LINE AND THE SHEATHING SHALL BE 20 GAUGE WOVEN WIRE MESH WITH 1 INCH OPENINGS.
2. BERM SHALL HAVE A TOP WIDTH OF 2 FEET MINIMUM WITH SIDE SLOPES BEING 2:1 (H:V) OR FLATTER.
3. PLACEMENT OF THE ROCK ALONG THE SHEATHING SHALL NOT BE LESS THAN 18 INCHES.
4. THE WIRE SHEATHING SHALL BE WRAPPED AROUND THE ROCK AND SECURED WITH TIE WIRE SO THAT THE ENDS OF THE SHEATHING OVERLAP AT LEAST 2 INCHES, AND THE BERM RETAINS ITS SHAPE WHEN WALKED UPON.

BERM SHALL BE BUILT ALONG THE CONTOUR AT ZERO PERCENT GRADE OR AS NEAR AS POSSIBLE.

THE ENDS OF THE BERM SHALL BE TIED INTO EXISTING UPSLOPE GRADE AND THE BERM SHALL BE BURIED IN A TRENCH APPROXIMATELY 3 TO 4 INCHES DEEP TO PREVENT FAILURE OF THE CONTROL.

INSPECTION REPORT

DATE: _____

SIGNATURE: _____

IS THE BERM A MINIMUM OF 18 INCHES HIGH ?	IS LEVEL OF SILT GREATER THAN 6 INCHES DEEP?

MAINTENANCE REQUIRED FOR ROCK BERMS:

TO BE PERFORMED BY: _____ ON OR BEFORE: _____

HIGH SERVICE ROCK BERMS
INSPECTION FORM

GENERAL NOTES:

1. WOVEN WIRE SHEATHING SHALL BE PERPENDICULAR TO THE FLOW LINE AND THE SHEATHING SHALL BE 20 GAUGE WOVEN WIRE MESH WITH 1 INCH OPENINGS.
2. BERM SHALL HAVE A TOP WIDTH OF 2 FEET MINIMUM WITH SIDE SLOPES BEING 2:1 (H:V) OR FLATTER.
3. PLACEMENT OF THE ROCK ALONG THE SHEATHING SHALL NOT BE LESS THAN 18 INCHES.
4. THE WIRE SHEATHING SHALL BE WRAPPED AROUND THE ROCK AND SECURED WITH TIE WIRE SO THAT THE ENDS OF THE SHEATHING OVERLAP AT LEAST 2 INCHES, AND THE BERM RETAINS ITS SHAPE WHEN WALKED UPON.

BERM SHALL BE BUILT ALONG THE CONTOUR AT ZERO PERCENT GRADE OR AS NEAR AS POSSIBLE.

THE ENDS OF THE BERM SHALL BE TIED INTO EXISTING UPSLOPE GRADE AND THE BERM SHALL BE BURIED IN A TRENCH APPROXIMATELY 3 TO 4 INCHES DEEP TO PREVENT FAILURE OF THE CONTROL.

INSPECTION REPORT

DATE: _____

SIGNATURE: _____

IS THE BERM A MINIMUM OF 24 INCHES HIGH ?	IS LEVEL OF SILT GREATER THAN 6 INCHES DEEP?

MAINTENANCE REQUIRED FOR HIGH SERVICE ROCK BERMS:

TO BE PERFORMED BY: _____ ON OR BEFORE: _____

17. ATTACHMENT J - Schedule of Interim and Permanent Soil Stabilization Practices.


Temporary Stabilization - No bare ground exposed during construction will be left to stabilize naturally. In any disturbed area where construction activities have ceased, permanently or temporarily, the contractor shall initiate temporary stabilization of the area by the use of seeding and mulching within 14 days, except in areas where construction activities are scheduled to resume within 21 days. The temporary seeding will consist of Green Sprangletop, Buffalo Grass, and Bermuda Grass with straw or cedar mulch applied on final layer in accordance with TxDOT Item 164- Seeding for Erosion Control. Depending on the growing season at the time of construction, mixture and application rates may be modified by the engineer.

Permanent Stabilization - Disturbed portions of the site where construction activities permanently cease shall be stabilized with permanent seed no later than 14 days after the last construction activity. The permanent seed mix shall consist of Green Sprangletop, Buffalo Grass, and Bermuda Grass with straw or cedar mulch applied on final layer in accordance with TxDOT Item 164 - Seeding for Erosion Control. Depending on the growing season at the time of construction, mixture and application rates may be modified by the engineer. It shall be the contractors responsibility to provide watering bi-weekly for the seeded areas for a period of 30 calendar days.

ATTACHMENT G

MASTER DRAINAGE AREA MAP

File Name: F:\110109\110109.dwg



ADDED AREA WILL
REMAIN AS OPEN SPACE
NO DRAINAGE IMPACT.

SCALE IN FEET
600 300 0 300 600
SCALE: 1" = 600'

LEGEND

- OVERALL DRAINAGE AREA BOUNDARY
- - - SUB-AREA DRAINAGE BOUNDARY
- (A) DRAINAGE AREA DESIGNATION
- [1] DRAINAGE NODE POINT
- DIRECTION OF FLOW

DRAINAGE AREA DESIGNATION	AREA (ACRES)	AREA (MILES ²)
A	992.3	1.550
B	175.7	0.275
C	82.9	0.130
D	134.3	0.210
E	177.7	0.278
F	158.2	0.247

SCS UNIT HYDROGRAPH TYPE III DISTRIB. AMC II (DEVELOPED CONDITIONS)

DRAINAGE NODE POINT	CONTRIBUTING D.A.'s	TOTAL AREA (ACRES)	CN	TIME OF CONCENTRATION (min.)	Q ₁₀ (cfs)	Q ₂₅ (cfs)	Q ₁₀₀ (cfs)
1	A	992.3	86	49	2399.2	3167.0	4582.4
2	B	175.7	86	17	672.9	886.3	1278.6
3	A+B+C	1250.9	86	52	2930.8	3865.2	5585.1
4	A+B+C+D	1385.2	86	57	3081.0	4062.8	5870.2
5	A+B+C+D+E	1562.9	86	63	3271.9	4316.0	6238.3
6	A+B+C+D+E+F	1721.1	86	69	3421.4	4520.9	6546.3

NOTES:

- NODE POINTS [1] & [2] ARE LOCATED ON THE UPSTREAM END OF THE CULVERTS BELOW S.H. 46.
- NODE POINTS [3], [4], [5] & [6] ARE CONFLUENCE POINTS OF CONTRIBUTING DRAINAGE AREAS ALONG BLIEDERS CREEK.

OVERALL DRAINAGE INFORMATION AND
CALCULATIONS OBTAINED FROM PREVIOUSLY
APPROVED TSCHIRHART RANCH SUBDIVISION
(SGI 2005)

REVISIONS	DESCRIPTION
DATE	



MASTER DRAINAGE AREA MAP OF MANOR CREEK SUBDIVISION NEW BRAUNFELS, TEXAS

THE Schultz Group, INC.
CONSULTING ENGINEERS & LAND SURVEYORS
2461 LOOP 337 NEW BRAUNFELS, TEXAS 78130
PHONE (830) 606-3913 FAX (830) 625-2204

DRAWN BY: D.C./M.H.
CHECKED BY: S.S.
DATE: FEBRUARY 2010
JOB NO.: 110109

Permanent Stormwater Section
for Regulated Activities
on the Edwards Aquifer Recharge Zone
and Relating to 30 TAC §213.5(b)(4)(C), (D)(li), (E), and (5), Effective June 1, 1999

REGULATED ENTITY NAME: Manor Creek Subdivision

Permanent best management practices (BMPs) and measures that will be used during and after construction is completed.

1. N/A Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
2. N/A These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
 - The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
 - A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is provided below
3. N/A Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
4. X Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
 - X This site will be used for low density single-family residential development and has 20% or less impervious cover.
 - N/A This site will be used for low density single-family residential development but has more than 20% impervious cover.
 - N/A This site will not be used for low density single-family residential development.
5. N/A The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described

in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

N/A **ATTACHMENT A - 20% or Less Impervious Cover Waiver.** This site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is found at the end of this form.

N/A This site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.

N/A This site will not be used for multi-family residential developments, schools, or small business sites.

6. **ATTACHMENT B - BMPs for Upgradient Stormwater.**

N/A A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is identified as **ATTACHMENT B** at the end of this form.

N/A If no surface water, groundwater or stormwater originates upgradient from the site and flows across the site, an explanation is provided as **ATTACHMENT B** at the end of this form.

X If permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, an explanation is provided as **ATTACHMENT B** at the end of this form.

7. **ATTACHMENT C - BMPs for On-site Stormwater.**

N/A A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is identified as **ATTACHMENT C** at the end of this form.

X If permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, an explanation is provided as **ATTACHMENT C** at the end of this form.

8. X **ATTACHMENT D - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is provided at the end of this form. Each feature identified in the Geologic Assessment as "sensitive" or "possibly sensitive" has been addressed.

9. X The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.

X The permanent sealing of or diversion of flow from a naturally-occurring "sensitive" or "possibly sensitive" feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed for any naturally-occurring "sensitive" or "possibly sensitive" features on this site.

N/A **ATTACHMENT E - Request to Seal Features.** A request to seal a naturally-

occurring "sensitive" or "possibly sensitive" feature, that includes a justification as to why no reasonable and practicable alternative exists, is found at the end of this form. A request and justification has been provided for each feature.

10. N/A **ATTACHMENT F - Construction Plans.** Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information have been signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed permanent BMPs and measures are provided at the end of this form. Design Calculations, TCEQ Construction Notes, all man-made or naturally occurring geologic features, all proposed structural measures, and appropriate details must be shown on the construction plans.
11. N/A **ATTACHMENT G - Inspection, Maintenance, Repair and Retrofit Plan.** A plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is provided at the end of this form. The plan has been prepared and certified by the engineer designing the permanent BMPs and measures. The plan has been signed by the owner or responsible party. The plan includes procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofits as well as a discussion of record keeping procedures.
12. N/A The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
N/A Pilot-scale field testing (including water quality monitoring) may be required for BMPs that are not contained in technical guidance recognized by or prepared by the executive director.
— **ATTACHMENT H - Pilot-Scale Field Testing Plan.** A plan for pilot-scale field testing is provided at the end of this form.
13. N/A **ATTACHMENT I - Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is provided at the end of this form. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity which increase erosion that results in water quality degradation.

Responsibility for maintenance of permanent BMPs and measures after construction is complete.

14. X The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
15. N/A A copy of the transfer of responsibility must be filed with the executive director at the

appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **PERMANENT STORMWATER SECTION** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Michael G. Short, P.E.

Print Name of Customer/Agent



Signature of Customer/Agent

2/11/10

Date

EXEMPTION FROM PERMANENT BMP'S NOTIFICATION

Due to this site containing less than 20% impervious cover, other permanent BMP's are not required. If the percent impervious cover increases above 20% or land use changes, the exemption of the whole site as described in the property boundaries required by 30 TAC 213.4(g)(relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

PERMANENT STORMWATER SECTION

6. ATTACHMENT B - BMP's for Upgradient Stormwater.

Permanent BMP's or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site because this stormwater consists primarily of runoff from surrounding properties that are adjacent to the project site and are of different ownership. Interceptor swales are being proposed just inside the property lines to bypass the upgradient flow and these swales will be vegetated upon completion of the site.

7. ATTACHMENT C - BMP's for On-Site Stormwater.

There are no permanent BMP's required for this project site due to the total impervious cover being less than 20% of the total project site. However, 50 ft. native environment buffer zones have been shown around all sensitive features and this can be found on the Site Plan in the Water Pollution Abatement Plan section of this report. Temporary BMP's will be installed downstream of all stormwater that will flow over the exposed areas during construction. These temporary BMP's can also be found on the Site Plan previously mentioned.

8. ATTACHMENT D - BMP's for Surface Streams.

The proposed Temporary BMP's for this site will consist of silt fence, rock berms, high service rock berms and temporary construction entrance/exit. Due to this site having less than 20% impervious cover; no other permanent BMP's are required. However, 50 ft. native environment buffer zones have been shown around all sensitive features and this can be found on the Site Plan in the Water Pollution Abatement Plan section of this report. The sensitive features are: Features S-15, 21, 25, 35, 61, 63, 70, 71, 81, 85 and S-89.

Agent Authorization Form
For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

Richard N. Maier

Print Name

Title - Owner/President/Other Assistant Secretary of

Continental Homes of Texas, L.P., a Texas limited partnership

Corporation/Partnership/Entity Name

have authorized Michael G. Short, P.E.

Print Name of Agent/Engineer

of The Schultz Group, Inc.

Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For applicants who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.

4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.

by Richard M. Mace 12/1/09
Applicant's Signature r. p. Date

THE STATE OF Texas §

County of Texas §

BEFORE ME, the undersigned authority, on this day personally appeared Richard M. Mace known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 1 day of December, 2009.



Katrina McDonald
NOTARY PUBLIC

Katrina McDonald
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 8/10/13

Texas Commission on Environmental Quality
Edwards Aquifer Protection Program
Application Fee Form

NAME OF PROPOSED REGULATED ENTITY: Manor Creek Subdivision
REGULATED ENTITY LOCATION: Approx. 2 miles West from Loop 337 on the NE side of SH 46
NAME OF CUSTOMER: Continental Homes of Texas, L.P.
CONTACT PERSON: Michael G. Short, P.E. PHONE: (830) 606-3913
(Please Print)

Customer Reference Number (if issued): CN 601213523 (nine digits)
Regulated Entity Reference Number (if issued): RN 104801568 (nine digits)

Austin Regional Office (3373) ☐ Hays ☐ Travis ☐ Williamson
San Antonio Regional Office (3362) ☒ Bexar ☐ Comal ☐ Medina ☐ Kinney ☐ Uvalde

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to (Check One):

<input type="checkbox"/> Austin Regional Office	<input checked="" type="checkbox"/> San Antonio Regional Office
<input type="checkbox"/> Mailed to TCEQ: TCEQ – Cashier Revenues Section Mail Code 214 P.O. Box 13088 Austin, TX 78711-3088	<input type="checkbox"/> Overnight Delivery to TCEQ: TCEQ - Cashier 12100 Park 35 Circle Building A, 3rd Floor Austin, TX 78753 512/239-0347

Site Location (Check All That Apply): ☒ Recharge Zone ☐ Contributing Zone ☐ Transition Zone

Type of Plan	Size	Fee Due
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	266.916	\$8,000.00
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	Acres	\$
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$


Signature

2/12/10
Date

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282.

Texas Commission on Environmental Quality
 Edwards Aquifer Protection Program
Application Fee Schedule
 30 TAC Chapter 213 (effective 05/01/2008)

**Water Pollution Abatement Plans and Modifications
 Contributing Zone Plans and Modifications**

PROJECT	PROJECT AREA IN ACRES	FEE
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

PROJECT	COST PER LINEAR FOOT	MINIMUM FEE MAXIMUM FEE
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

PROJECT	COST PER TANK OR PIPING SYSTEM	MINIMUM FEE MAXIMUM FEE
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

PROJECT	FEE
Exception Request	\$500

Extension of Time Requests

PROJECT	FEE
Extension of Time Request	\$150

Check Number

0230598

Date

02/09/10

Texas Commission on Environmental Qua

14250 Judson Road

DRH Inc. Texas Disb Account

Stub 1 of 1

1382697

PO Numb	Invoice Number	Subdv Lot#	Lot Address	Cost Cde	Legal Desc	Gross	Deductions	Amount Paid
2/4/20103	42552		Manor Creek 6			8,000.00		8,000.00
						8,000.00		8,000.00

Check Number

0230598

Date

02/09/10

Texas Commission on Environmental Qua

14250 Judson Road

DRH Inc. Texas Disb Account

Stub 1 of 1

1382697

PO Numb	Invoice Number	Subdv Lot#	Lot Address	Cost Cde	Legal Desc	Gross	Deductions	Amount Paid
2/4/20108	42552		Manor Creek 6			8,000.00		8,000.00
						8,000.00		8,000.00

THIS CHECK IS PRINTED IN RED AND BLUE INK ON THE FACE ON CHEMICAL AND BLEACH REACTIVE PAPER WITH INVISIBLE FLUORESCENT FIBERS AND BASKETWEAVE ON BACK MP

Controlled Disbursement

Bank of America, N.A.

Atlanta, Dekalb County, Georgia

64-1278

611 GA

Check Number

230598

DRH Inc. Texas Disb Account

01 Commerce Street, Suite 500

Fort Worth, TX 76102

1382697

Date

Amount

02/09/10

\$*****8,000.00

Void after 6 months from date of issue

Pay EIGHT THOUSAND AND 00/100 *****

To The Order Of:

Texas Commission on Environmental Qua
14250 Judson Road
San Antonio TX 78233-4480

D. L. Horton



TCEQ Use Only

TCEQ Core Data Form

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided)			
<input type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application)			
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)		<input checked="" type="checkbox"/> Other	WPAP Modification
2. Attachments Describe Any Attachments: (ex. Title V Application, Waste Transporter Application, etc.)			
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Manor Creek Subdivision			
3. Customer Reference Number (if issued)		4. Regulated Entity Reference Number (if issued)	
CN 601213523		RN 104801568	

SECTION II: Customer Information

5. Effective Date for Customer Information Updates (mm/dd/yyyy)			
6. Customer Role (Proposed or Actual) – as it relates to the <u>Regulated Entity</u> listed on this form. Please check only <u>one</u> of the following:			
<input type="checkbox"/> Owner	<input type="checkbox"/> Operator	<input checked="" type="checkbox"/> Owner & Operator	
<input type="checkbox"/> Occupational Licensee	<input type="checkbox"/> Responsible Party	<input type="checkbox"/> Voluntary Cleanup Applicant	<input type="checkbox"/> Other: _____
7. General Customer Information			
<input type="checkbox"/> New Customer		<input type="checkbox"/> Update to Customer Information	<input type="checkbox"/> Change in Regulated Entity Ownership
<input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State)		<input checked="" type="checkbox"/> No Change**	
**If "No Change" and Section I is complete, skip to Section III – Regulated Entity Information.			
8. Type of Customer:			
<input type="checkbox"/> Corporation	<input type="checkbox"/> Individual	<input type="checkbox"/> Sole Proprietorship- D.B.A	
<input type="checkbox"/> City Government	<input type="checkbox"/> County Government	<input type="checkbox"/> Federal Government	<input type="checkbox"/> State Government
<input type="checkbox"/> Other Government	<input type="checkbox"/> General Partnership	<input type="checkbox"/> Limited Partnership	<input type="checkbox"/> Other: _____
9. Customer Legal Name (If an individual, print last name first: ex: Doe, John) <u>If new Customer, enter previous Customer below</u> <u>End Date:</u>			
10. Mailing Address:			
City		State	ZIP
			ZIP + 4
11. Country Mailing Information (if outside USA)		12. E-Mail Address (if applicable)	
13. Telephone Number		14. Extension or Code	15. Fax Number (if applicable)
() -			() -
16. Federal Tax ID (9 digits)	17. TX State Franchise Tax ID (11 digits)	18. DUNS Number (if applicable)	19. TX SOS Filing Number (if applicable)
20. Number of Employees			21. Independently Owned and Operated?
<input type="checkbox"/> 0-20 <input type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher			<input type="checkbox"/> Yes <input type="checkbox"/> No

SECTION III: Regulated Entity Information

22. General Regulated Entity Information (If New Regulated Entity" is selected below this form should be accompanied by a permit application)			
<input type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information <input checked="" type="checkbox"/> No Change** (See below)			
**If "NO CHANGE" is checked and Section I is complete, skip to Section IV, Preparer Information.			
23. Regulated Entity Name (name of the site where the regulated action is taking place)			

24. Street Address of the Regulated Entity: (No P.O. Boxes)							
	City		State		ZIP		ZIP + 4
25. Mailing Address:							
	City		State		ZIP		ZIP + 4
26. E-Mail Address:							
27. Telephone Number		28. Extension or Code		29. Fax Number (if applicable)			
() -				() -			
30. Primary SIC Code (4 digits)		31. Secondary SIC Code (4 digits)		32. Primary NAICS Code (5 or 6 digits)		33. Secondary NAICS Code (5 or 6 digits)	
34. What is the Primary Business of this entity? (Please do not repeat the SIC or NAICS description.)							

Questions 34 – 37 address geographic location. Please refer to the instructions for applicability.

35. Description to Physical Location:							
36. Nearest City		County		State		Nearest ZIP Code	
37. Latitude (N) In Decimal:				38. Longitude (W) In Decimal:			
Degrees	Minutes	Seconds		Degrees	Minutes	Seconds	

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form or the updates may not be made. If your Program is not listed, check other and write it in. See the Core Data Form instructions for additional guidance.

<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Industrial Hazardous Waste	<input type="checkbox"/> Municipal Solid Waste
<input type="checkbox"/> New Source Review – Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS	<input type="checkbox"/> Sludge
<input type="checkbox"/> Stormwater	<input type="checkbox"/> Title V – Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil	<input type="checkbox"/> Utilities
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Waste Water	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:


SECTION IV: Preparer Information

40. Name:	Michael G. Short, P.E.	41. Title:	Senior Engineer
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address
(830) 606-3913		(830) 625-2204	mshort@schultzgroupinc.com

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 9 and/or as required for the updates to the ID numbers identified in field 39.

(See the Core Data Form instructions for more information on who should sign this form.)

Company:	The Schultz Group, Inc.	Job Title:	Senior Engineer
Name (In Print):	Michael G. Short, P.E.	Phone:	(830) 606-3913
Signature:		Date:	2/12/10